CLEARWATER – ESTATE SERIES

71 1/2 x 42 3/16 x 23 1/4 (1820 x 1070 x 590) • Fax on Demand #1282

MODEL #AI7242R



AQUATIC ADVANTAGE

- National distribution
- 6 manufacturing facilities
- Private fleet
- Centralized customer service
- Field support
- 24-hour fax-on-demand

COLOR & TRIM OPTIONS

Stock	Premium
Almond (C, M)	Black (C, M)
Bone (C, M)	Cashmere (M)
Linen/Biscuit (C, M)	Mexican Sand (M)
Sterling Silver (C, M)	Red (M)
White (C, M)	Sandbar (M)

C = Color Matched Trim

M = Metallic Trim (Brushed Nickel, Chrome, Polished Brass)

FEATURES

- 8 hydrotherapy jets: pressure-flo (4), StressEaz neck and shoulder therapy (2), recessed rotary (2)
- 1.75hp pump
- Electronic on/off control
- Deep bathing well
- Acrylic grab bar
- Slip-resistant floor
- Pre-leveled ABS support base
- Quiet pad anti-vibration pump mount
- Center Front drain
- Lucite cast acrylic surface
- Limited lifetime warranty

OPTIONS

- Chromatherapy LED lighting
- 1.5kW inline maintenance heater
- Comfort pillow: Biscuit, Black, White
- Grab bar(s):
 Chrome, Oil Rubbed Bronze,
 Polished Brass, Brushed Nickel,
 Color matched (Biscuit,
 White, Clear)
- Cable drive waste & overflow: Chrome, Oil Rubbed Bronze, Polished Brass, Brushed Nickel, Color Matched (Biscuit, Bone, White)
- Factory installed rigid ABS tile flange
- Optional pump location
- Acrylic skirt: Color Matched







בם

2


TECHNICAL SPECIFICATIONS

Estate Series • Fax on Demand #1282


CLEARWATER

71 1/2 x 42 3/16 x 23 1/4 (1820 x 1070 x 590) inches (mm)





Deck Width 1 ½



Note: Tub Only units do not come standard with the Pre-leveled ABS Support Base.

FEATURES Ibs (kg)	Dimensional Tolerance \pm 3/8". Dimensions needed for site preparation should be measured from the	unit. Aquatic assumes no responsibility for preparatory work.
-------------------	--	---

L-

3

0 4


42 ¾


Type and Model #	Material	Jets	Pump	Heater	Controls	Drain	Pkg. Wt.
Whirlpool #AI7242R	Acrylic	8	1.75 HP	1.5 kw Inline (optional)	Electronic on/off	Center Front	247 (112)

DIMENSIONS	inches	(mm)
------------	--------	------

Width	Depth	Height	Skirt
Overall / Net	Overall / Net	Overall / Net	Height
71 ½ (1815)	42 ¾ (1070)	23 ¼ (590)	

PLUMBING DIMENSIONS inches (mm)





SUMP DATA inches (mm)

Capacity to	Min. Operating
Overflow	Capacity
gal (ltr)	gal (ltr)
90 (2285)	71 (269)

ELECTRICAL DATA

Component	Specification	Requirement	
Pump	1.75 HP; 12 AMP; 110 V	15 AMP; 110V, separate circuit; Class A GFCI	
Optional Heater	1.5 kW; 12.5 AMP; 110 V	15 AMP; 110V, separate circuit; Class A GFCI	

NOTES: 1) Where applicable, utilize cut-out templates packed with unit for deck cutouts.

2) 16 x 20 (405 x 510) minimum access required at pump/blower location(s).