

Printed from Grundfos CAPS [2011.05.069]

GRUNDFOS'

	$\sim$	Company name: - Created by: - Phone: -							
	DFOS®	Fax:		_					
GILONI		Date:		-					
Description	Value	Н					TP 40-	160/2, 6	0 Hz
Product name:	TP 40-160/2 U-G-A-BUBE U-G-A	(ft)				 Pumn		d = Wate	
	BUBE	40				Liquid	l temper	ature = 6	58 °F
Product Number:	91122108					Densi	ty = 62.4	4 lb/ft <sup>3</sup> _	
EAN number:	5700394584142	20							
		30							
Technical:	50.4110	_							
Actual calculated flow:	59.4 US gpm	20							
Resulting head of the pump:	35.7 ft	_							
Head max:	52.5 ft	10							
Shaft seal:	BUBE	10							
Maximum operating pressure	145 psi	-							
Pump version:	U		2 00		40			0/112	(
Matariala			0 20	30	40	50	60	Q(US	gpm)
Materials:	Cast iron	P2							
Pump housing: Impeller:		(HP)				_			
	EN-JL1040 ASTM 25 B	0.6							
	Stainless steel	0.4							
	DIN WNr. 1.4301	0.2							
	AISI 304	0.2							
Material code:	AISI 304 A	-	1			1	1	1	·
	7	- [			M12				
Installation:		-			П	Xi			
Maximum operating pressure	145 psi	- [		3/16	╶╫┵	u the			
Flange standard:	USA	- [		э Э		Si/	777T		
Connect code:	G	- [			ſ	Y			
Pipe connection:	1 1/2"	- 4"	4"			÷			
	1 1/2	-    T							
Liquid:		-				- ·	-		
Liquid temperature range	5 284 °F		$\neg$	•		619	7		
Liquid temp:	68 °F					4			
	·								
Electrical data:							<u>NPT 1</u>	/4	
Number of poles:	2	2 9/16"	T I		. 4	4			
Power (P2) required by pump	0.738 HP			5 7/8"	μE		⊒_f\		
Main frequency:	60 Hz		J	-   +	-#-				
- 1 2-					$\mu$	<u>∽#</u> ₽	Ø		
Others:		1 11/16"	5/8"	.116"	5	3/4"			
	Namreg	2 7/		2 11/16		11 1/2	2"		
Country code:		3 15/	-			_			

Printed from Grundfos CAPS [2011.05.069]

GRUNDFOS 2/3

