



### KITCHEN FAUCET

- Single handle, lever, pull-down kitchen faucet, 2-function wand.

### STANDARD SPECIFICATIONS

- Single handle, 2-function pull-down kitchen faucet for exposed mounting on two and three hole sinks.
- 13 3/16" (335mm) high, 8" (203mm) long, spout swings 360°.
- Lever handle. Control mechanism is rotating stainless steel ball type with replaceable non-metallic seats.
- Control shall return to neutral position when faucet is turned off.
- Pull-down wand operates in an aerated or spray mode via a toggle diverter.
- Integral check valves in sprayer assembly.
- Mounting wrench to assist in tightening mounting nut securely.
- Hose travels inside mounting shank so it will not interfere with deck edges.
- 1/2" - 14 NPSM threaded male inlet adapters.
- Model P188102LF-SD includes soap dispenser

### WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the Original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all Industrial, Commercial and Business applications.



### COMPLIES WITH

- ASME A112.18.1/CSA B125.1

Indicates compliance to ICC/ANSI A117.1

Verified compliant with 0.25% weighted average Pb content regulations.

