

HYDAPIPE®

Surface Mounted Shower System

- 1-801S-FSB: Standard length**
- 1-802S-FSB: Short length**

Pressure Balancing mixing valve integral service stops and adjustable stop screw to limit handle turn. Wall/hand shower with flexible 5' metal hose, in-line vacuum breaker, wall connection and flange. 30" slide bar for hand shower mounting. Attached soap dish and top cap. Stainless steel covering to be 18 gauge with #4 brush finish.


Modifications:

Add:

- Suffix 285:** Fre-Flo, all brass, fixed spray (no ball joint)
- Suffix 21:** Single supply, manual shut off, 4 arm handle
- Suffix 60:** Single supply, metering shut off
- Suffix 56:** Pressure Balance and metering combination

Delete:

- Suffix S:** If soap dish is not required



**SYMMONS PRODUCTS MEET
ANSI A112.18.1M, EPA '92
AND ALL KNOWN FLOW RATE
REQUIREMENTS.
Shower Heads and Hand Showers
2.5 GPM (9.5 L/min)**

Job/Location

.....

Engineer

.....

Contractor

.....

For ADA compliance (Americans with Disabilities Act) consult ADAAG or your state regulations for proper product choice and mounting locations.

Symmons Industries, Inc. ■ 31 Brooks Drive ■ Braintree, MA 02184
 (800) 796-6667, (781) 848-2250 ■ Fax (800) 961-9621, (781) 843-3849
 Website: www.symmons.com ■ Email: customerservice@symmons.com

©2003, 2008 Symmons Industries, Inc. Printed in U.S.A. ■ 043008

