Lindale[™] Technical Specification

Robe Hook

Y3103

Stock Numbers:


- Y3103BN Robe Hook **Brushed Nickel Finish**
- Y3103BRB Robe Hook Mediterranean Bronze Finish
- Y3103CH – Robe Hook Chrome Finish


Materials:

Robe Hook post is die cast from highest quality zinc alloy (Zamac). Casting is plated in Chrome, Brushed Nickel or Mediterranean Bronze.



Dimensions:





Installation Instructions:

- 1. Remove mounting plate from hardware pack.
- 2. Position the mounting plate on the wall at desired location with "UP" facing you. Mark hole locations.
- Drill 2 holes as marked using 5/16" drill bit. 3.
- Fold ends of the plastic toggle anchor together and insert into each hole 4. in the wall.
- Lightly tap anchors until flush with the wall. 5.
- 6. One at a time, insert plastic pin into each anchor and lightly tap to activate anchor. Remove pin and repeat on other anchor.
- 7. Place the mounting plate on the wall over the installed wall anchors with "UP" facing you.
- 8. Tighten screws.
- 9. Place decorative product over the mounting plate with setscrew facing down and tighten setscrew.

Cleaning Instructions:

To preserve the fine finish of this product, clean only with a soft damp cloth. Dry well. Do not use commercial or abrasive cleaners.

Stock Number: By Creative Specialties Robe Hook

25300 AL MOEN DRIVE • NORTH OLMSTED, OH 44070 CORPORATE HEADQUARTERS: (800) 321-8809 • FAX: (800) 848-6636 INTERNATIONAL: (440) 962-2000 • FAX: (440) 962-2726 CUSTOMER SERVICE (USA): 800-882-0116 • FAX: (888) 379-2720 WWW.CSI.MOEN.COM

©Copyright Creative Specialties International