



A Moen Incorporated Brand


Baystone™



NSF UPC®



Model:
CA42111 series



Two Handle Widespread Lavatory With Waste

DESCRIPTION

- Metal construction with various finishes identified by suffix
- 1/2" IPS shanks
- Designed to be installed on 8" to 16" centers
- Includes 50/50 pop-up type waste assembly
- Six (6) individual boxes per master carton

OPERATION

- Lever style handle
- Hot side: Turn counterclockwise to open (clockwise to close)
- Cold side: Turn clockwise to open (counterclockwise to close)
- Will operate with less than 5 lbs. of torque
- No grasping motion required to operate the faucet handle
- Feature red/blue hot/cold temperature indicators

FLOW

- Flow is limited to 1.5 gpm max. (5.7 L/min) at 60 psi

CARTRIDGE

- Ceramic disc technology
- Non-metallic, non-ferrous, and brass materials
- Single body construction for easy replacement

STANDARDS

- Third party certified to WaterSense® CSA B-125.1, ASME A112.18.1, and all applicable requirements referenced therein including NSF 61/9
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA for lever handles

WARRANTY – RESIDENTIAL, COMMERCIAL

- Ten year limited warranty against defects in materials and manufacturing workmanship
- Refer to the installation instructions enclosed with each CFG product or call 1-888-450-4910 for complete warranty information

NOTE:

- The spout is designed to be installed through 1" (26mm) minimum diameter hole. Valve body installs through 1-1/4" (32 mm) diameter holes.
- Maximum deck thickness: 1-1/2" (38 mm)

