

2623DPR | 300 SERIES



ELECTRIC VALVE ADAPTER 3/4" & 1" MODELS



MODELS

Model Description

2623DPR-.75	3/4" PVC valve adapter
2623DPR-1	1" PVC valve adapter
300-.75	3/4" glass-reinforced nylon valve adapter
300-1	1" glass-reinforced nylon valve adapter

SPECIFYING INFORMATION

2623DPR - XX	
MODEL	SIZE
2623DPR - 2623DPR PVC valve adapter	.75 - 3/4" size 1 - 1" size
Example: A 2623DPR, 1" PVC valve adapter = 2623DPR-1	

300 - XX	
MODEL	SIZE
300 - 300 glass-reinforced nylon valve adapter	.75 - 3/4" size 1 - 1" size
Example: A 300, 1" glass-reinforced nylon valve adapter = 300-1	

Note: Anti-siphon valve to be mounted above ground at least 6" above highest sprinkler head (consult local codes).

KEY FEATURES

2623DPR Series

- Converts Champion® brass anti-siphon valves to electric operation
- Internal and external bleed (flush mode)
- Rugged, double-beaded diaphragm
- Heavy-duty, corrosion- and UV-resistant PVC and stainless steel construction



300 Series

- Converts 3/4-inch and 1-inch Champion brass anti-siphon valves (models 300-.75 and 300-1) & 1-inch Irritrol manual valves to electric operation
- Internal and external bleed (flush mode)
- Rugged, double-beaded nylon-reinforced EPDM diaphragm
- Externally removable self-cleaning metering system
- Tough, glass-reinforced nylon, stainless steel and brass construction
- Ergonomic flow control allows precise flow adjustment and manual shutoff
- Buna-N valve seat seal
- Encapsulated injection-molded solenoid with a captive hex plunger
- Accepts OmniReg® modular pressure regulator

Champion® is a registered trademark of Arrowhead Brass and Plumbing, LLC.



SINGLE PIECE ADAPTERS MAKE CONVERSIONS SIMPLE



OPERATING SPECIFICATIONS

- Pressure range: 10-150 psi



ELECTRICAL SPECIFICATIONS

- Solenoid: 24 V AC
- Inrush volt-amp: 24 V AC - 9.6 VA
- Inrush current: .4 amp
- Holding volt-amp: 24 V AC - 4.8 VA
- Holding current: .2 amp

DIMENSIONS

- **2623DPR Series:** H: 6 3/4", W: 2 7/8"
- **300 Series:** H: 7 1/4", W: 4"

OPTIONAL ACCESSORIES

- (A) Recycled-water solenoid kit (RW60-KIT); purple solenoid with purple warning tag
- (B) DC latching solenoid (DCL)
Note: Maximum pressure for a valve that utilizes latching solenoid is 120 psi.
- (C) OmniReg® regulator (OMR-30)

* Optional accessories are field-installable.
Must specify separately if required.