



Model 501-TQ Model 502-TQ

Same as 501/502 Trip Levers except
QUICK ADJUST® has scale label on
the overflow pipe.
For most tubs 14"-16" high



ADA

See price list for complete item numbers and available options.

When ordering, please specify complete item number and any applicable option codes.

WATCO



For More Information Contact:
WATCO Manufacturing Company
1220 South Powell Road
Independence, MO 64057-2724
Ph. 816-796-3900 • FAX 816-796-0875
www.watcomfg.com

Always a step ahead

Tubular Brass

Trip Lever 501/502-TL

Trip Lever 501/502-TQ

For most tubs 14" - 16" high

Trip Lever 551/552-TL

For most tubs up to 24" high

**Sturdy 1.5" 17g and 20g Tubular Brass
Slip-Joint Assembly**

SPECIFICATIONS

FEATURES:

- Designed for heavy-duty use in hotels, motels, and rental property.
- Retainer plate for overflow elbow

APPROVALS (Quick Adjust®):

- Manufactured in compliance with ASME A112.18.2-2005/CSA B125.2-2005; and TIL MSE-051.

OPERATION:

- Move trip lever, located on overflow plate, up to close drain and down to open drain.

THREAD SIZE (Strainer Body and Drain Ell):

- 1½" – 11½ NPSM (Coarse Thread)
- 1.865" Major Diameter (outside thread diameter)
- 11.5 threads per inch

PIPING: ☐ 17g: 501 model ☐ 20g: 502 model

OPTIONS:

- Brass Ferrules (add code "F" to part number)
- Slip 'N Solder (no slip joints; add code "U")
- Special lengths available:
 - Overflow extension (add code "EXlength")
example: EX6
 - Drain extension (add code "Dlength") example: D4

FINISHES:

Tub Closure:	Trip Lever
CP- Chrome Plated	•
BB- Brushed Bronze	•
BN- Brushed Nickel	•
BZ- Oil-Rubbed Bronze	•
CB- Chrome Brushed	•
NP- Nickel Polished	•
PB- Polished Brass	•
WH- White	•
WI- Wrought Iron	•