



PRESFLO® (PF) Foot Actuated (FA) only

OPTIONS:

- Removable tail piece (add code "RT-2")
- Condensate Drain adaptor (add code "CD")

Model 510

Tub Closure, Washer, and Drain Ell only. See next page for available tub closures.

See price list for complete item numbers and available options. When ordering, please specify complete item number and any applicable option codes.



For More Information Contact:
WATCO Manufacturing Company
1220 South Powell Road
Independence, MO 64057-2724
Ph. 816-796-3900 • FAX 816-796-0875
www.watcomfg.com

Tubular Plastic

Model 500

For most tubs 14" - 16" high

Model 550

For most tubs up to 24" high

1.5" Tubular Plastic Bath Wastes Slip-Joint Assembly Now Coarse Thread

SPECIFICATIONS

FEATURES:

- · Metal strainer body for cast iron or plastic tubs
- Theft-resistant brass stopper
- Designed for heavy-duty use in hotels, motels, and rental properties
- Replaceable drip-proof Buna-N-Seal
- · Retainer plate for overflow elbow

APPROVALS:

 Manufactured in compliance with ASTM F 409-2002 and NSF/ANSI 14-2007; CSA standards B181.1 and B181.2.

PATENTS:

 U.S. Pat. 4,457,030; 4,720,877; 5,758,368; and Patents Pending

THREAD SIZE (Strainer Body and Drain Elbow):

- 1¹/₂" 11¹/₂ NPSM (Coarse Thread)
- 1.865" Major Diameter (outside thread diameter)
- 11.5 threads per inch

PIPING:

PVC

□ ABS

Roughing-In Dimensions

