



PIPE TOOLS & VISES
SINCE 1896

ADJUSTABLE WRENCHES

FEATURES

- Triple-coated nickel-chrome exterior finish to resist rust.
- Precision-ground jaw slides make for the **smoothest action**.

With hardened and tempered, forged alloy steel handles, phosphorous bronze springs and a triple-coated nickel-chrome exterior finish, Reed Adjustable Wrenches are constructed of the finest materials available. Precise, parallel jaw surfaces ensure good grip of nuts. 22° 30' angle allows for closest quarter work on hex nuts. Slip-resistant handle, lower cost, blackened adjustable wrenches of the same construction are also available.

CHROME

| Catalog No. | Item Code | Capacity | | Length | | Weight | |
|-------------|-----------|----------|----------------|--------|-----|--------|------|
| | | in-nom. | actual O.D. mm | in | mm | lbs | kg |
| CW4 | 02199 | 7/16 | 13 | 4 | 114 | 0.1 | 0.05 |
| CW6 | 02201 | 3/4 | 20 | 6 | 152 | 0.3 | 0.1 |
| CW8 | 02203 | 7/8 | 25 | 8 | 203 | 0.5 | 0.2 |
| CW10 | 02205 | 1 1/8 | 30 | 10 | 254 | 0.8 | 0.4 |
| CW12* | 02207 | 1 5/16 | 35 | 12 | 305 | 1.4 | 0.6 |
| CW15 | 02209 | 1 7/16 | 40 | 15 | 381 | 2.7 | 1.2 |
| CW18 | 02211 | 2 1/16 | 50 | 18 | 457 | 4.7 | 2.1 |
| CW24 | 02218 | 2 1/2 | 63 | 24 | 610 | 7.9 | 3.6 |

BLACKENED

| | | | | | | | |
|-------|-------|--------|----|----|-----|-----|-----|
| CWB6 | 02212 | 3/4 | 20 | 6 | 152 | 0.3 | 0.1 |
| CWB8 | 02213 | 7/8 | 25 | 8 | 203 | 0.5 | 0.2 |
| CWB10 | 02214 | 1 1/8 | 30 | 10 | 254 | 0.8 | 0.4 |
| CWB12 | 02215 | 1 5/16 | 35 | 12 | 305 | 1.4 | 0.6 |
| CWB15 | 02216 | 1 7/16 | 40 | 15 | 381 | 2.7 | 1.2 |
| CWB18 | 02217 | 2 1/16 | 50 | 18 | 457 | 4.7 | 2.1 |

*AWWA Approved for Tapping Contest.



✓ WHY REED?

Jaw slides are precision ground to provide smooth action.

COMFORT GRIP – ADJUSTABLE WRENCHES

FEATURES

- Same precision as Reed's adjustable wrenches with an **added grip** for more secure handhold.
- To increase **ergonomics**, Reed comfort grips are thicker and harder than most.

Use the best adjustable wrenches in new ways: a plastic dip coating gives ergonomic advantages of greater comfort and less hand fatigue. The plastic grip is also stickier than the steel handle, which combines with the larger diameter to make these wrenches easier to grip while working. Parallel jaw surfaces ensure good grip of nut. 22° 30' angle allows for closest quarter work on hex nuts.

| Catalog No. | Item Code | Capacity | | Length | | Weight | |
|-------------|-----------|----------|----------------|--------|-----|--------|-----|
| | | in-nom. | actual O.D. mm | in | mm | lbs | kg |
| CW6GRIP | 02906 | 3/4 | 20 | 6 | 152 | 0.3 | 0.1 |
| CW8GRIP | 02908 | 7/8 | 25 | 8 | 203 | 0.5 | 0.2 |
| CW10GRIP | 02910 | 1 1/8 | 30 | 10 | 254 | 1.0 | 0.5 |
| CW12GRIP | 02912 | 1 5/16 | 35 | 12 | 305 | 1.5 | 0.7 |

NOTE: These are comfort grips only, they are not made for electrical insulation.



✓ WHY REED?

Reed puts a thicker, harder, more comfortable, longer lasting coating on the smoothest, most exact adjustable wrenches available.

TORQUE WRENCHES FOR CAST IRON SOIL PIPE

FEATURES

- Ratcheting action is fast and maximum torque is preset.
- Guaranteed accurate to ±10%.

Torque Wrenches for Cast Iron Soil Pipe are engineered to provide recommended torque on No-Hub® soil pipe connections/fitting clamps. Torque wrenches can also loosen clamp screws and are designed for hand comfort. Ratcheting action is fast and maximum torque is preset. It releases with a click when reached for secure, leak free joints.

| Catalog No. | Item Code | Hex Size | Torque | | Length | | Weight | |
|-------------|-----------|----------|-------------|--------------|--------|-----|--------|-----|
| | | | inch pounds | Newton meter | in | mm | lbs | kg |
| TW516 | 02298 | 5/16" | 60 | 6.8 | 6 | 152 | 0.9 | 0.4 |
| TW38 | 02300 | 3/8" | 80 | 9.0 | 5.8 | 148 | 0.9 | 0.4 |

SOIL PIPE CUTTERS ON P. 14

