

ROMAX 3000

For leak-proof connections for copper and PEX pipe, the ROTHENBERGER line of press tools are easier, faster and safer than soldering! The ROMAX 3000 offers the user the ease of getting into tight spaces, but with capacity of up to 4".

The ROMAX 3000 jaws are interchangeable with standard manufacturer's systems. The tool comes equipped with an emergency shut-off switch and a safety latch which prevents unintentional opening of the jaw attachment. With its proprietary 18 volt, 3 amp Lithium battery, the ROMAX 3000 can complete 160 cycles on a single battery charge. Press cycle time is only 5-seconds, saving time and money!



• Light-weight in-line style tool is easy to maneuver

• 160 Press cycles per battery charge

• Kit includes tool, battery, charger, case and copper jaws 1/2" - 2"

Product Profile

FEATURES

- Light-weight in-line style tool is easy to maneuver
- Jaw head rotates 350° for use in tight spaces
- Quick 5 second cycle time
- 160 Press cycles per battery charge
- LED Work light allows for work in dark areas
- Emergency shut-off switch and safety latch
- Balanced weight distribution for fatigue-free work
- Easy to use; one trigger controls all tool functions
- Jaws are interchangeable with standard manufacturer's systems
- Long battery life; High-quality, powerful, long-lasting 18 volt, 3 amp Li-Ion
- Kit includes tool, battery, charger, case and copper jaws 1/2" - 2"

TECHNICAL DATA

Dimensions	24" x 21" x 9" (LxWxH)
Weight	59.10 lbs (kit)
Battery	18 volt, 3 amp, Lithium Ion
Battery Charge Time	approx 20 min
Pressing Capacity:	
Copper	4"
PEX	1-1/4"
Cycle Time	approx 5-6 seconds

Description	lb	No.
ROMAX 3000 Kit w/ 6 jaws	59.1	15800
ROMAX 3000 Kit, no jaws	21.6	15801
Li-Ion Battery	1.4	15810
Li-Ion Battery Charger	1.5	15811
1/2" Copper Jaw	4.4	15222X
3/4" Copper Jaw	4.4	15223X
1" Copper Jaw	4.4	15224X
1-1/4" Copper Jaw	4.4	15225X
1-1/2" Copper Jaw	4.4	15226X
2" Copper Jaw	4.4	15227X
3/8" PEX Jaw	4.4	15251X
1/2" PEX Jaw	4.4	15252X
5/8" PEX Jaw	4.4	15253X
3/4" PEX Jaw	4.4	15254X
1" PEX Jaw	4.4	15255X
1-1/4" PEX Jaw	5.4	15256X