

CONCENTRIC PUMPS



HIGH EFFICIENCY CONCENTRIC PUMP

OPERATES IN WATER RESERVOIRS OF 1/2" TO 4" LOW DRAW / LOW RECOVERY

PUMP FLOW RATE PERFORMANCE

120 VAC, 60 HZ

GALLONS PER HOUR 1 FT. HEAD HEIGHT

EVAPORATIVE COOLER RETROFIT PUMP FOR USE WITH SPECIFIED EVAPORATIVE COOLERS ONLY BK91

ONE YEAR WARRANTY

336 pumps per pallet

| DIAL P/N | MODEL | CFM / GPH* | VOLTS | COLOR | APPROVAL** | CTN QTY | CTN WT |
|----------|-------|------------|-------|-------|------------|---------|--------|
|----------|-------|------------|-------|-------|------------|---------|--------|

RESIDENTIAL CONCENTRIC



| | | • UL Classified | | • Flame Retardant Motor Housing | | • Heavy Duty Motor | |
|--------|------------------------|-------------------------------|------|---------------------------------|-------|--------------------|------|
| | | • Auto Reset Thermal Overload | | • Grounded 3 Prong Plug | | • Low Level Pump | |
| ▲ 1150 | UL5500 Premium Pump | 5,500 / 240 | 115V | Black | UL/UR | 12.0 | 24.5 |
| ▲ 1175 | UL7500 Premium Pump | 7,500 / 360 | 115V | Blue | UL/UR | 12.0 | 28.8 |
| ▲ 1195 | UL11000 Premium Pump | 11,000 / 420 | 115V | Green | UL/UR | 12.0 | 33.8 |
| ▲ 1279 | UL7500-2 Premium Pump | 7,500 / 360 | 230V | Orange/Black | UL/UR | 6 | 14.1 |
| ▲ 1286 | UL11000-2 Premium Pump | 11,000 / 420 | 230V | Orange/Black | UL/UR | 6 | 16.7 |

COMMERCIAL CONCENTRIC



| | | • UL Classified | | • Molded 3 Prong Plug | | • Low Level Operation | |
|--------|------------------|---------------------------------|------|---------------------------------|-------|-----------------------|------|
| | | • Auto Reset Thermal Overload | | • Grounded Round SJT Power Cord | | | |
| | | • Flame Retardant Motor Housing | | • Heavy Duty Motor | | | |
| ▲ 1414 | UL7500LA Pump | 7,500 / 375 | 115V | Black | UL/UR | 12 | 31.5 |
| ▲ 1424 | UL11000LA Pump | 11,000 / 440 | 115V | Black | UL/UR | 12 | 35.6 |
| ▲ 1429 | UL11000-2LA Pump | 11,000 / 440 | 230V | Orange/Black | UL/UR | 6 | 16.5 |

INDUSTRIAL CONCENTRIC



| | | • Same features as Commercial Pumps | | • 6 Ft Grounded Round SJT Power Cord | | • Requires 5/8" Or 3/4" I.D. Pump Hose | |
|--------|------------------|-------------------------------------|------|--------------------------------------|-------|--|------|
| ▲ 1387 | UL15000LA Pump | 12 to 21,000 / 505 | 115V | Black | UL/UR | 6 | 17.4 |
| ▲ 1400 | UL25000LA Pump | 15 to 25,000 / 580 | 115V | Black/Grey | UL/UR | 6 | 19.0 |
| ▲ 1396 | UL15000-2LA Pump | 12 to 21,000 / 505 | 230V | Orange/Black | UL/UR | 6 | 17.5 |
| ▲ 1402 | UL25000-2LA Pump | 15 to 25,000 / 580 | 230V | Orange/Grey | UL/UR | 6 | 17.9 |

CONCENTRIC REPLACEMENT FOR MASTERCool® / ARCTIC CIRCLE®



| | | • Replacement Pumps for Mastercool® (using 8" and 12" Media) and Arctic Circle® Coolers | | • UL Classified | | | |
|--------|-----------------|---|------|---|-------|---|------|
| | | • Exceeds OEM Pump Performance and Longevity | | • Includes Mesh Basket & Mounting Bracket | | | |
| ▲ 1442 | MC8500UL Pump | 4 to 8,500 / 360 | 115V | Tan | UL/UR | 6 | 14.0 |
| ▲ 1443 | MC8500-2UL Pump | 4 to 8,500 / 360 | 230V | Orange/Black | UL/UR | 6 | 15.7 |

*Gallons per hour flow rate at 1 foot head height.

**UL Classified Replacement Pump (UL) and UL Recognized Pump (UR)

▲UPC Items