

FLAIR-IT FITTINGS

PLUMBING

L

In Section L:	Fresh Water Line	Filters	Winterizing	Pumps	Faucet & Shower	Sink & Drain	Holding Tanks	Drain Valves & Fittings	Drain Hose	Chemicals & Toilets
---------------	------------------	---------	-------------	-------	-----------------	--------------	---------------	-------------------------	------------	---------------------

FLAIR-IT FITTINGS, continued

Order #	Mfr. #	Dim. A	Dim. B	Dim. C
FLAIR-IT FEMALE ADAPTERS				
24570	#06841	1/2" FL	1/2" FPT Adapter	
24571	#06847	3/4" FL	3/4" FPT Adapter	
24572	#06851	1/2" FL	3/8" FPT Adapter	
FLAIR-IT SWIVEL STRAIGHT TERMINATION FITTINGS				
				Flair-It to faucet connection.
24507	#06874	3/8" FL	1/2" FPT BSP Swivel	
24508	#06873	1/2" FL	1/2" FPT BSP Swivel	
24584	#06856	1/2" FL	3/4" FPT	
FLAIR-IT PLUG-CAP				
				Used for capping off a Flair-It fitting.
24588	#06859	3/8" FPT Cap		
24516	#06860	1/2" FPT Cap		
24517	#06861	3/4" FPT Cap		
FLAIR-IT GARDEN HOSE ADAPTER				
24585	#06866	1/2" GHP	3/4" FGH Swivel	
FLAIR-IT BALLCOCK ADAPTER				
				Flair-It connection to water closet.
24586	#06865	1/2" FL	3/4" BCT Swivel	
24587	#06869	3/8" FL	3/4" BCT Swivel	
FLAIR-IT DRAIN OR ANGLE STOP VALVE				
				Flair-It connections drain and angle valve.
24515	#06884	1/2" FL	1/2" FL	
24604	#06882	3/8" FL	3/8" FL	
FLAIR-IT ANGLE STOP VALVE				
				A 90° valve with flare connections both ends.
24514	#06885	1/2" FL	1/2" FL	
24605	#06883	3/8" FL	3/8" FL	
FLAIR-IT THREE-WAY BYPASS VALVES				
				24937 is an in-line 3-way valve; 24938 is a water heater 3-way valve.
24937	#06910	1/2" FL	1/2" FL	1/2" FL
24938	#06912	1/2" FL	1/2" MPT	1/2" FL
FLAIR-IT STRAIGHT STOP VALVE				
				Flair-It connections in-line valve.
24592	#06879	3/8" FL	3/8" FL	
24512	#06880	1/2" FL	1/2" FL	
FLAIR-IT ECONOMY 10-PACKS OF FITTINGS				
24942	#06435 (BAG 10)	1/2"	Saniprene Seals, 10/Bag	
FLAIR-IT TURNING BEND SUPPORT				
26119	#10500	1/2"	Turning Bend Support	
FLAIR-IT INLET TEE & BRASS VALVE ASSEMBLY				
				For refrigerator installation.
Tee (1/2" P x 1/2" P x 1/8" FPT) is used to install refrigerators with polybutylene pipe. Connection to brass valve (1/4" x 1/8" ID NSF listed). To seal the connection between the valve and the tee, use teflon tape or liquid teflon. Do not use pipe dope or other materials not specifically recommended by the mfr. Threaded fitting must not be overly tightened. Every installation must be successfully leak-tested according to the industry's standards before use.				
25445	#05834		Inlet Tee/Brass Valve Assembly	

