




# NO LEAD Yard Hydrants - Frost Proof



## NO LEAD Series Frost Proof Yard Hydrant Features:



**CLAYTON MARK**®



- Fully frost proof, shut-off valve below frost line.
- Heavy cast iron head with 3/4" brass discharge connection and bucket hook. All weather **powder coated** finish.
- Can be padlocked.
- Heavy, galvanized steel, corrosion resistant, 1" stand-pipe.
- Galvanized carbon steel connecting rod. Stainless steel operating rod.
- Long lasting Buna-N rubber plunger with solid brass core.
- Integral valve seat cast into brass valve body. 3/4" FPT connection with double bypass bottom valve for superior flow, less risk of debris blockage.
- 1/8" FPT back drain hole.
- Rated to 80 PSI, adjustable. See page 2.18 for adjustment procedure.
- Packed securely in individual heavy weight carton.
- Independent lab tested.
- Lead Free. **Third party certified to NSF/ANSI 372.**

Part Number	Bury Depth	Overall Length	Weight (lbs)
54511NL	1	42"	12.4
54512NL	2	54"	15.2
54513NL	3	66"	17.8
54514NL	4	78"	21.0
54515NL	5	90"	22.3
54516NL	6	102"	26.2
54518NL	8	126"	30.7