

NSF Infrared Thermometer w/ Folding Probe

INF145 UPC: 053533508208

Functions

- 8:1 Distance-to-spot ratio
- Temperature range: -76° to 662°F (-60° to 350°C)
- Temperature probe

Features

- HACCP Zone display
- Circular laser targeting
- Dual display
- Selectable emissivity level: 0.1 to 1.0
- Min/Max/Hold

Includes

Batteries 2 (AAA)
Manual

Safety standards

CE Conformity
NSF

Warranty

1-Year limited warranty

Support materials

- Manual: online
- Data sheet: online



Dual Input Logging Thermometer

DT302 UPC: 05353350562

Functions

- Dual thermocouple input
- J-Type: -346° to 2192°F (-210° to 1200°C)
- K-Type: -328° to 2498°F (-200° to 1370°C)
- T-Type: -418° to 752°F (-250° to 400°C)
- E-Type: -238° to 1832°F (-150° to 1000°C)
- Differential T1-T2

Features

- Data logging
- 9,999 Memory positions
- USB interface (software included)
- Thermocouple temperature offset
- Min/Max/Avg/Hold
- Probe storage
- Accepts J, K, T and E type probes

Warranty

3-Year limited warranty

Includes

K-Type temperature probes 2 (ATT39)
Batteries 2 (AAA)
Quick Start Guide
Manual

Safety standards

IP67
CATI
CE Conformity



Quad Input Logging Thermometer

DT304 UPC: 05353350563

Functions

- Quad thermocouple input
- J-Type: -346° to 2192°F (-210° to 1200°C)
- K-Type: -328° to 2498°F (-200° to 1370°C)
- T-Type: -418° to 752°F (-250° to 400°C)
- E-Type: -238° to 1832°F (-150° to 1000°C)
- Differential T1-T2 and T3-T4

Features

- Data logging
- 9,999 Memory positions
- USB interface (software included)
- Thermocouple temperature offset
- Min/Max/Avg/Hold
- Probe storage
- Accepts J, K, T and E type probes

Warranty

3-Year limited warranty

Includes

K-Type temperature probes 4 (ATT39)
Batteries 2 (AAA)
Quick Start Guide
Manual

Safety standards

IP67
CE Conformity
CATI
CSA 22.2



Dial Pocket Thermometers



T125/3	05353370005	1-3/4" Dial Thermometer 25° to 125°F
T160	05353370007	1" Dial Thermometer -40° to 160°F
T160/3	05353370008	1-3/4" Dial Thermometer -40° to 160°F
T220	05353370011	1" Dial Thermometer 0° to 220°F
T220/3	05353370012	1-3/4" Dial Thermometer 0° to 220°F
TC100	05353370019	1" Dial Thermometer -10° to 100°C
TC70	05353370021	1" Dial Thermometer -40° to 70°C

Temperature Probes

				
ATT6 05353360155 J-Type 4' Standard with oven clip	ATT19 053533603699 Temperature Probe, J-Type Oven Clip	ATT26 05353360123 J-Type liquid probe	ATT27 05353360124 J-Type bead probe	ATT29 05353360126 K-Type fiberglass coated probe
				
ATT29A 05353360222 K-Type fluoroplastic coated probe	ATT29APACK 05353360639 K-Type fluoroplastic coated probe (10 pack)	ATT30 05353360129 J-Type 8" Liquid probe	ATT36 05353360132 K-Type 8" Surface probe w/ handle	ATT39 05353360596 K-Type probe w/ wire wrap handle
				
ATT55A 053533603989 Thermistor probe, liquid	ATT56A 053533603996 Thermistor probe, air	ATT62 053533602272 Thermistor probe, sealed 15 ft.	ATT70 05353360334 K-Type to input jack adapter	ATT71 05353360334 K-Type to input jack temperature probe
				
ATT100 05353360235 K-Type 6" liquid probe	ATTEXT 05353360612 K-Type 10' extension	ATTPC3 05353360694 K-Type pipe clamp adapter (clamp style)	ATTPC4 05353350840 K-Type Pipe Clamp Probe (grip style)	

Test Leads

					
AAC 05353360075 Alligator Clips, Slip-On	AAC3 05353360386 Alligator Clips, Screw-On	ATLTX 05353360647 Modular Test Lead Extension Wire	ATL1 05353360641 Modular Lead Tips-Standard (ATLTX Required)	ATL2 05353360642 Modular Lead Tips-Alligator (ATLTX Required)	ATL3 05353360643 Modular Lead Tips-Grabber (ATLTX Required)
					
ATL5 05353360645 Modular Lead Tips-Back Probe (ATLTX Required)	ATL6 05353360646 Modular Lead Tips-Piercing (ATLTX Required)	ATL55 05353360204 Test Leads (Standard)	ATL57 05353360662 Silicone Test Leads	ATL301KIT 05353360571 Test Lead Kit	ATLBPk 05353360649 Back Probe Test Lead Kit