
TAG:	

Surgical Sink Faucet

Architect/Engineering Specifications:

8" wall mount mixing faucet with polished chrome plated brass body, 5 3/4" swivel/rigid gooseneck with stream regulator outlet, compression cartridges with spring checks, 4" wrist action handles and 1/2" NPT female inlets. Certified to ASME A112.18.1/CSA B125.1, NSF 61-Section 9 and NSF 372. Meets ADA ANSI/ICC A117.1 requirements.



5 3/4" [145mm] 10 13/16" [274mm] 2 3/8" [61mm]

Features & Benefits:

- 8" wall mount mixing faucet with polished chrome plated brass body
- 5 3/4" swivel/rigid gooseneck
- · Lock washer provided for rigid application
- · Stream regulator outlet, Series 1
- Quarter-turn Eterna compression cartridges w/ spring checks to prevent cross flow of water
- 4" wrist action handles w/ color coded indexes
- 1/2" NPT female eccentric inlets w/ Ø2" flanges
- Adjustable centers from 7 3/4" to 8 1/4"
- Material: Polished chrome plated brass body & tubular spout and chrome plated metal handles

Product Compliance:

- ASME A112.18.1 / CSA B125.1
- NSF 61 Section 9
- NSF 372 (Low Lead Content)
- ANSI A117.1 (ADA)

Warranty: One Year (Limited)

LOW LEAD COMPLIANT

Performance Data:

Pressure: 20 - 125 psiTemperature: 40°F - 140°F

• Flow Rate: 23.09 GPM @ 60 psi



Optional Outlets (Series 1 / VR Series 6)

		Non-Aerated		VR Non-Aerated	Optional Handles	
GPM	Aerated	(Laminar)	VR Aerated	/R Aerated (VR La	(VR Laminar)	☐ 4" Wrist Action (Standard)
0.35	N/A	□ B-0199-01-N035	N/A	□ B-0199-06-N035	□ Lever	
0.5	N/A	□ B-0199-01-N05	N/A	□ B-0199-06-N05	□ 4-Arm	
1.0	□ B-0199-01-F10	N/A	□ B-0199-06-F10	N/A	Optional Cartridges With Checks	
1.5	□ B-0199-01-WS	□ B-0199-29	□ B-0199-06-WS	□ B-0199-29VR		
2.2	□ B-0199-01	□ B-0199-21	□ B-0199-06	□ B-0199-21-VRF	☐ Quarter-Turn Cerama w/ Check Valve	
					□ Quarter-Turn Eterna w/ Spring Check (Standard)	







T&S BRASS AND BRONZE WORKS, INC.

