

Wall Mounted Slide/Grab Bar & Hand Shower with non-positive shut-off, T-600B-V Series Specification Submittal

Feature Highlights

- ADA compliant wall mounted slide/grab bar with adjustable slide for hand shower cradle
- Hand shower wand #ADACHS-WHT (for T-600B-V series only), non-positive shut-off, single function, standard 5 foot flexible metal hose and in-line vacuum breaker
- Grab bar available in 24, 36 and 48 inch length made in brushed stainless steel
- Standard flow rate is 2.5 gpm (9.5 L/min)
 Optional lower flow rate restrictor available
- 90 degree wall mounted water supply elbow in chrome

Model Numbers

□ T-600B-24-V
24 inch slide/grab bar with hand shower
 □ T-600B-24-V-NE
24 inch slide/grab bar with hand shower,
without wall mounted water supply elbow
 □ T-600B-36-V
36 inch slide/grab bar with hand shower
 □ T-600B-36-V-NE
36 inch slide/grab bar with hand shower,
without wall mounted water supply elbow
 □ T-600B-48-V
48 inch slide/grab bar with hand shower
 □ T-600B-48-V-NE
48 inch slide/grab bar with hand shower,

without wall mounted water supply elbow





Options / Modifications

Append appropriate -suffix to model number

- □ CG -1.5 1.5 (5.7 L/min) flow rate restrictor
- □ -2.0 2.0 (7.6 L/min) flow rate restrictor
- □ -72 72 inch flexible metal hose in place of 60 inch length
- □ -R 60 inch white vinyl hose in place of flexible metal hose
- □ -R72 72 inch white vinyl hose in place of flexible metal hose
- □ -QD Quick disconnect on water supply end of hand shower hose

Finish Options / Modifications

Append appropriate -suffix to model number

- -Brushed stainless steel grab bar (standard)
- -White hand shower wand (standard)
- -Chrome wall elbow (standard)

Compliance

- -ASME A112.18.1/CSA B125.1
- -WaterSense 1.5 gpm and 2.0 gpm





Warranty

- Limited Lifetime to the original end purchaser in consumer installations
- 5 years for commercial installations

