
PEERLESS

6" (152 mm) 1 7/16" 2" (36 mm) (51 mm) Max. Desk Thickness 4 X 1 5/16"~1 1/2 (33~38 mm) 6 1/2" Hole Size (165 mm) 8" (203 mm) 10" . (254 mm) 8 7/8" Min. 2 1/2" (64 mm) (225 mm) Clearance to Back Splash 360° swing spout Recommended 7 1/2" (190 mm) (102 mm) | 5/16"~1 1/2" (33~38 mm) Hole Size 1 7/8" (47 mm) Max. Desk Thickness 1/2"-14 NPSM

P188501LF



KITCHEN FAUCET

Single Handle Deck Mount

STANDARD SPECIFICATIONS:

- Max. flow rate 1.8 gpm @ 60 psi, 6.8 L/min @ 414 kPa
- Two or four hole mount
- Spout rotates 360°
- 1/2"-14 NPSM threaded male inlet shanks
- Replaceable rotating ball valve with replaceable non-metallic inlet seats

WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes; or, for commercial users, for 5 years from the date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or for commercial users, for 1 year from the date of purchase. No warranty is provided on batteries.

COMPLIES WITH:

ASME A112.18.1 / CSA B125.1 Indicates compliance to

- ICC / ANSI A117.1
- Verified compliant with 0.25% weighted average Pb content regulations.