

ELECTRIC POWER TOOLS

WIRE WHEELS & BRUSHES

Accessories

Fill Materials


Carbon Steel: Excellent fatigue resistance and fast cutting qualities. Available in cup end and wheel brush configurations.

Stainless Steel (Type 302): Highly corrosion-resistant and should be used where contamination or after-rust is a problem, such as brushing aluminum or stainless steel materials. Particularly suited for nuclear work, naval, aircraft and aerospace construction. Available in cup end and wheel brush configurations.



Crimped:  Provides a continuous brushing action and a relatively fine finish.



Straight:  Used in knot construction to provide maximum impact action for severe applications.



Standard Twist: Has slight tuft at the end of the wire knot, providing some flexibility for use on irregular surfaces.



Cable Twist: The wire is tightly twisted to the end of the knot, providing very aggressive cutting action.



Stringer Bead Twist: The wire is very tightly twisted to the end of the knot, creating a very narrow face. Primarily used for weld cleaning.

Knot Style Wire Cup Brush



Carbon Steel .020" (20 knots)

302 Stainless Steel .020" (20 knots)

Carbon Steel .023" (24 knots)

Diam.	Arbor	Qty Per Pkg.	Max RPM	Part #
2-3/4"	M10 x 1.25	1	14,000 RPM	743201-5A
2-3/4"	M10 x 1.5	1	14,000 RPM	743223-A
2-3/4"	5/8" -11	1	14,000 RPM	743209-A
2-3/4"	M10 x 1.25	1	14,000 RPM	743204-A
2-3/4"	5/8" -11	1	14,000 RPM	743209-B
4"	5/8" -11	1	10,000 RPM	743208-0A
6"	5/8" -11	1	6,600 RPM	743206-A

Crimped Style Wire Cup Brush



Carbon Steel .014"

Carbon Steel .020"

Carbon Steel .020"

3"	M10 x 1.25	1	14,000 RPM	743201-4
3"	M10 x 1.5	1	14,000 RPM	743224-A
3"	5/8" -11	1	14,000 RPM	743205-6
4"	5/8" -11	1	9,000 RPM	743207-2
6"	5/8" -11	1	6,600 RPM	743206-B

Wire Bevel Wheel Brush



Carbon Steel .0118"

3-3/8"	M10 x 1.25	1	12,500 RPM	743203-0
3-3/8"	M10 x 1.5	1	12,500 RPM	743228-A
3-3/8"	5/8" -11	1	12,500 RPM	743210-A

Stringer Bead Wheel Brush – Twist Wire



Carbon Steel .020" 3/16" Face Width

302 Stainless Steel .020" 3/16" Face Width

4"	M10 x 1.25	1	20,000 RPM	743203-5A
4"	M10 x 1.5	1	20,000 RPM	743225-A
4"	5/8" -11	1	20,000 RPM	743213-A
5"	5/8" -11	1	12,500 RPM	743216-A
6"	5/8" -11	1	9,000 RPM	743203-6B
4"	M10 x 1.25	1	20,000 RPM	743204-B
4"	5/8" -11	1	20,000 RPM	743213-B

Knot Wire Wheel Brush – Full Cable Twist



Carbon Steel .020" 24 knots

302 Stainless Steel .020" 24 knots

4"	M10 x 1.25	1	20,000 RPM	743203-4B
4"	M10 x 1.50	1	20,000 RPM	743226-A
4"	5/8" -11	1	20,000 RPM	743211-A
5"	5/8" -11	1	12,500 RPM	743217-A
4"	M10 x 1.25	1	20,000 RPM	743215-A
4"	5/8" -11	1	20,000 RPM	743214-A

Knot Wire Wheel Brush – Standard Twist



Carbon Steel .014" 24 knots

Carbon Steel .020" 24 knots

4"	M10 x 1.25	1	20,000 RPM	743203-4C
4"	M10 x 1.5	1	20,000 RPM	743227-A
4"	5/8" -11	1	20,000 RPM	743212-A