



OFFSET PUMP

OPERATES IN WATER RESERVOIRS OF 1/2" TO 4" LOW DRAW

PUMP FLOW RATE PERFORMANCE

120 VAC, 60 HZ

GALLONS PER HOUR
1 FT. HEAD HEIGHT

290	250	225
UL10000	UL7000	UL5000

90 DAY WARRANTY

336 pumps per pallet

DIAL P/N	MODEL	CFM / GPH*	VOLTS	COLOR	APPROVAL**	CTN QTY	CTN WT
----------	-------	------------	-------	-------	------------	---------	--------

RESIDENTIAL OFFSET

<ul style="list-style-type: none"> • Auto Reset Thermal Overload • Flame Retardant Motor Housing 		<ul style="list-style-type: none"> • Molded 3 Prong Plug & Grounded Cord • Low Level Pump 					
▲1055	UL5000 Offset Pump	5,000 / 225	115V	Maroon	UL/UR	12	22.6
▲1075	UL7000 Offset Pump	7,000 / 250	115V	Tan	UL/UR	12	24.6
▲1095	UL10000 Offset Pump	10,000 / 290	115V	Gray	UL/UR	12	26.5



OFFSET REPLACEMENT FOR MASTERCOOL® / AEROCOOL® / COMFORTCOOL™

<ul style="list-style-type: none"> • Optional Bleed Tee • Auto Reset Thermal Overload • Flame Retardant Motor Housing 		<ul style="list-style-type: none"> • Heavy Duty Motor • Molded 3 Prong Plug • Grounded Power Cord 			<ul style="list-style-type: none"> • Low Level Pump • UL Classified • One Year Warranty 		
▲1438	UL 115V Pump for Single Inlet Coolers	8" Media/ 290	115V	Gray	UL/UR	6	12.7
▲1440	UL 230V Pump for Single Inlet Coolers	8" Media/ 290	230V	Gray	UL/UR	6	15.1



Recommended for MasterCool® EC 430/440, EC 630/640, IM 450/460, IM 650/660; AeroCool® 4400/4800, ACD 5800/6800; UltraCool® 4500/6500; ComfortCool™ SI 5000/7000.

*Gallons per hour flow rate at 1 foot head height.

**UL Classified Replacement Pump (UL) and UL Recognized Component Pump (UR).

