

**FS2701**

### 2,500 RPM SCREWDRIVER 6-Stage Torque Adjustment

- Powerful 6.0 AMP motor with 0-2,500 RPM to handle the most challenging applications
- Less weight (only 4.0 lbs.) with precision balance for ultimate user comfort
- Built-in L.E.D. light illuminates the work area for greater productivity in low-light applications
- Steel-reinforced belt clip for user convenience and increased durability
- Directional air-flow vents channel the tool's air output away from the user's face
- Large trigger with lock-on button located mid-handle for operator convenience

**Model FS2701 Includes:** 5/16" Magnetic Nutsetter, 2-5/8" (784804-5)

Bit Type	1/4" Hex
No Load Speed (variable speed)	0 - 2,500 RPM
AMPS	6
Overall Length	11-1/8"
Net Weight	4 lbs.
Shipping Weight	3.306 lbs.

**6844**

### AUTOFEED SCREWDRIVER "Tool-less" Screw Depth Adjustment

- High torque for driving screws up to 2-15/16" long
- Adjustable stopper base can be set for different screw lengths
- Ergonomic in-line D-handle design for driving control
- Silent clutch for reduced maintenance and quiet operation
- Belt clip for attaching to belt or holster
- "Tool-less" screw depth adjustment for easy depth settings

**Model 6844 Includes:** #2 Phillips Power Bit, 5/pk (B-10475), Tool Case

Bit Type	1/4" Hex
Collated Screw Capacity	1-3/4" - 2-15/16"
No Load Speed	3,000 RPM
AMPS	4.3
Overall Length	17-1/4"
Net Weight	4.5 lbs.
Shipping Weight	11.02 lbs.

**NEW XRF02**

### 18v LXT® AUTOFEED SCREWDRIVER KIT Ideal for Hanging Drywall

- Makita-built 4-pole motor delivers superior fastening speed with 4,000 RPM
- High collated screw capacity range: 1" to 2-1/8"
- Screw guide prevents screw strip tangling and can fold against the autofeed housing for easy storing
- Rugged aluminum dust-proof autofeed housing provides smooth sliding action

**Model XRF02 Includes:** (2) 18v LXT® Lithium-Ion 3.0Ah Battery (BL1830), 18v Lithium-Ion Rapid Optimum Charger (DC18RC), #2 Phillips Power Bit, 2/pk (B-10481), Square Power Bit, 1/pk (784645-9), Tool Bag

**Model XRF02Z Includes:** Tool Only; Battery and Charger not included

Bit Type	1/4" Hex
Collated Screw Capacity	1" - 2-3/16"
No Load Speed	4,000 RPM
Battery	18v LXT® Lithium-Ion
Overall Length	16-3/4"
Net Weight (with battery)	5.1 lbs.
Shipping Weight	13.4 lbs.

**6952**

### 1/4" IMPACT DRIVER Fast 0-3,200 RPM and High Torque of 88.5 ft.lbs.

- Variable speed trigger (0 - 3,200 RPM) for easy operation
- Impact resistant aluminum housing for gear protection and durability
- Compact and lightweight (3.1 lbs.) for both vertical and horizontal applications
- Rubberized pistol grip provides increased comfort on the job
- Dual ball bearings for longer tool life
- 2.3 AMP motor for high performance (0-3,100 IPM)

**Model 6952 Includes:** Belt Clip (324284-9), Tool Case

Capacity:	Hex Drive (1/4")
Impacts Per Minute (variable speed)	0 - 3,100 IPM
No Load Speed (variable speed)	0 - 3,200 RPM
Maximum Torque (ft.lbs./N•m)	120 ft.lbs./162 N•m
AMPS	2.3
Overall Length	9"
Net Weight	3.1 lbs.
Shipping Weight	6.6 lbs.

**6953**

### 1/2" IMPACT WRENCH W/ DETENT PIN ANVIL 0 - 3,000 RPM and Max Torque of 110 ft.lbs.

- All metal hammer casing to withstand all environments
- Externally accessible brushes for easy replacement
- 0 - 3,000 impacts per minute for maximum efficiency
- Compact length for easier handling and operator control
- Convenient belt clip attaches to both sides of the tool
- Ideal for garage door installers, metal framers and deck builders

**Model 6953 Includes:** Belt Clip (324284-9), Tool Case

Capacity:	Square Drive (1/2")
Impacts Per Minute (variable speed)	0 - 3,000 IPM
No Load Speed (variable speed)	0 - 3,000 RPM
Maximum Torque (ft.lbs./N•m)	110 ft.lbs./150 N•m
AMPS	2.5
Overall Length	9-1/8"
Net Weight	3.3 lbs.
Shipping Weight	6.6 lbs.

**TW0200**

### 1/2" IMPACT WRENCH W/ DETENT PIN ANVIL Max Torque of 150 ft.lbs.

- Variable speed 0 - 2,200 RPM for controlled fastening
- Efficient impact system with less vibration
- Externally accessible brushes for easy replacement
- Precision gearing with ball and needle bearing construction for smooth and efficient power transmission
- Compact and lightweight (4.9 lbs.) for use in close quarters
- Impact-resistant aluminum gear case with rubber boot for increased durability

**Model TW0200 Includes:** Belt Clip (324284-9), Tool Case

Capacity:	Square Drive (1/2")
Impacts Per Minute (variable speed)	0 - 2,200 IPM
No Load Speed (variable speed)	0 - 2,200 RPM
Maximum Torque (ft.lbs./N•m)	150 ft.lbs./200 N•m
AMPS	3.3
Overall Length	9-7/8"
Net Weight	4.9 lbs.
Shipping Weight	8.8 lbs.

## Screwdriver Accessories

### Nose Cone

Model	Part #
FS2200, FS4200/A/TP, FS6200/TP, LXSFO1	195542-8

### Nose Cone

Model	Part #
6825, 6823N, 68245N/NA	151726-8
6821, 6826	152483-1
XDT01, XDT08, XDT04, XDT09	194633-2
FS2200, FS4200/A/TP, FS6200/TP, XSF03	158876-0

### Locator

Size	Model	Part #
1/4"	6826N	152821-7
5/16"		152822-5
5/16"	FS2500	450967-6
3/8"	6826	152823-3
For Power Bits	6827	322120-3

### Power Cords

Length	Model	Part #
8.4'	FS2200, FS2500, FS4200, FS6200	664064-4
50'	FS4200TP, FS6200TP	699037-8
50'	FS4200A	660066-8-50

## Drywall Cut-Out Tool Accessories

### Industrial Cut-Out Bits

Description	Size	Qty./Pkg.	Model	Part #
Drywall/ Guide Tip	1/8"	10	3706, XOC01	193452-3
Window/ Door	1/4"	1		193453-1

### Circular Guide

Description	Model	Part #
Cleaner, more precise circle/arc cuts up to 14" in diameter	3706, XOC01	193454-9

### Collet Cone and Adaptor

Description	Size	Model	Part #
Collet Cone	1/4"		763608-8
Collet Cone	1/8"	3706	763660-6
Collet Cone	1/4"		763676-1
Collet Cone	1/8"	XOC01	763677-9

## Autofeed Screwdriver Accessories

### Autofeed Screwdriver 30" Extension Handle

Model	Part #
6834	192501-3
6844, BFR750, XRF01	194500-1