## TOTO<sub>®</sub>

# MW6342034CEFG

Supreme® II / WASHLET®+ C100 One-Piece Toilet - 1.28 GPF

#### **FEATURES**

- Concealed supply connection for seamless installation
- High-efficiency Tornado Flush® (1.28GPF/4.8LPF)
- CEFIONTECT® glaze prevents debris from sticking to ceramic surfaces for easy cleaning
- Universal Height
- Elongated front bowl
- Decorative one-piece design with high-profile tank
- Chrome trip lever
- 12" Rough-in, less supply
- See Spec sheet SW2034T20 for WASHLET features

#### **MODELS**

• CST634CEFGT20 - With CEFIONTECT glaze

#### **REQUIRED WASHLET+**

SW2034T20 WASHLET® + C100
 Fits TOTO WASHLET+ toilet bowl models only

# CEFIONTECT WASHLET Tornado Flush

#### COLORS/FINISHES

Standard #01 Cotton

#### PRODUCT SPECIFICATION

The one-piece high-efficiency Tornado Flush toilet shall be 1.28GPF/4.8LPF. Universal Height Toilet with CEFIONTECT glaze finish. Toilet shall have high-profile tank, elongated front bowl and chrome trip lever. Toilet shall be **TOTO Model CST634CEFGT20#01**.

See TOTO Specification sheet **SW2034T20** for details on required WASHLET.

#### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1
- Certifications: IAPMO(cUPC), EPA WaterSense, State of Massachusetts, City of Los Angeles, and others
- Code compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California AB715, California Green Building Code, City of Los Angeles Water Efficiency Ordinance
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements







### Supreme® II / WASHLET®+ C100 One-Piece Toilet - 1.28 GPF

#### **SPECIFICATIONS**

Water Use
Flush System
Min. Water Pressure
Water Surface
Trap Diameter
Rough-in
1.28 GPF/4.8LPF
8 psi (flowing)
7-1/8" x 9-1/8"
2-1/8"
12"

Trap SealWarrantyZ-1/8"One Year Limited Warranty

Material Vitreous china
 Shipping Weight CST634CEEGT20

 Shipping Weight CST634CEFGT20 104lbs. SW2034T20 16.0lbs.

Shipping Dimensions CST634CEFGT20

29-1/2" L x 18"W

 $\times$  19-1/4"  $H^1 \times$  27-1/8"  $H^2$ 


SW2034T20

23 1/2"X 20 1/2" X 9"

#### **INSTALLATION NOTES**


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

• See Spec sheet **SW2034T20** for Washlet details



\*SUGGESTED DIMENSIONS

RD-XXXXX, MW6342034CEFG, V.01

