





Template must be full scale 1:1 when printed





**ThermaTouch Control**

#### SPECIFICATIONS – ThermaTouch Control

Construction.....ABS Injection molded plastic  
 Controllability.....Steam, Light & Sound  
 Audio Out ..... 1/8” Barrel Jack  
 Power Supply.....ThermaSol PDM (10-8147)  
 Display ..... 7” Wide LCD Touch Screen

#### SPECIFICATIONS – Aromatherapy Steam Head

Construction..... 360 Half Hard Brass  
 Aromatherapy.....Integral Reservoir  
 Operation.....Thermal operated retractable outlet

#### Features:

- Activate last showers settings
- Turn Steam/Light/Music Systems: On or Off
- Control lighting
- Set Time and Temperature Volume settings
- Tranquility Environment: Built-in Sound and Video
- Bluetooth enabled
- Stereo Audio output

#### Aromatherapy Retractable Steam Head:

- Patented NoTouch™ retractable steam head with integral Aromatherapy well
- Available in 14 finishes
- Sleek new design dispenses steam safely
- Whisper quiet operation

#### Installation Notes:

- Refer to ThermaSol installation Instructions Doc No. 81190 for complete instructions.
- Requires wall cut out opening of 7-3/8” Wide X 5-3/8” High X 3-1/2” Deep.
- Use Mud Ring for Tile installation and ThermaTouch Control placement (04-8544).
- Ensure 3-1/2” clearance behind the rear of the control for cable clearance.
- The steam head should be installed 12” inches from the floor and 6” from any wall. Locate as far as possible from the bathing seating area or location of the users and not below any fixtures.

#### Product Specification:

The ThermaTouch Control is a 7” LCD Touchscreen Control used to operate other ThermaSol modules such as Steam Room functions, Light, Sound and Tranquility Visualization, Stereo Audio output and Ethernet connection. The control is approx. 8-1/8” Wide X 6 - 1/8” High X 2 - 1/2” Deep. It requires a wall cutout 7-3/8” Wide X 5-3/8” High and must have a clear in wall depth of 3-1/2”.

#### Shipping Information:

Weight.....1.8 lbs.  
 Length.....11 in.  
 Width.....14 in.  
 Height.....8 in.

#### Styling Information:

The ThermaTouch Control is available in a sleek recessed style with a black face and finished edge. The Steam Head is available in four trim styles: Traditional; Contemporary; Modern and Regency

#### Finish Chart:

Select desired finish and replace XX with code. No-Touch Aromatherapy steam head and control finishes.

PC = Polished Chrome  
 SC = Satin Chrome  
 PB = Polished Brass  
 SB = Satin Brass  
 AB = Antique Brass  
 COP = Polished Copper  
 ACOP = Antique Copper

PC = Polished Chrome  
 SC = Satin Chrome  
 PB = Polished Brass  
 SB = Satin Brass  
 AB = Antique Brass  
 COP = Polished Copper  
 ACOP = Antique Copper



**Traditional Edge**



**Contemporary Edge**




**Modern Edge**




**Regency Edge**


For any further assistance please contact ThermaSol at 800.776.0711 or [sales@thermasol.com](mailto:sales@thermasol.com)



**STEAM HEAD**




**THERMATOUCH**



**SPECIFICATIONS – POWER DISTRIBUTION MODULE**

Construction..... ABS Plastic  
 Power Supply ..... UL Listed Class 2 & II, (03-7142)  
 Internal Operating Voltage.....24V DC, 60 Watt



**Basic Functions:**

- Distributes DC Power and Digital signals to system modules:
- Serenity Light, Sound and Rainhead
- ThermaTouch or Signature Series Controls
- Solitude Wireless Module - SWM-2 (signal only)
- Steam Generator (signal only)

**Installation Notes:**

Overall size is approximately 5-3/4" long by 3-3/4" wide and 1-1/2" high. (Without connections) Allow space; 3" Min. for connections. Unit consists of a low voltage (24VDC) circuit board inside a box that can be placed up to 25 feet from the Light and Sound fixture or up to 50 feet from the Steam Generator. A separate universal voltage Power Adapter is provided (03-7142), it requires a standard 110V AC two prong wall outlet.

**Product Specification:**

5-3/4" L x 3-3/4" W x 1-1/2" H Body.  
 This PDM requires a ThermaSol Steam Generator and/or Light and Sound System and separate power supply for proper operation.

For any further assistance please contact  
 ThermaSol at 800.776.0711 or  
[sales@thermasol.com](mailto:sales@thermasol.com)

**Shipping Information:**

Weight.....4 lbs.  
 Length.....11 in.  
 Width.....14 in.  
 Height.....8 in.

