

ALUMINUM SEMI-TRASH PUMPS

APPLICATIONS

Ideal for high volume water* transfer and dewatering. Can handle liquid slurries including sand, pebbles, and suspended solids less than 1/2" in diameter.

FEATURES & BENEFITS

- Durable cast iron semi-open style impeller
- Lightweight aluminum outer casing includes heavy-duty roll frame
- Wear-resistant silicon carbide mechanical seal
- Easy to prime to 25'; no additional priming required after initial fill
- Built-in check valve
- EPA certified



6RLAG-3LST



6RLAG-2LST

**Not to be used for applying driveway sealant.*

Model	Item No.	UPC	cc	Intake	Discharge	Suction Lift	Max. Head	Max. Flow (GPM)	Fuel Tank (qt)	Engine
6RLAG-2LST	617034	0 10121 14503 0	208	2" MNPT	2" MNPT	25'	92'	150	3.8	4 Stroke OHV (208cc)
6RLAG-3LST	617037	0 10121 14506 1	208	3" MNPT	3" MNPT	25'	85'	264	3.8	4 Stroke OHV (208cc)

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
6RLAG-2LST	17.5"	20"	16.5"	52	3.34	8	4	2
6RLAG-3LST	17.75"	22.75"	19"	66	4.44	8	4	2

Aluminum Semi-Trash Pumps

