

ENGINE DRIVE SEMI-TRASH PUMP

APPLICATIONS

Ideal for high volume water* transfer and dewatering. Can handle liquid slurries including sand, pebbles, and suspended solids less than 1/2" in diameter.

FEATURES & BENEFITS

- Powered by Commercial Grade Honda GX160 (163cc) engine
- Durable cast iron semi-open style impeller
- Lightweight aluminum outer casing includes heavy-duty roll frame
- Wear-resistant silicon carbide mechanical seal
- Easy to prime to 25'; no additional priming required after initial fill
- Built-in check valve
- EPA certified

**Not to be used for applying driveway sealant.*

POWERED by
HONDA™



Powered by HONDA™ is a registered trademark of HONDA Motor Co., Ltd.



Model	Item No.	UPC	cc	Intake	Discharge	Suction Lift	Max. Head	Max. Flow (GPM)	Fuel Tank (qt)	Engine
6RLAG-3HST	617041	0 10121 14514 6	163	3" MNPT	3" MNPT	25'	85'	264	3.8 qt	Honda GX160

CARTON SPECIFICATIONS

Model	Length	Width	Height	Weight (lbs)	Carton Cubes (cu ft)	Pallet Quantity	Quantity per Layer	Layers per Pallet
6RLAG-3HST	18"	22"	17"	68.15 lbs	3.896	8	4	2

6RLAG-3HST

