



4" Submersible Well Pumps

Ideal for the supply of fresh water to rural homes, farms, and cabins that have 4" and greater diameter drilled wells to depths of 250 feet.

- Powered by industry-standard 2- or 3-wire motors
- Thermoplastic discharge and motor bracket
- Stainless steel pump shell
- Built-in suction screen and check valve
- 12 gpm and 22 gpm models available
- 1-1/4" FNPT discharge

See next page for specifications.



Control Boxes for 4" Submersible Well Pumps

Model	Item No.	HP	Volts
RLCB05-115	640188	1/2	115
RLCB05-230	640199	1/2	230
RLCB07-230	640190	3/4	230
RLCB10-230	640191	1	230
RLCB15-230	640222	1-1/2	230





Model	Item Number	HP	Wires	Volts	Amps	Depth to Water	Discharge Pressure (PSI)										Shut-Off
							0	10	20	30	40	50	60	70	80		
							Gallons per Minute										
12 GPM																	
RL12G05-2W1V	14942401	1/2	2	115	12	20'	-	19	18	16	15	14	12	10	6	231'	
						40'	19	18	16	15	14	13	11	7	2		
						60'	18	17	16	14	13	11	7	3	-		
						80'	17	16	15	13	11	8	3	-	-		
						100'	16	15	13	11	8	4	-	-	-		
						140'	14	12	9	5	-	-	-	-	-		
						200'	7	2	-	-	-	-	-	-	-		
RL12G05-2W2V RL12G05-3W2V*	14942402 14942405	1/2	2 3	230	6	20'	-	19	18	16	15	14	12	10	6	231'	
						40'	19	18	16	15	14	13	11	7	2		
						60'	18	17	16	14	13	11	7	3	-		
						80'	17	16	15	13	11	8	3	-	-		
						100'	16	15	13	11	8	4	-	-	-		
						140'	14	12	9	5	-	-	-	-	-		
						200'	7	2	-	-	-	-	-	-	-		
RL12G07-2W2V RL12G07-3W2V*	14942403 14942406	3/4	2 3	230	8	20'	-	20	18	17	16	16	15	14	12	291'	
						40'	20	19	17	17	16	15	14	13	11		
						60'	19	18	17	16	15	14	13	11	9		
						80'	18	17	16	15	14	13	11	9	6		
						100'	17	16	15	14	13	12	9	6	3		
						140'	15	15	14	13	10	7	4	-	-		
						240'	13	11	8	5	1	-	-	-	-		
RL12G10-2W2V RL12G10-3W2V*	14942404 14942407	1	2 3	230	10.4	20'	-	-	20	19	18	17	16	16	15	399'	
						40'	-	20	19	18	17	16	16	15	14		
						60'	20	19	18	17	17	16	15	14	13		
						80'	19	18	17	17	16	15	14	13	12		
						100'	18	17	17	16	15	14	13	12	11		
						140'	17	16	16	15	14	13	12	10	8		
						200'	15	14	13	11	11	9	7	5	2		
						240'	14	12	11	10	8	6	3	-	-		
						280'	12	10	8	6	4	1	-	-	-		
						300'	10	9	7	4	1	-	-	-	-		
						340'	7	5	2	-	-	-	-	-	-		
						380'	3	-	-	-	-	-	-	-	-		
RL12G15-3W2V	14942408	1-1/2	3	230	11.5	20'	-	-	-	20	19	18	17	17	16	545'	
						40'	-	-	20	19	18	18	17	17	16		16
						60'	-	20	19	18	18	17	17	16	16		16
						80'	20	19	18	18	17	17	16	16	15		15
						100'	19	18	18	17	17	16	16	15	15		
						140'	18	17	17	16	16	15	15	14	14		
						200'	17	16	16	15	15	14	13	13	12		
						240'	16	15	15	14	14	13	12	11	10		
						280'	15	14	14	13	12	11	10	9	8		
						300'	14	14	13	12	12	10	9	8	6		
						340'	13	13	12	11	10	8	7	5	3		
						380'	12	11	10	9	7	5	3	1	-		
						440'	9	8	6	4	2	-	-	-	-		
500'	5	3	-	-	-	-	-	-	-								
22 GPM																	
RL22G10-3W2V*	14942409	1	3	230	10.4	20'	-	-	-	31	28	26	23	19	11	221'	
						40'	-	-	32	28	26	24	20	12	1		
						60'	-	33	29	16	24	20	14	3	-		
						80'	-	29	27	24	21	15	4	-	-		
						100'	30	27	25	22	16	6	-	-	-		
						140'	25	23	18	9	-	-	-	-	-		
200'	13	2	-	-	-	-	-	-	-								

* Includes control box.