


INDOOR INSTALLATION



OUTDOOR INSTALLATION

- ① KD2 CONTROLLER
- SECURE TO WALL WITH APPROPRIATE FASTENERS
- ② EXISTING GROUNDED 115V OUTLET
- ③ 3-PRONG "PIGTAIL" POWER CORD
- ④ 1" FIELD CONDUIT FOR FIELD WIRES
- ⑤ CLIMATE LOGIC CABLE
- ⑥ 1/2" CONDUIT FOR ELECTRICAL POWER CONDUCTORS PER LOCAL AND NATIONAL CODES
- ⑦ ELECTRICAL COVER

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURERS SPECIFICATIONS.
2. ALL ELECTRICAL WORK MUST CONFORM TO LOCAL CODES. REFER TO PRODUCT LITERATURE FOR ADDITIONAL INSTALLATION AND ADJUSTMENT INFORMATION.
3. DO NOT SCALE DRAWINGS.
4. CONTRACTORS NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT: www.irritrol.com

IRRITROL® KD2 SERIES

INTERIOR AND EXTERIOR WALL-MOUNT CONTROLLER