

## Drake® Close Coupled Toilet, 1.6 & 0.8 GPF

### FEATURES

- DYNAMAX TORNADO FLUSH® utilizes 360° cleaning power to reach every part of the bowl
- Dual flush 1.6 & 0.8 GPF (6.0 & 3.0 LPF)
- CEFIONTECT® ceramic glaze prevents debris and mold from sticking to ceramic surfaces
- Specially designed to accommodate a WASHLET®+
- Design of the bowl reduces water flow resistance resulting in a quieter flushing sound
- Elongated front bowl and seat
- Universal Height
- Chrome plated trip lever
- 12" Rough-in
- Semi-concealed trapway

### MODELS

- **MS746124CSMFG (#01)**  
With CEFIONTECT ceramic glaze & includes SS124 SoftClose® seat

### COMPONENTS

- **CT746CUFGT40**  
Elongated bowl with CEFIONTECT
- **ST746SMA**  
Tank and cover only
- **SS124**  
SoftClose seat

### OPTIONAL COMPONENTS

- **THU773#01**  
Trip Lever - Cotton
- **THU773#BN**  
Trip Lever - Brushed Nickel
- **THU773#PN**  
Trip Lever - Polished Nickel

### COLORS/FINISHES

- #01 Cotton



-  **DYNAMAX TORNADO FLUSH**
-  **Universal Height**
-  **CEFIONTECT**

### PRODUCT SPECIFICATION

The two-piece DYNAMAX TORNADO FLUSH toilet shall be dual flush 1.6 GPF/0.8 GPF. Toilet shall be 12" rough-in. Toilet shall have optional CEFIONTECT ceramic glaze and be at Universal Height. Toilet shall have elongated front bowl and chrome plated trip lever. Toilet shall be TOTO Model MS746124CSMFG\_\_\_\_\_.

### CODES/STANDARDS

- Meets and exceeds ASME A112.19.2/CSA B45.1, ASME A112.19.14
- Certifications: IAPMO(cUPC®), EPA WaterSense, State of Massachusetts, and others
- Code Compliance: UPC, IPC, NSPC, NPC Canada, and others
- Legislative Compliance: California Green Building Code, City of Los Angeles Water Efficiency Ordinance, and others
- ADA compliant (when installed with trip lever located on the approach side)
- Complies with CA Prop 65 warning requirements



# MS746124CSMFG

## Drake® Close Coupled Toilet, 1.6 & 0.8 GPF


### SPECIFICATIONS

<b>Water Use</b>	1.6 & 0.8 GPF (6.0 & 3.0 LPF)
<b>Flush System</b>	DYNAMAX TORNADO FLUSH®
<b>Min. Water Pressure</b>	8 psi (Flowing)
<b>Water Surface</b>	5-5/8" x 4-1/8"
<b>Trap Diameter</b>	2-1/2"
<b>Rough-in</b>	12"
<b>Trap Seal</b>	2-1/8"
<b>Warranty</b>	One Year Limited Warranty
<b>Material</b>	Vitreous China
<b>Shipping Weight</b>	CT746CUFGT40 66 lbs. ST746SMA 35 lbs.
<b>Shipping Dimensions</b>	CT746CUFGT40 18-3/4" L x 10-1/2" W x 18-1/8" H ST746SMA 18-3/4" L x 8-3/8" W x 16" H

### INSTALLATION NOTES


Back-to-Back Toilet Installations:

TOTO recommends the use of a nationally listed, double sanitary tee-wye only, in vertical waste stacks, in accordance with the stipulations noted in the majority of nationally recognized plumbing codes.



To maintain adequate wall gap between the back of the tank and wall, mount the floor flange at a nominal 12" rough-in distance.

### DIMENSIONS



**TOTO®**

*These dimensions and specifications are subject to change without notice*