



▲ Designate proper finish suffix



see what Delta can do™

IN2ITION®

- H₂Okinetic® 2-In-1 Shower
- 5-Spray Setting Shower Head
- 5-Spray Setting Hand Shower
- Certified Dual Check Valves

FEATURES:

- Touch-Clean® Spray Holes
- H₂Okinetic® PowerDrench® Spray
- MagnaTite® Docking
- Lumicoat® Finish (-PR models only)
- Lumicoat® Finishes easily wipe clean without cleaners and chemicals on the products most commonly touched areas

STANDARD SPECIFICATIONS:

- Max. flow rate 1.75 gpm at 80 psi, 6.6 L/min @ 550 kPa (58620-▲-PK and 58620-▲-PR-PK)
- Max. flow rate 2.5 gpm at 80 psi, 9.5 L/min @ 550 kPa (58620-▲25 and 58620-▲-PR25-PK)
- Certified dual check valves for backflow prevention
- Integrated hand shower docks securely into shower head when not in use
- Hand shower with five spray settings - pause is a non-positive shut-off
- Diverter lever rotates to change shower head spray settings
- Push Button changes spray selection on hand shower
- Shower head diverter allows for single or shared operation of shower head (Full Body Spray in shared position) and hand shower
- 60" - 82" (1524 mm - 2083 mm) stretchable metal hose
- Ball connector swivel angle is 37° (18.5° per side)
- Fits standard 1/2"-14 NPT pipe fitting
- Spray settings include: H₂Okinetic® PowerDrench® spray, Full Body spray, Massaging spray, Soft Waterfall spray, and Pause

WARRANTY:

- Parts and Finish – Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date the product is received by the original purchaser or their authorized representative (installation contractor, etc.).
- Please go to www.deltafaucet.com for the complete details of our limited warranty.



Certified by
CSA Group
SHOWER HEADS
ROAMERS DE DUCHES
CABEZAS DE REGADERA

COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1◆
- ASME A112.18.3◆
- EPA WaterSense® - Applies to 58620-▲-PK & 58620-▲-PR -PK

- ◆ Your Delta hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3 and ASME A112.18.1/CSA B125.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta Faucet Company reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

DSP-B-58620-PK Rev. C

Delta Faucet Company

55 E. 111th Street, Carmel, IN 46280
350 South Edgeware Road, St. Thomas, ON N5P 4L1
© 2025 Delta Faucet Company