CROSSCUTTING BLADE



Ultimate Cut-Off Blades

USE IN



Table Saws

Miter Saws



Radial Arm **Table Saws**

Sliding Compound Miter Saws

APPLICATION

Polish material as it cuts, giving it glass-smooth finishes when crosscutting hard and soft woods. No sanding is required.



UNIQUE SIDE

GRIND polishes the material to produce a superior finish



LASER-CUT **ANTI-VIBRATION**

SLOTS drastically reduce vibration and sideways movement in the cut extending blade life, and giving a crisp, swirl-free flawless finish

DEPTH OF CUT





MATERIALS









When crosscutting, 5 to 7 teeth should be working in the wood at one time




RECOMMENDED USE


CUT QUALITY	FAIR	GOOD	EXCELLENT
Non-ferrous			
Laminate			
Plywood	1" Max T		
Chip Board	1" Max T		
Crosscuts Wood			
Rips Wood			

CARBIDE GRADE









DIA.	KERF	PLATE	ARBOR	TEETH	Perma-SHIELD®
8"	.116	.098	5/8"	64 ATB	LU85R008
9"	.116	.098	5/8"	72 ATB	LU85R009
10"	.116	.098	5/8"	80 ATB	LU85R010
12"	.116	.098	1"	96 ATB	LU85R012
14"	.136	.118	1"	108 ATB	LU85R014
15"	.136	.118	1"	108 ATB	LU85R015