# **Gas Appliance Connectors & Plumbing Supplies**

Connect with Confidence®



**Peace of mind means** 

never having to doubt your gas connection





# TABLE OF CONTENTS

Range Connectors6-7
Furnace Connectors8-9
Dryer Connectors10-11
Water Heater Connectors12-13
Space Heater Connectors14-15
Gas Log Connectors
Wall Heater Connectors
Tankless Water Heater Kits19
High BTU Connectors
LP Gas Connectors
Manufactured Home Gas Connector Kits23
Moveable Foodservice Connectors and Accessories24
Reliaguard® Gas Connector Kits25
Gas Flow Measurement And Diagnostic Tool Kits26
Gas Adapters and Shutoff Valves27
Gas Appliance and Line Pressure Regulators28
Supr-Safe® Stainless Steel Gas Connector Specification
SafetyShield® Yellow Coated Stainless Steel Gas Connector Specification
LV Black Coated Stainless Steel Gas Connector Specification31
Ultra Flow® High BTU Gas Connector Specification
Certifications
Dormont Showroom and POP Accessories
Terms and Conditions
Warranty Information

## **WARNING**

This literature is not intended to replace the available installation instructions or the experience of a trained product installer. Please refer to the installation manual for further information and product warnings.



## A COMPLETE LINE OF GAS CONNECTORS FOR ALL TYPES OF GAS APPLIANCES

Proudly Designed and Assembled in the USA



#### **Stainless Steel Gas Connectors**

Durable, naturally corrosion-resistant 304 stainless steel gas connectors for indoor or outdoor stationary appliance applications.



#### **Coated Stainless Steel Gas Connectors**

SafetyShield® features a premium antimicrobial coating to inhibit bacteria growth, improve corrosion and UV protection, and enhance flame and smoke resistance.



## Stainless Steel Gas Hearth Connectors with High-Temperature Black Coating

Specifically engineered for high-temperature applications such as gas logs, fireplace inserts and free-standing fireplaces.

The coating also features a premium antimicrobial coating to inhibit bacteria growth, improve corrosion and UV protection, and enhance flame and smoke resistance.



## Stainless Steel Gas Hearth Connectors with High-Temperature Black Coating for High BTU Applications

Engineered for high-temperature, high BTU applications such as gas logs, fireplace inserts and free-standing fireplaces.

Whisperflex also features a low-visibility black polymer coating that hides the connector from view. The specialized corrugation significantly reduces "whistling" from low flow appliances.



#### **High BTU Stainless Steel Gas Connectors**

Available with hot-dipped, heavy-duty gray PVC coating, SafetyShield yellow coating or stainless steel for indoor and outdoor high BTU applications.

Gas Connector Kits are available for mobile home installations.



#### 15 PSIG Stainless Steel Gas Connectors

Designed for outdoor, above-ground use, this gas connector is a safe and easy alternative to typical copper polyethylene connectors for the connection of propane tanks. This connector is rated to 15 PSIG—all other connectors are approved under ANSI Z21.24 to 1/2 PSIG.



#### FloPro - MD Gas Flow and Pressure Measurement System

The Dormont FloPro®-MD is a portable 3-in-1 gas flow meter, digital manometer, and calculator that helps service technicians and installers perform equipment start-ups, commissioning, and quickly diagnose gas flow or gas pressure issues to your gas burning equipment.



#### Commercial Foodservice Gas Connector and SnapFast Ouick-Disconnect

Specifically engineered for commercial cooking equipment, the Dormont Safety System<sup>TM</sup> Blue Hose<sup>®</sup> features antimicrobial PVC coating and patented Stress Guard<sup>TM</sup> technology. The SnapFast QD and restraining cable complete the gas connection and extend the service life of the gas connector.

# DURABLE, CORROSION-RESISTANT STAINLESS STEEL TUBING

# Exclusive No-Neck® design increases tubing flexibility. **Design** certified **Quality flared end adapters** Safety and quality For indoor and outdoor use. create a metal to metal seal to ensure Consistent quality ensures a integrity in critical applications. safe product you can trust.

#### Features

Quality flared end adapters ...... Creates a metal to metal seal to ensure integrity

use with natural, manufactured, mixed, liquefied petroleum (LP) and LP-gas air mixtures.

#### **Benefits**

No Neck® design ....... Increases flexibility

in critical applications.



Ordinary connector neck



Dormont No-Neck®

# Dormont's No-Neck® Design

With ordinary connectors, the tubing's straight neck enters the nut, and after being subjected to flexing, they may develop cracks that can result in a gas leak.

The Dormont No-Neck design reduces this danger because the first few tubing corrugations are enclosed within the nut. This results in increased tubing flexibility.

#### Indoor

CSA Design Certified under ANSI Z21.24/CSA 6.10, Dormont connectors are durable, flexible and easy to install. Designed with the safety of your home in mind, these connectors can be used for installation of all of the gas appliances throughout your home.

- Range
- Dryer
- Water Heater
- Gas Fireplaces
- Gas Logs
- Space Heater
- Furnace
- · Wall Heater

#### Outdoor

CSA Design Certified under ANSI Z21.75/CSA 6.27 for gas connectors for the connection of fixed appliances for outdoor installation to the gas supply.

- Rooftop Units
- Outdoor Dryer
- Stationary Outdoor Grills
- Gas Fire Pits
- Generators

#### **Manufactured Home**

CSA Design Certified under ANSI Z21.75/CSA 6.27 for gas connectors for the connection of park trailers and manufactured (mobile) homes to the gas supply. Large BTU capacity assures proper gas flow. Optional hot-dipped gray PVC coating provides added protection against weather and atmospheric conditions.

- Mobile Home Gas Meter
- Cross-over Gas Connection Kits

#### High BTU

CSA Design Certified under ANSI Z21.24/CSA 6.10, Dormont High BTU connectors ensure that gas appliances operate at their peak performance at all times. Refer to the BTU chart provided on page 14 for specifics.

- Commercial Water Heaters
- High-capacity Furnaces
- Boilers
- Tankless Water Heaters
- Up to 1.5 Million BTUs
- 1" OD, 1-1/4" OD and 1-1/2" OD




## HOW TO SELECT THE RIGHT CONNECTOR






















All appliance types can be found in the Table of Contents on pg. 1 of the catalog

2 Select your gas connector type/build



Uncoated stainless steel: Dormont's base offering Includes the 10, 20, 30, 40, 50, and 60 Series

Black powder coating: for applications where the connector needs to be less visible, such as hearth Includes the 10A and 20A Series

Yellow powder coating: Offers additional protection from chemical or weather-related corrosion and an Antimicrobial additive to inhibit the growth of harmful bacteria, mold and mildew. Includes the 10C, 20C, 30C and 40C Series

Gray PVC coating: Dormont's most durable, heavy-duty coating Includes the 31, 41, 51, and 61 Series

Black Powder Coating with Specialized Whisper Free Corrugations: For use in hearths and appliances prone to "whistling" lines. Includes the 10ANW and 20ANW Series

Determine length and end fittings

Dormont gas connectors are available in 12", 14", 18", 24", 30", 36", 48", 60" and 72"

Determine the size fitting you need, whether it's male or female, a straight or angled connector valve












Identify your model number and corresponding ordering code
Please see the next page (pg. 5) for directions on how to build your applicable part number.



# **Gas Connectors**



Charact	er 1:
Connect	or Diameter and Style
Part #	
10	3/8" OD (1/4" ID) - Uncoated
10C	3/8" OD (1/4" ID) - SafetyShield Yellow Coated
10A	3/8" OD (1/4" ID) - Low Visibility Black Coated
10ANW	3/8" OD (1/4" ID) - WhisperFlex Black Coated
11	3/8" OD (1/4" ID) - Gray PVC Coated
20	1/2" OD (3/8" ID) - Uncoated
20C	1/2" OD (3/8" ID) - SafetyShield Yellow Coated
20A	1/2" OD (3/8" ID) - Low Visibility Black Coated
20ANW	1/2" OD (3/8" ID) - WhisperFlex Black Coated
21	1/2" OD (3/8" ID) - Gray PVC Coated
30	5/8" OD (1/2" ID) - Uncoated
30C	5/8" OD (1/2" ID) - SafetyShield Yellow Coated
30A	5/8" OD (1/2" ID) - Low Visibility Black Coated
31	5/8" OD (1/2" ID) - Gray PVC Coated
31P	5/8" OD (1/2" ID) - 15PSIG Gray PVC Coated
40	1" OD (3/4" ID) - Uncoated
40C	1" OD (3/4" ID) - SafetyShield Yellow Coated
41	1" OD (3/4" ID) - Gray PVC Coated
50	1-1/4" OD (1" ID) - Uncoated
51	1-1/4" OD (1" ID) - Gray PVC Coated
60	1-1/2" OD (1-1/4" ID) - Uncoated
61	1-1/2" OD (1-1/4" ID) - Gray PVC Coated


Choice of fitting or valve for both ends of connector (choose two)			
Part #			
21	3/8" MIP (Tapped 1/4" FIP)		
22	3/8" FIP		
23	3/8" MIP Elbow		
24	3/8" FIP Elbow		
31	1/2" MIP (Tapped 3/8" FIP)		
32	1/2" FIP		
33	1/2" MIP Elbow		
34	1/2" FIP Elbow		
35	1/2" FIP Straight Connector Valve		
36	1/2" FIP Angle Connector Valve		
41	3/4" MIP (Tapped 1/2" FIP)		
42	3/4" FIP		
43	3/4" MIP Elbow		
44	3/4" FIP Elbow		
45	3/4" FIP Straight Connector Valve		
46	3/4" FIP Angle Connector Valve		
51	1" MIP (Tapped 3/4" FIP)		
52	1" FIP		
61	1-1/4" MIP (Tapped 1" FIP)		
62	1-1/4" FIP		
98	Nut Only		

Characters 2 & 3:



The product charts include the most popular configurations for specific applications. Additional configurations are available, please reach out to Dormont for additional information.

# Fittings and Gas Shutoff Valves



	Character 1: Style of accessory (fitting or valve)			
Part #				
90	Fitting			
91	Connector Valve			
92	Straight Valve			
93	Angle Connector Valve			
94	Full Port Valve			
95	Elbow			

Characters 2 & 3: Choice of fitting or valve for both ends of				
connector (choose two)				
Part #				
10	3/8" OD Flare			
20	1/2" OD Flare			
21	3/8" MIP (Tapped 1/4" FIP)			
22	3/8" FIP			
30	5/8" OD Flare (15/16"-16 Thread)			
31	1/2" MIP (Tapped 3/8" FIP)			
32	1/2" FIP			
40	1" OD Flare			
41	3/4" MIP (Tapped 1/2" FIP)			
42	3/4" FIP			
50	1-1/4" OD Flare			
51	1" MIP (Tapped 3/4" FIP)			
52	1" FIP			
60	1-1/2" OD Flare			
61	1-1/4" MIP (Tapped 1" FIP)			
62	1-1/4" FIP			



# **RANGE CONNECTORS**

## Proudly Designed and Assembled in the USA



**30 Series** 5/8" OD (1/2" ID)



# Supr-Safe® Stainless Steel Standard Fittings

FIP end MIP end

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
30-3132-36	0240152	1/2" MIP x 1/2" FIP x 36"L	25	23
30-3132-48	0240153	1/2" MIP x 1/2" FIP x 48"L	25	27
30-3132-60	0240154	1/2" MIP x 1/2" FIP x 60"L	12	15
30-3132-72	0240787	1/2" MIP x 1/2" FIP x 72"L	12	17
30-3131-36	0240146	1/2" MIP x 1/2" MIP x 36"L	25	24
30-3131-48	0240147	1/2" MIP x 1/2" MIP x 48"L	25	28
30-3131-60	0240148	1/2" MIP x 1/2" MIP x 60"L	12	16
30-3131-72	0240149	1/2" MIP x 1/2" MIP x 72"L	12	17
30-3232-36	0240164	1/2" FIP x 1/2" FIP x 36"L	25	22
30-3232-48	0240165	1/2" FIP x 1/2" FIP x 48"L	25	26
30-3232-60	0240166	1/2" FIP x 1/2" FIP x 60"L	12	15
30-3232-72	0240783	1/2" FIP x 1/2" FIP x 72"L	12	17
30-3141-36	0240156	1/2" MIP x 3/4" MIP x 36"L	25	25
30-3141-48	0240157	1/2" MIP x 3/4" MIP x 48"L	25	29
30-3141-60	0240158	1/2" MIP x 3/4" MIP x 60"L	12	16
30-3141-72	0240159	1/2" MIP x 3/4" MIP x 72"L	12	18
30-3142-36	0240160	1/2" MIP x 3/4" FIP x 36"L	25	24
30-3142-48	0240161	1/2" MIP x 3/4" FIP x 48"L	25	28
30-3142-60	0240162	1/2" MIP x 3/4" FIP x 60"L	12	16
30-3142-72	0240801	1/2" MIP x 3/4" FIP x 72"L	12	18
30-3242-36	0240543	1/2" FIP x 3/4" FIP x 36"L	25	24
30-3242-48	0240649	1/2" FIP x 3/4" FIP x 48"L	25	27
30-3242-60	0240753	1/2" FIP x 3/4" FIP x 60"L	12	16
30-3242-72	0240794	1/2" FIP x 3/4" FIP x 72"L	12	17
30-4141-36	0240588	3/4" MIP x 3/4" MIP x 36"L	25	26
30-4141-48	0240678	3/4" MIP x 3/4" MIP x 48"L	25	30
30-4141-60	0240773	3/4" MIP x 3/4" MIP x 60"L	12	17
30-4141-72	0240820	3/4" MIP x 3/4" MIP x 72"L	12	18
30-4242-36	0240169	3/4" FIP x 3/4" FIP x 36"L	25	25
30-4242-48	0240170	3/4" FIP x 3/4" FIP x 48"L	25	29
30-4242-60	0240171	3/4" FIP x 3/4" FIP x 60"L	12	16
30-4242-72	0240816	3/4" FIP x 3/4" FIP x 72"L	12	18
30-3135-36	0240778	1/2" MIP x 1/2" FIP Ball Valve x 36"L	25	30
30-3135-48	0240831	1/2" MIP x 1/2" FIP Ball Valve x 48"L	25	27
30-3135-60	0240894	1/2" MIP x 1/2" FIP Ball Valve x 60"L	12	19
30-3135-72	0240913	1/2" FIP x 1/2" FIP Ball Valve x 72"L	12	20
30-3235-36	0242390	1/2" FIP x 1/2" FIP Ball Valve x 36"L	25	30
30-3235-48	0240823	1/2" FIP x 1/2" FIP Ball Valve x 48"L	25	27
30-3235-60	0240893	1/2" FIP x 1/2" FIP Ball Valve x 60"L	12	18
30-3235-72	0242391	1/2" FIP x 1/2" FIP Ball Valve x 72"L	12	20

<sup>\*\*</sup> For product specifications see page 29

<sup>\*\*\*</sup> Retail bagged connectors available upon request



MIP end

12 43-10

# **RANGE CONNECTORS**

25

25

12

12

25

20

12

12

25

20

12

12

25

29

16

18

30 27

19

20

38

27

18

20

#### Proudly Designed and Assembled in the USA



**30C Series** 5/8" OD (1/2" ID)

	EXAMPLE			
Part#	30C	31	32	48
Character	1	2	3	4

# Connection End Guide Characters 3 & 4: Choice of fitting or valve for both ends of connector (choose two)

Part #	
31	1/2" MIP (Tapped 3/8" FIP)
32	1/2" FIP
33	1/2" MIP Elbow
34	1/2" FIP Elbow
35	1/2" FIP Straight Connector Valve
36	1/2" FIP Angle Connector Valve
41	3/4" MIP (Tapped 1/2" FIP)
42	3/4" FIP
43	3/4" MIP Elbow
44	3/4" FIP Elbow
45	3/4" FIP Straight Connector Valve
46	3/4" FIP Angle Connector Valve

30C-4242-36

30C-4242-48

30C-4242-60

30C-4242-72

30C-3135-36

30C-3135-48

30C-3135-60

30C-3135-72

30C-3235-36

30C-3235-48

30C-3235-60

30C-3235-72

0240711

0240771

0240846

0240887

0240854

0240895

0242411

0242412

0242419

0242051

0242052

0242053

3/4" FIP x 3/4" FIP x 36"L Coated

3/4" FIP x 3/4" FIP x 48"L Coated

3/4" FIP x 3/4" FIP x 60"L Coated

3/4" FIP x 3/4" FIP x 72"L Coated

1/2" MIP x 1/2" FIP Ball Valve x 36"L Coated

1/2" MIP x 1/2" FIP Ball Valve x 48"L Coated

1/2" MIP x 1/2" FIP Ball Valve x 60"L Coated

1/2" MIP x 1/2" FIP Ball Valve x 72"L Coated

1/2" FIP x 1/2" FIP Ball Valve x 36"L Coated

1/2" FIP x 1/2" FIP Ball Valve x 48"L Coated

1/2" FIP x 1/2" FIP Ball Valve x 60"L Coated

1/2" FIP x 1/2" FIP Ball Valve x 72"L Coated

# SafetyShield® Premium Yellow Coated Stainless Steel Standard Fittings

Model Number	Code	Description	Pack Quantity	Pack Weight (lbs)
30C-3132-36	0240178	1/2" MIP x 1/2" FIP x 36"L Coated	25	23
30C-3132-48	0240179	1/2" MIP x 1/2" FIP x 48"L Coated	25	27
30C-3132-60	0240807	1/2" MIP x 1/2" FIP x 60"L Coated	12	15
30C-3132-72	0240857	1/2" MIP x 1/2" FIP x 72"L Coated	12	17
30C-3131-36	0240173	1/2" MIP x 1/2" MIP x 36"L Coated	25	24
30C-3131-48	0240174	1/2" MIP x 1/2" MIP x 48"L Coated	25	28
30C-3131-60	0240175	1/2" MIP x 1/2" MIP x 60"L Coated	12	16
30C-3131-72	0240859	1/2" MIP x 1/2" MIP x 72"L Coated	12	17
30C-3232-36	0240182	1/2" FIP x 1/2" FIP x 36"L Coated	25	22
30C-3232-48	0240724	1/2" FIP x 1/2" FIP x 48"L Coated	25	26
30C-3232-60	0240804	1/2" FIP x 1/2" FIP x 60"L Coated	12	15
30C-3232-72	0240855	1/2" FIP x 1/2" FIP x 72"L Coated	12	17
30C-3141-36	0240701	1/2" MIP x 3/4" MIP x 36"L Coated	25	25
30C-3141-48	0240180	1/2" MIP x 3/4" MIP x 48"L Coated	25	29
30C-3141-60	0240836	1/2" MIP x 3/4" MIP x 60"L Coated	12	16
30C-3141-72	0240877	1/2" MIP x 3/4" MIP x 72"L Coated	12	18
30C-3142-36	0015603	1/2" MIP x 3/4" FIP x 36"L Coated	25	24
30C-3142-48	0240181	1/2" MIP x 3/4" FIP x 48"L Coated	25	28
30C-3142-60	0240835	1/2" MIP x 3/4" FIP x 60"L Coated	12	16
30C-3142-72	0240873	1/2" MIP x 3/4" FIP x 72"L Coated	12	18
30C-3242-36	0242451	1/2" FIP x 3/4" FIP x 36"L Coated	25	24
30C-3242-48	0240754	1/2" FIP x 3/4" FIP x 48"L Coated	25	27
30C-3242-60	0240824	1/2" FIP x 3/4" FIP x 60"L Coated	12	16
30C-3242-72	0240870	1/2" FIP x 3/4" FIP x 72"L Coated	12	17
30C-4141-36	0240715	3/4" MIP x 3/4" MIP x 36"L Coated	25	26
30C-4141-48	0240774	3/4" MIP x 3/4" MIP x 48"L Coated	25	30
30C-4141-60	0240848	3/4" MIP x 3/4" MIP x 60"L Coated	12	17
30C-4141-72	0240891	3/4" MIP x 3/4" MIP x 72"L Coated	12	18

FIP end

TO

<sup>\*\*</sup> For product specifications see page 30

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# **FURNACE CONNECTORS**

Proudly Designed and Assembled in the USA







# Supr-Safe® Stainless Steel Standard Gas Fittings

FIP end MIP end mm2 2 7

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
30-3132-12	0240335	1/2" MIP x 1/2" FIP x 12"L	25	16
30-3132-18	0240150	1/2" MIP x 1/2" FIP x 18"L	25	18
30-3132-24	0240151	1/2" MIP x 1/2" FIP x 24"L	25	20
30-3132-30	0240483	1/2" MIP x 1/2" FIP x 30"L	25	21
30-3132-36	0240152	1/2" MIP x 1/2" FIP x 36"L	25	23
30-3131-12	0240343	1/2" MIP x 1/2" MIP x 12"L	25	17
30-3131-18	0240144	1/2" MIP x 1/2" MIP x 18"L	25	18
30-3131-24	0240145	1/2" MIP x 1/2" MIP x 24"L	25	21
30-3131-30	0240493	1/2" MIP x 1/2" MIP x 30"L	25	22
30-3131-36	0240146	1/2" MIP x 1/2" MIP x 36"L	25	24
30-3232-12	0240326	1/2" FIP x 1/2" FIP x 12"L	25	16
30-3232-18	0240368	1/2" FIP x 1/2" FIP x 18"L	25	17
30-3232-24	0240163	1/2" FIP x 1/2" FIP x 24"L	25	19
30-3232-30	0240472	1/2" FIP x 1/2" FIP x 30"L	25	21
30-3232-36	0240164	1/2" FIP x 1/2" FIP x 36"L	25	22
30-3141-12	0240366	1/2" MIP x 3/4" MIP x 12"L	25	18
30-3141-18	0240416	1/2" MIP x 3/4" MIP x 18"L	25	20
30-3141-24	0240463	1/2" MIP x 3/4" MIP x 24"L	25	22
30-3141-30	0240538	1/2" MIP x 3/4" MIP x 30"L	25	23
30-3141-36	0240156	1/2" MIP x 3/4" MIP x 36"L	25	25
30-4242-12	0240387	3/4" FIP x 3/4" FIP x 12"L	25	18
30-4242-18	0240441	3/4" FIP x 3/4" FIP x 18"L	25	19
30-4242-24	0240491	3/4" FIP x 3/4" FIP x 24"L	25	22
30-4242-30	0240568	3/4" FIP x 3/4" FIP x 30"L	25	23
30-4242-36	0240169	3/4" FIP x 3/4" FIP x 36"L	25	25
30-3135-12	0240681	1/2" MIP x 1/2" FIP Ball Valve x 12"L	25	23
30-3135-18	0240155	1/2" MIP x 1/2" FIP Ball Valve x 18"L	25	24
30-3135-24	0240735	1/2" MIP x 1/2" FIP Ball Valve x 24"L	25	26
30-3135-30	0240767	1/2" MIP x 1/2" FIP Ball Valve x 30"L	25	28
30-3135-36	0240778	1/2" MIP x 1/2" FIP Ball Valve x 36"L	25	30
30-3235-12	0240674	1/2" FIP x 1/2" FIP Ball Valve x 12"L	25	23
30-3235-18	0242388	1/2" FIP x 1/2" FIP Ball Valve x 18"L	25	24
30-3235-24	0240729	1/2" FIP x 1/2" FIP Ball Valve x 24"L	25	26
30-3235-30	0242389	1/2" FIP x 1/2" FIP Ball Valve x 30"L	25	27
30-3235-36	0242390	1/2" FIP x 1/2" FIP Ball Valve x 36"L	25	29

<sup>\*\*</sup> For product specifications see page 29

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# **FURNACE CONNECTORS**

## Proudly Designed and Assembled in the USA



**30C Series** 5/8" OD (1/2" ID)

	EXAMPLE			
Part#	30C	31	32	48
Character	1	2	3	4

# Connection End Guide Characters 3 & 4: Choice of fitting or valve for both ends of connector (choose two)

Part #	
31	1/2" MIP (Tapped 3/8" FIP)
32	1/2" FIP
33	1/2" MIP Elbow
34	1/2" FIP Elbow
35	1/2" FIP Straight Connector Valve
36	1/2" FIP Angle Connector Valve
41	3/4" MIP (Tapped 1/2" FIP)
42	3/4" FIP
43	3/4" MIP Elbow
44	3/4" FIP Elbow
45	3/4" FIP Straight Connector Valve
46	3/4" FIP Angle Connector Valve

# SafetyShield® Yellow Coated Stainless Steel Standard Gas Fittings

FIP end	MIP end

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
30C-3132-12	0240442	1/2" MIP x 1/2" FIP x 12"L Coated	25	16
30C-3132-18	0240176	1/2" MIP x 1/2" FIP x 18"L Coated	25	18
30C-3132-24	0240177	1/2" MIP x 1/2" FIP x 24"L Coated	25	20
30C-3132-30	0240628	1/2" MIP x 1/2" FIP x 30"L Coated	25	21
30C-3132-36	0240178	1/2" MIP x 1/2" FIP x 36"L Coated	25	23
30C-3131-12	0240455	1/2" MIP x 1/2" MIP x 12"L Coated	25	17
30C-3131-18	0240521	1/2" MIP x 1/2" MIP x 18"L Coated	25	18
30C-3131-24	0240172	1/2" MIP x 1/2" MIP x 24"L Coated	25	21
30C-3131-30	0240639	1/2" MIP x 1/2" MIP x 30"L Coated	25	22
30C-3131-36	0240173	1/2" MIP x 1/2" MIP x 36"L Coated	25	24
30C-3232-12	0240434	1/2" FIP x 1/2" FIP x 12"L Coated	25	16
30C-3232-18	0240495	1/2" FIP x 1/2" FIP x 18"L Coated	25	17
30C-3232-24	0240564	1/2" FIP x 1/2" FIP x 24"L Coated	25	19
30C-3232-30	0240622	1/2" FIP x 1/2" FIP x 30"L Coated	25	21
30C-3232-36	0240182	1/2" FIP x 1/2" FIP x 36"L Coated	25	23
30C-3141-12	0240485	1/2" MIP x 3/4" MIP x 12"L Coated	25	18
30C-3141-18	0240560	1/2" MIP x 3/4" MIP x 18"L Coated	25	20
30C-3141-24	0240615	1/2" MIP x 3/4" MIP x 24"L Coated	25	22
30C-3141-30	0240666	1/2" MIP x 3/4" MIP x 30"L Coated	25	23
30C-3141-36	0240701	1/2" MIP x 3/4" MIP x 36"L Coated	25	25
30C-4242-12	0240522	3/4" FIP x 3/4" FIP x 12"L Coated	25	18
30C-4242-18	0240590	3/4" FIP x 3/4" FIP x 18"L Coated	25	19
30C-4242-24	0240633	3/4" FIP x 3/4" FIP x 24"L Coated	25	22
30C-4242-30	0240684	3/4" FIP x 3/4" FIP x 30"L Coated	25	23
30C-4242-36	0240711	3/4" FIP x 3/4" FIP x 36"L Coated	25	25
30C-3135-12	0240749	1/2" MIP x 1/2" FIP Ball Valve x 12"L Coated	25	23
30C-3135-18	0240782	1/2" MIP x 1/2" FIP Ball Valve x 18"L Coated	25	24
30C-3135-24	0240799	1/2" MIP x 1/2" FIP Ball Valve x 24"L Coated	25	26
30C-3135-30	0242410	1/2" MIP x 1/2" FIP Ball Valve x 30"L Coated	25	28
30C-3135-36	0240854	1/2" MIP x 1/2" FIP Ball Valve x 36"L Coated	25	30
30C-3235-12	0242049	1/2" FIP x 1/2" FIP Ball Valve x 12"L Coated	25	23
30C-3235-18	0240776	1/2" FIP x 1/2" FIP Ball Valve x 18"L Coated	25	24
30C-3235-24	0242418	1/2" FIP x 1/2" FIP Ball Valve x 24"L Coated	25	26
30C-3235-30	0242050	1/2" FIP x 1/2" FIP Ball Valve x 30"L Coated	25	27
30C-3235-36	0242419	1/2" FIP x 1/2" FIP Ball Valve x 36"L Coated	25	29

<sup>\*\*</sup> For product specifications see page 30

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# **DRYER CONNECTORS**

## Proudly Designed and Assembled in the USA



**20 Series** 1/2" OD (3/8" ID)



# Supr-Safe® Stainless Steel Standard Gas Fittings

FIP end

California de la companya della companya della companya de la companya della comp

MIP end

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
20-3132-36	0240126	1/2" MIP x 1/2" FIP x 36"L	25	19
20-3132-48	0240127	1/2" MIP x 1/2" FIP x 48"L	25	22
20-3132-60	0240128	1/2" MIP x 1/2" FIP x 60"L	12	12
20-3132-72	0240129	1/2" MIP x 1/2" FIP x 72"L	12	14
20-2131-36	0240403	3/8" MIP x 1/2" MIP x 36"L	25	17
20-2131-48	0240487	3/8" MIP x 1/2" MIP x 48"L	25	20
20-2131-60	0242455	3/8" MIP x 1/2" MIP x 60"L	12	12
20-2131-72	0242458	3/8" MIP x 1/2" MIP x 72"L	12	14
20-3131-36	0240119	1/2" MIP x 1/2" MIP x 36"L	25	19
20-3131-48	0240120	1/2" MIP x 1/2" MIP x 48"L	25	22
20-3131-60	0240121	1/2" MIP x 1/2" MIP x 60"L	12	13
20-3131-72	0240122	1/2" MIP x 1/2" MIP x 72"L	12	14
20-3122-36	0240372	1/2" MIP x 3/8" FIP x 36"L	25	18
20-3122-48	0240458	1/2" MIP x 3/8" FIP x 48"L	25	21
20-3122-60	0240586	1/2" MIP x 3/8" FIP x 60"L	12	12
20-3122-72	0240680	1/2" MIP x 3/8" FIP x 72"L	12	14
20-2232-36	0240364	3/8" FIP x 1/2" FIP x 36"L	25	17
20-2232-48	0240449	3/8" FIP x 1/2" FIP x 48"L	25	21
20-2232-60	0240601	3/8" FIP x 1/2" FIP x 60"L	12	12
20-2232-72	0240672	3/8" FIP x 1/2" FIP x 72"L	12	13
20-3135-36	0240132	1/2" MIP x 1/2" FIP Ball Valve x 36"L	25	26
20-3135-48	0240747	1/2" MIP x 1/2" FIP Ball Valve x 48"L	25	28
20-3135-60	0240809	1/2" MIP x 1/2" FIP Ball Valve x 60"L	12	16
20-3135-72	0240853	1/2" MIP x 1/2" FIP Ball Valve x 72"L	12	18

<sup>\*\*</sup> For product specifications see page 29

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# **DRYER CONNECTORS**

## Proudly Designed and Assembled in the USA



**20C Series** 1/2" OD (3/8" ID)

	EXAMPLE			
Part#	30C	31	32	48
Character	1	2	3	4

Conn	ection End Guide			
Characters 2 & 3: Choice of fitting or valve for both ends of connector (choose two)				
Part #				
21	3/8" MIP (Tapped 1/4" FIP)			
22	3/8" FIP			
23	3/8" MIP Elbow			
24	3/8" FIP Elbow			
31	1/2" MIP (Tapped 3/8" FIP)			
32	1/2" FIP			
33	1/2" MIP Elbow			
34	1/2" FIP Elbow			
35	1/2" FIP Straight Connector Valve			
36	1/2" FIP Angle Connector Valve			

# SafetyShield® Yellow Coated Stainless Steel Standard Gas Fittings

FIP end	MIP end
	13

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
20C-3132-36	0240141	1/2" MIP x 1/2" FIP x 36"L Coated	25	19
20C-3132-48	0240142	1/2" MIP x 1/2" FIP x 48"L Coated	25	22
20C-3132-60	0240731	1/2" MIP x 1/2" FIP x 60"L Coated	12	12
20C-3132-72	0240788	1/2" MIP x 1/2" FIP x 72"L Coated	12	14
20C-2131-36	0240559	3/8" MIP x 1/2" MIP x 36"L Coated	25	17
20C-2131-48	0240643	3/8" MIP x 1/2" MIP x 48"L Coated	25	20
20C-2131-60	0240727	3/8" MIP x 1/2" MIP x 60"L Coated	12	12
20C-2131-72	0240786	3/8" MIP x 1/2" MIP x 72"L Coated	12	14
20C-3131-36	0240137	1/2" MIP x 1/2" MIP x 36"L Coated	25	19
20C-3131-48	0240138	1/2" MIP x 1/2" MIP x 48"L Coated	25	22
20C-3131-60	0240741	1/2" MIP x 1/2" MIP x 60"L Coated	12	13
20C-3131-72	0240791	1/2" MIP x 1/2" MIP x 72"L Coated	12	14
20C-3122-36	0240512	1/2" MIP x 3/8" FIP x 36"L Coated	25	18
20C-3122-48	0240618	1/2" MIP x 3/8" FIP x 48"L Coated	25	21
20C-3122-60	0240713	1/2" MIP x 3/8" FIP x 60"L Coated	12	12
20C-3122-72	0240768	1/2" MIP x 3/8" FIP x 72"L Coated	12	14
20C-2232-36	0240506	3/8" FIP x 1/2" FIP x 36"L Coated	25	17
20C-2232-48	0240608	3/8" FIP x 1/2" FIP x 48"L Coated	25	21
20C-2232-60	0240709	3/8" FIP x 1/2" FIP x 60"L Coated	12	12
20C-2232-72	0240764	3/8" FIP x 1/2" FIP x 72"L Coated	12	14
20C-3135-36	0240775	1/2" MIP x 1/2" FIP Ball Valve x 36"L Coated	25	26
20C-3135-48	0240815	1/2" MIP x 1/2" FIP Ball Valve x 48"L Coated	25	29
20C-3135-60	0240872	1/2" MIP x 1/2" FIP Ball Valve x 60"L Coated	12	16
20C-3135-72	0240905	1/2" MIP x 1/2" FIP Ball Valve x 72"L Coated	12	18

<sup>\*\*</sup> For product specifications see page 30

<sup>\*\*\*</sup> Retail bagged connectors available upon request



## WATER HEATER CONNECTORS

#### Proudly Designed and Assembled in the USA

MIP end



20 Series 1/2" OD (3/8" ID)



# Supr-Safe® Stainless Steel Standard Gas Fittings

0240675

1 2 7 C. Continue **Model Number** Ordering Description Pack Weight Quantity (lbs) 20-2121-12 0240272 3/8" MIP x 3/8" MIP x 12"L 25 9 20-2121-18 0240297 3/8" MIP x 3/8" MIP x 18"L 25 10 20-2121-30 0242330 3/8" MIP x 3/8" MIP x 18"L 25 14 20-2121-24 0240316 3/8" MIP x 3/8" MIP x 24"L 25 12 20-2131-12 0240275 3/8" MIP x 1/2" MIP x 12"L 25 11 20-2131-18 0240306 3/8" MIP x 1/2" MIP x 18"L 25 12 20-2131-24 0240327 3/8" MIP x 1/2" MIP x 24"L 25 14 3/8" MIP x 1/2" MIP x 30"L 20-2131-30 0242331 25 16 20-3132-12 0240123 1/2" MIP x 1/2" FIP x 12"L 25 13 0240124 25 20-3132-18 1/2" MIP x 1/2" FIP x 18"L 14 20-3132-24 0240125 1/2" MIP x 1/2" FIP x 24"L 25 16 20-3132-30 0240370 1/2" MIP x 1/2" FIP x 30"L 25 17 20-3131-12 0240290 1/2" MIP x 1/2" MIP x 12"L 25 13 20-3131-18 0240117 1/2" MIP x 1/2" MIP x 18"L 25 14 20-3131-24 0240118 1/2" MIP x 1/2" MIP x 24"L 25 16 0240378 1/2" MIP x 1/2" MIP x 30"L 25 18 20-3131-30 20-2232-12 0242336 3/8" FIP x 1/2" FIP x 12"L 25 12 20-2232-18 0240284 3/8" FIP x 1/2" FIP x 18"L 25 13 20-2232-24 0240307 3/8" FIP x 1/2" FIP x 24"L 25 14 25 16 20-2232-30 0240337 3/8" FIP x 1/2" FIP x 30"L 20-2222-12 0240256 3/8" FIP x 3/8" FIP x 12"L 25 11 20-2222-24 0240286 3/8" FIP x 3/8" FIP x 12"L 25 13 20-2222-18 0240265 3/8" FIP x 3/8" FIP x 18"L 25 12 20-2222-30 0242335 3/8" FIP x 3/8" FIP x 30"L 25 15 0240553 20-3135-12 1/2" MIP x 1/2" FIP Ball Valve x 12"L 25 20 20-3135-18 0240130 1/2" MIP x 1/2" FIP Ball Valve x 18"L 25 21 20-3135-24 0240131 1/2" MIP x 1/2" FIP Ball Valve x 24"L 25 23 20-3135-30 1/2" MIP x 1/2" FIP Ball Valve x 30"L 24

FIP end

<sup>\*\*</sup> For product specifications see page 29

<sup>\*\*\*</sup> Retail bagged connectors available upon request



MIP end

No. of Street

# WATER HEATER CONNECTORS

FIP end

TO

Proudly Designed and Assembled in the USA



**20C Series** 1/2" OD (3/8" ID)

	EXAMPLE			
Part#	30C	31	32	48
Character	1	2	3	4

# Connection End Guide Characters 2 & 3: Choice of fitting or valve for both ends of connector (choose two)

Part #	
21	3/8" MIP (Tapped 1/4" FIP)
22	3/8" FIP
23	3/8" MIP Elbow
24	3/8" FIP Elbow
31	1/2" MIP (Tapped 3/8" FIP)
32	1/2" FIP
33	1/2" MIP Elbow
34	1/2" FIP Elbow
35	1/2" FIP Straight Connector Valve
36	1/2" FIP Angle Connector Valve

# SafetyShield® Yellow Coated Stainless Steel Standard Gas Fittings

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
20C-2121-12	0242363	3/8" MIP x 3/8" MIP x 12"L	25	9
20C-2121-18	0242364	3/8" MIP x 3/8" MIP x 18"L	25	10
20C-2121-30	0242366	3/8" MIP x 3/8" MIP x 18"L	25	14
20C-2121-24	0242365	3/8" MIP x 3/8" MIP x 24"L	25	12
20C-2131-12	0242143	3/8" MIP x 1/2" MIP x 12"L	25	11
20C-2131-18	0242369	3/8" MIP x 1/2" MIP x 18"L	25	12
20C-2131-24	0240440	3/8" MIP x 1/2" MIP x 24"L	25	14
20C-2131-30	0242370	3/8" MIP x 1/2" MIP x 30"L	25	16
20C-3132-12	0240354	1/2" MIP x 1/2" FIP x 12"L	25	13
20C-3132-18	0240139	1/2" MIP x 1/2" FIP x 18"L	25	14
20C-3132-24	0240140	1/2" MIP x 1/2" FIP x 24"L	25	16
20C-3132-30	0240509	1/2" MIP x 1/2" FIP x 30"L	25	17
20C-3131-12	0240365	1/2" MIP x 1/2" MIP x 12"L	25	13
20C-3131-18	0240135	1/2" MIP x 1/2" MIP x 18"L	25	14
20C-3131-24	0240136	1/2" MIP x 1/2" MIP x 24"L	25	16
20C-3131-30	0240520	1/2" MIP x 1/2" MIP x 30"L	25	18
20C-2232-12	0242161	3/8" FIP x 1/2" FIP x 12"L	25	12
20C-2232-18	0242162	3/8" FIP x 1/2" FIP x 18"L	25	13
20C-2232-24	0240402	3/8" FIP x 1/2" FIP x 24"L	25	14
20C-2232-30	0242163	3/8" FIP x 1/2" FIP x 30"L	25	16
20C-2222-12	0240305	3/8" FIP x 3/8" FIP x 12"L	25	11
20C-2222-24	0242372	3/8" FIP x 3/8" FIP x 12"L	25	13
20C-2222-18	0242156	3/8" FIP x 3/8" FIP x 18"L	25	12
20C-2222-30	0242157	3/8" FIP x 3/8" FIP x 30"L	25	15
20C-3135-12	0240665	1/2" MIP x 1/2" FIP Ball Valve x 12"L	25	20
20C-3135-18	0240699	1/2" MIP x 1/2" FIP Ball Valve x 18"L	25	21
20C-3135-24	0240143	1/2" MIP x 1/2" FIP Ball Valve x 24"L	25	23
20C-3135-30	0240752	1/2" MIP x 1/2" FIP Ball Valve x 30"L	25	24

<sup>\*\*</sup> For product specifications see page 30

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# **SPACE HEATER CONNECTORS**

Proudly Designed and Assembled in the USA

MIP end





Supr-Safe® Stainless Steel Standard Gas Fittings FIP end

Model Number	Ordering	Description	Pack	Pack Weight
	Code		Quantity	(lbs)
10-3132-12	0240276	1/2" MIP x 1/2" FIP x 12"L	25	13
10-3132-18	0240296	1/2" MIP x 1/2" FIP x 18"L	25	14
10-3132-24	0240315	1/2" MIP x 1/2" FIP x 24"L	25	15
10-3132-30	0240345	1/2" MIP x 1/2" FIP x 30"L	25	17
10-3132-36	0240112	1/2" MIP x 1/2" FIP x 36"L	25	18
10-3132-48	0240113	1/2" MIP x 1/2" FIP x 48"L	25	20
10-3132-60	0240581	1/2" MIP x 1/2" FIP x 60"L	12	11
10-3132-72	0240652	1/2" MIP x 1/2" FIP x 72"L	12	12
10-3131-12	0240287	1/2" MIP x 1/2" MIP x 12"L	25	13
10-3131-18	0240108	1/2" MIP x 1/2" MIP x 18"L	25	14
10-3131-24	0240109	1/2" MIP x 1/2" MIP x 24"L	25	15
10-3131-30	0240353	1/2" MIP x 1/2" MIP x 30"L	25	17
10-3131-36	0240110	1/2" MIP x 1/2" MIP x 36"L	25	18
10-3131-48	0240111	1/2" MIP x 1/2" MIP x 48"L	25	20
10-3131-60	0240599	1/2" MIP x 1/2" MIP x 60"L	12	11
10-3131-72	0240664	1/2" MIP x 1/2" MIP x 72"L	12	12
10-3135-12	0240508	1/2" MIP x 1/2" FIP Ball Valve x 12"L	25	17
10-3135-24	0240595	1/2" MIP x 1/2" FIP Ball Valve x 24"L	25	19
10-3135-30	0242279	1/2" MIP x 1/2" FIP Ball Valve x 24"L	25	20
10-3135-36	0240660	1/2" MIP x 1/2" FIP Ball Valve x 24"L	25	22
10-3135-18	0240556	1/2" MIP x 1/2" FIP Ball Valve x 28"L	25	18
10-3135-48	0240708	1/2" MIP x 1/2" FIP Ball Valve x 48"L	25	24
10-3135-60	0240769	1/2" MIP x 1/2" FIP Ball Valve x 60"L	12	13
10-3135-72	0242188	1/2" MIP x 1/2" FIP Ball Valve x 72"L	12	14

<sup>\*\*</sup> For product specifications see page 29

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# SPACE HEATER CONNECTORS

Proudly Designed and Assembled in the USA



**10C Series** 3/8" OD (1/4" ID)

	EXAMPLE			
Part#	30C	31	32	48
Character	1	2	3	4

#### **Connection End Guide** Characters 2 & 3: Choice of fitting or valve for both ends of connector (choose two) Part # 3/8" MIP (Tapped 1/4" FIP) 21 22 3/8" FIP 3/8" MIP Elbow 23 24 3/8" FIP Elbow 1/2" MIP (Tapped 3/8" FIP) 31 32 1/2" FIP 33 1/2" MIP Elbow 1/2" FIP Elbow 34 35 1/2" FIP Straight Connector Valve 1/2" FIP Angle Connector Valve 36

# SafetyShield® Yellow C Standar

ber	Ordering	Description		Pack	Pack Weight
	ted Staii as Fittin	nless Steel igs	FIP end		MIP end
	a				

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
10C-3132-12	0240348	1/2" MIP x 1/2" FIP x 12"L Coated	25	10
10C-3132-18	0240381	1/2" MIP x 1/2" FIP x 18"L Coated	25	11
10C-3132-24	0240419	1/2" MIP x 1/2" FIP x 24"L Coated	25	13
10C-3132-30	0240461	1/2" MIP x 1/2" FIP x 30"L Coated	25	14
10C-3132-36	0240507	1/2" MIP x 1/2" FIP x 36"L Coated	25	15
10C-3132-48	0240115	1/2" MIP x 1/2" FIP x 48"L Coated	25	17
10C-3132-60	0240700	1/2" MIP x 1/2" FIP x 60"L Coated	12	10
10C-3132-72	0240743	1/2" MIP x 1/2" FIP x 72"L Coated	12	11
10C-3131-12	0240358	1/2" MIP x 1/2" MIP x 12"L Coated	25	10
10C-3131-18	0240396	1/2" MIP x 1/2" MIP x 18"L Coated	25	11
10C-3131-24	0240435	1/2" MIP x 1/2" MIP x 24"L Coated	25	13
10C-3131-30	0240482	1/2" MIP x 1/2" MIP x 30"L Coated	25	14
10C-3131-36	0240530	1/2" MIP x 1/2" MIP x 36"L Coated	25	15
10C-3131-48	0240616	1/2" MIP x 1/2" MIP x 48"L Coated	25	17
10C-3131-60	0242317	1/2" MIP x 1/2" MIP x 60"L Coated	12	10
10C-3131-72	0240751	1/2" MIP x 1/2" MIP x 72"L Coated	12	11
10C-3135-12	0240629	1/2" MIP x 1/2" FIP Ball Valve x 12"L Coated	25	15
10C-3135-18	0240667	1/2" MIP x 1/2" FIP Ball Valve x 18"L Coated	25	16
10C-3135-24	0240694	1/2" MIP x 1/2" FIP Ball Valve x 24"L Coated	25	16
10C-3135-30	0242318	1/2" MIP x 1/2" FIP Ball Valve x 30"L Coated	25	19
10C-3135-36	0240734	1/2" MIP x 1/2" FIP Ball Valve x 36"L Coated	25	20
10C-3135-48	0240780	1/2" MIP x 1/2" FIP Ball Valve x 48"L Coated	25	22
10C-3135-60	0240841	1/2" MIP x 1/2" FIP Ball Valve x 60"L Coated	12	13
10C-3135-72	0242319	1/2" MIP x 1/2" FIP Ball Valve x 72"L Coated	12	14

<sup>\*\*</sup> For product specifications see page 30

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# **GAS LOG CONNECTORS**

Proudly Designed and Assembled in the USA



**10A Series** 3/8" OD (1/4" ID) **10ANW Series** 3/8" OD (1/4" ID)



# LV Black Coated Standard Gas Fittings



Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
10A-2122-12	0240328	3/8" MIP x 3/8" FIP x 12"L Black Coated	25	8
10A-2122-18	0240355	3/8" MIP x 3/8" FIP x 18"L Black Coated	25	9
10A-2122-24	0240390	3/8" MIP x 3/8" FIP x 24"L Black Coated	25	10
10A-2122-30	0242281	3/8" MIP x 3/8" FIP x 30"L Black Coated	25	12
10A-2122-36	0240474	3/8" MIP x 3/8" FIP x 36"L Black Coated	25	12
10A-3132-12	0240377	1/2" MIP x 1/2" FIP x 12"L Black Coated	25	10
10A-3132-18	0240417	1/2" MIP x 1/2" FIP x 18"L Black Coated	25	11
10A-3132-24	0240456	1/2" MIP x 1/2" FIP x 24"L Black Coated	25	13
10A-3132-30	0240504	1/2" MIP x 1/2" FIP x 30"L Black Coated	25	14
10A-3132-36	0240551	1/2" MIP x 1/2" FIP x 36"L Black Coated	25	15
10A-2131-12	0240386	3/8" MIP x 1/2" MIP x 12"L Black Coated	25	9
10A-2131-18	0240430	3/8" MIP x 1/2" MIP x 18"L Black Coated	25	10
10A-2131-24	0240466	3/8" MIP x 1/2" MIP x 24"L Black Coated	25	11
10A-2131-30	0240519	3/8" MIP x 1/2" MIP x 30"L Black Coated	25	13
10A-2131-36	0240566	3/8" MIP x 1/2" MIP x 36"L Black Coated	25	14
10A-2121-12	0240373	3/8" MIP x 3/8" MIP x 12"L Black Coated	25	8
10A-2121-18	0240412	3/8" MIP x 3/8" MIP x 18"L Black Coated	25	9
10A-2121-24	0240452	3/8" MIP x 3/8" MIP x 24"L Black Coated	25	10
10A-2121-30	0240496	3/8" MIP x 3/8" MIP x 30"L Black Coated	25	12
10A-2121-36	0240546	3/8" MIP x 3/8" MIP x 36"L Black Coated	25	12
10A-3131-12	0240407	1/2" MIP x 1/2" MIP x 12"L Black Coated	25	10
10A-3131-18	0240450	1/2" MIP x 1/2" MIP x 18"L Black Coated	25	11
10A-3131-24	0240486	1/2" MIP x 1/2" MIP x 24"L Black Coated	25	13
10A-3131-30	0240547	1/2" MIP x 1/2" MIP x 30"L Black Coated	25	14
10A-3131-36	0240587	1/2" MIP x 1/2" MIP x 36"L Black Coated	25	15
10A-2135-12	0240634	3/8" MIP x 1/2" FIP Ball Valve x 12"L Black Coated	25	14
10A-2135-18	0240670	3/8" MIP x 1/2" FIP Ball Valve x 18"L Black Coated	25	15
10A-2135-24	0240698	3/8" MIP x 1/2" FIP Ball Valve x 24"L Black Coated	25	16
10A-2135-30	0242283	3/8" MIP x 1/2" FIP Ball Valve x 30"L Black Coated	25	18
10A-2135-36	0240738	3/8" MIP x 1/2" FIP Ball Valve x 36"L Black Coated	25	19



# WhisperFlex Premium Black coated Standard Gas Fittings



Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
10ANW-2122-12	0243442	3/8" MIP x 3/8" FIP x 12"L Black Coated WF	25	15
10ANW-2122-18	0243443	3/8" MIP x 3/8" FIP x 18"L Black Coated WF	25	16
10ANW-2122-24	0244444	3/8" MIP x 3/8" FIP x 24"L Black Coated WF	25	17
10ANW-2121-18	0243441	3/8" MIP x 3/8" MIP x 18"L Black Coated WF	25	15
10ANW-2121-24	0243760	3/8" MIP x 3/8" MIP x 24"L Black Coated WF	25	16
10ANW-2121-36	68000274	3/8" MIP x 3/8" MIP x 36"L Black Coated WF	25	17
10ANW-2132-12	0240462	3/8" MIP x 1/2" FIP x 12"L Black Coated WF	25	15
10ANW-2132-18	0240557	3/8" MIP x 1/2" FIP x 18"L Black Coated WF	25	16
10ANW-2132-24	0240645	3/8" MIP x 1/2" FIP x 24"L Black Coated WF	25	17

<sup>\*\*</sup> For product specifications see page 31

<sup>\*\*\*</sup> Retail bagged connectors available upon request



FIP end

# **GAS LOG CONNECTORS**

## Proudly Designed and Assembled in the USA



**20A Series** 1/2" OD (3/8" ID)

**20ANW Series** 1/2" OD (3/8" ID)

	EXAMPLE			
Part#	30C	31	32	48
Character	1	2	3	4

## **Connection End Guide**

Characters 2 & 3:
Choice of fitting or valve for both ends of
connector (choose two)
CONTROCTOR (CHOOCO THO)

Part #	
21	3/8" MIP (Tapped 1/4" FIP)
22	3/8" FIP
23	3/8" MIP Elbow
24	3/8" FIP Elbow
31	1/2" MIP (Tapped 3/8" FIP)
32	1/2" FIP
33	1/2" MIP Elbow
34	1/2" FIP Elbow
35	1/2" FIP Straight Connector Valve
36	1/2" FIP Angle Connector Valve



# LV Black Coated S

Standard Gas Fittings		gs		
Model Number	Ordering Code	Description	Pack Quantity	Pack Weig (lbs)
20A-2122-12	0240399	3/8" MIP x 3/8" FIP x 12"L Black Coated	25	10
20A-2122-18	0240451	3/8" MIP x 3/8" FIP x 18"L Black Coated	25	10
201-2122-24	0240408	3/8" MID v 3/8" FID v 3/1" Black Coated	25	12

MIP end

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
20A-2122-12	0240399	3/8" MIP x 3/8" FIP x 12"L Black Coated	25	10
20A-2122-18	0240451	3/8" MIP x 3/8" FIP x 18"L Black Coated	25	10
20A-2122-24	0240498	3/8" MIP x 3/8" FIP x 24"L Black Coated	25	12
20A-2122-30	0242346	3/8" MIP x 3/8" FIP x 30"L Black Coated	25	13
20A-2122-36	0242347	3/8" MIP x 3/8" FIP x 36"L Black Coated	25	15
20A-3132-12	0240438	1/2" MIP x 1/2" FIP x 12"L Black Coated	25	13
20A-3132-18	0240490	1/2" MIP x 1/2" FIP x 18"L Black Coated	25	12
20A-3132-24	0240550	1/2" MIP x 1/2" FIP x 24"L Black Coated	25	16
20A-3132-30	0240605	1/2" MIP x 1/2" FIP x 30"L Black Coated	25	17
20A-3132-36	0240549	1/2" MIP x 1/2" FIP x 36"L Black Coated	25	19
20A-3131-12	0240448	1/2" MIP x 1/2" MIP x 12"L Black Coated	25	13
20A-3131-18	0240502	1/2" MIP x 1/2" MIP x 18"L Black Coated	25	14
20A-3131-24	0240558	1/2" MIP x 1/2" MIP x 24"L Black Coated	25	16
20A-3131-30	0240609	1/2" MIP x 1/2" MIP x 30"L Black Coated	25	18
20A-3131-36	0240650	1/2" MIP x 1/2" MIP x 36"L Black Coated	25	19
20A-2131-12	0240423	3/8" MIP x 1/2" MIP x 12"L Black Coated	25	11
20A-2131-18	0240473	3/8" MIP x 1/2" MIP x 18"L Black Coated	25	10
20A-2131-24	0240529	3/8" MIP x 1/2" MIP x 24"L Black Coated	25	12
20A-2131-30	0240589	3/8" MIP x 1/2" MIP x 30"L Black Coated	25	14
20A-2131-36	0240624	3/8" MIP x 1/2" MIP x 36"L Black Coated	25	17
20A-3135-12	0242126	1/2" MIP x 1/2" FIP Ball Valve x 12"L Black Coated	25	20
20A-3135-18	0242356	1/2" MIP x 1/2" FIP Ball Valve x 18"L Black Coated	25	21
20A-3135-24	0242124	1/2" MIP x 1/2" FIP Ball Valve x 24"L Black Coated	25	23
20A-3135-30	0242125	1/2" MIP x 1/2" FIP Ball Valve x 30"L Black Coated	25	24
20A-3135-36	0242126	1/2" MIP x 1/2" FIP Ball Valve x 36"L Black Coated	25	26

# WhisperFlex Black coated Standard Gas Fittings



Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
20ANW-2131-12	0242357	3/8" MIP x 1/2" FIP x 12"L Black Coated WF	25	21
20ANW-2131-18	0240646	3/8" MIP x 1/2" FIP x 18"L Black Coated WF	25	23
20ANW-2131-24	0240719	3/8" MIP x 1/2" FIP x 24"L Black Coated WF	25	26
20ANW-3132-12	0240561	1/2" MIP x 1/2" FIP x 12"L Black Coated WF	25	21
20ANW-3132-18	0240663	1/2" MIP x 1/2" FIP x 18"L Black Coated WF	25	23
20ANW-3132-24	0240722	1/2" MIP x 1/2" FIP x 24"L Black Coated WF	25	26

<sup>\*\*</sup> For product specifications see page 31

<sup>\*\*\*</sup> Retail bagged connectors available upon request

# WALL HEATER CONNECTORS

Proudly Designed and Assembled in the USA

MIP end

In 15-

# SAFETY SHIELD®

**10C Series** 3/8" OD (1/4" ID)



- \*\* For product specifications see page 30
- \*\*\* Retail bagged connectors available upon request



# **10A Series** 3/8" OD (1/4" ID)

	EXAMPLE			
Part#	30C	31	32	48
Character	1	2	3	4

# **Connection End Guide**

Characters 2 & 3: Choice of fitting or valve for both ends of connector (choose two)

Connector	(Choose two)
Part #	
21	3/8" MIP (Tapped 1/4" FIP)
22	3/8" FIP
23	3/8" MIP Elbow
24	3/8" FIP Elbow
31	1/2" MIP (Tapped 3/8" FIP)
32	1/2" FIP
33	1/2" MIP Elbow
34	1/2" FIP Elbow
35	1/2" FIP Straight Connector Valve
36	1/2" FIP Angle Connector Valve

- \* For additional configuration including nut x nut connectors see Flexible Gas Connectors and Plumbing Supplies Pricing Book or visit the Dormont website Dormont.com
- \*\* For product specifications see page 31
- \*\*\* Retail bagged connectors available upon request

# SafetyShield® Yellow Coated Stainless Steel Standard Gas Fittings

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)	
10C-3132-12	0240348	1/2" MIP x 1/2" FIP x 12"L Coated	25	10	
10C-3132-18	0240381	1/2" MIP x 1/2" FIP x 18"L Coated	25	11	
10C-3132-24	0240419	1/2" MIP x 1/2" FIP x 24"L Coated	25	13	
10C-3132-30	0240461	1/2" MIP x 1/2" FIP x 30"L Coated	25	14	
10C-3132-36	0240507	1/2" MIP x 1/2" FIP x 36"L Coated	25	15	
10C-3132-48	0240115	1/2" MIP x 1/2" FIP x 48"L Coated	25	17	
10C-3132-60	0240700	1/2" MIP x 1/2" FIP x 60"L Coated	12	10	
10C-3132-72	0240743	1/2" MIP x 1/2" FIP x 72"L Coated	12	11	
10C-2131-12	0240340	3/8" MIP x 1/2" MIP x 12"L Coated	25	10	
10C-2131-18	0242303	3/8" MIP x 1/2" MIP x 18"L Coated	25	11	
10C-2131-24	0242304	3/8" MIP x 1/2" MIP x 24"L Coated	25	13	
10C-2131-30	0242220	3/8" MIP x 1/2" MIP x 30"L Coated	25	14	
10C-2131-36	0242305	3/8" MIP x 1/2" MIP x 36"L Coated	25	15	
10C-2131-48	0242306	3/8" MIP x 1/2" MIP x 48"L Coated	25	17	
10C-2131-60	0242221	3/8" MIP x 1/2" MIP x 60"L Coated	12	10	
10C-2131-72	0242222	3/8" MIP x 1/2" MIP x 72"L Coated	12	11	
10C-2121-12	0242297	3/8" MIP x 3/8" MIP x 12"L Coated	25	10	
10C-2121-18	0242298	3/8" MIP x 3/8" MIP x 18"L Coated	25	11	
10C-2121-24	0242299	3/8" MIP x 3/8" MIP x 24"L Coated	25	13	
10C-2121-30	0242300	3/8" MIP x 3/8" MIP x 30"L Coated	25	14	
10C-2121-36	0240459	3/8" MIP x 3/8" MIP x 36"L Coated	25	15	
10C-2121-48	0242301	3/8" MIP x 3/8" MIP x 48"L Coated	25	17	
10C-2121-60	0242218	3/8" MIP x 3/8" MIP x 60"L Coated	12	10	
10C-2121-72	0240720	3/8" MIP x 3/8" MIP x 72"L Coated	12	11	

FIP end

# LV Premium Black Coated Standard Gas Fittings



Model Number Ordering Description Code		Code		Pack Weight (lbs)
10A-3132-12	0240377	1/2" MIP x 1/2" FIP x 12"L Black Coated	25	10
10A-3132-18	0240417	1/2" MIP x 1/2" FIP x 18"L Black Coated	25	11
10A-3132-24	0240456	1/2" MIP x 1/2" FIP x 24"L Black Coated	25	13
10A-3132-30	0240504	1/2" MIP x 1/2" FIP x 30"L Black Coated	25	14
10A-3132-36	0240551	1/2" MIP x 1/2" FIP x 36"L Black Coated	25	15
10A-2131-12	0240386	3/8" MIP x 1/2" MIP x 12"L Black Coated	25	9
10A-2131-18	0240430	3/8" MIP x 1/2" MIP x 18"L Black Coated	25	10
10A-2131-24	0240466	3/8" MIP x 1/2" MIP x 24"L Black Coated	25	11
10A-2131-30	0240519	3/8" MIP x 1/2" MIP x 30"L Black Coated	25	13
10A-2131-36	0240566	3/8" MIP x 1/2" MIP x 36"L Black Coated	25	14
10A-3131-12	0240407	1/2" MIP x 1/2" MIP x 12"L Black Coated	25	10
10A-3131-18	0240450	1/2" MIP x 1/2" MIP x 18"L Black Coated	25	11
10A-3131-24	0240486	1/2" MIP x 1/2" MIP x 24"L Black Coated	25	13
10A-3131-30	0240547	1/2" MIP x 1/2" MIP x 30"L Black Coated	25	14
10A-3131-36	0240587	1/2" MIP x 1/2" MIP x 36"L Black Coated	25	15
10A-2121-12	0240373	3/8" MIP x 3/8" MIP x 12"L Black Coated	25	8
10A-2121-18	0240412	3/8" MIP x 3/8" MIP x 18"L Black Coated	25	9
10A-2121-24	0240452	3/8" MIP x 3/8" MIP x 24"L Black Coated	25	10
10A-2121-30	0240496	3/8" MIP x 3/8" MIP x 30"L Black Coated	25	12
10A-2121-36	0240546	3/8" MIP x 3/8" MIP x 36"L Black Coated	25	12

Note: All low-visibility and Whisperflex connectors include black coated end fittings to further reduce visibility.



## TANKLESS WATER HEATER KITS



# Gas Tankless Water Heater Connection Kits

Get everything you need for a gas tankless water heater installation in one comprehensive kit.

#### Kits include

- Single Union Serve Valve Set
- High BTU Flexible Gas Connector for Indoor/Outdoor Installations
- Full Port Gas Ball Valve

Tankless Water Heater Connection Kits are available with either of the below connectors.

# 41 Series High BTU Gas Connector

Heavy-duty, antimicrobial, hot-dipped gray PVC coating for unmatched protection from weather and abuse, Ideal for outdoor installations



# 40C Series High BTU Gas Connector

Yellow polymer coating providing easy gas line identification and providing extra protection from chemical corrosion



#### Tankless Water Heater Kits

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
LFTV75FKIT18NW	0242443	Single Union Service Valve set, 18" Ultra Flow Gray PVC Coated High BTU Gas Connector, Full Port Gas	1	7
LFTV75FKIT24NW	0242444	Single Union Service Valve set, 24" Ultra Flow Gray PVC Coated High BTU Gas Connector, Full Port Gas	1	7
LFTV75FKIT18NW-CV	68004829	Single Union Service Valve set, 18" Safety Shield Yellow Coated High BTU Gas Connector, Full Port Gas Ball Valve	1	6
LFTV75FKIT24NW-CV	68004682	Single Union Service Valve set, 24" Safety Shield Yellow Coated High BTU Gas Connector, Full Port Gas Ball Valve	1	8



## HIGH BTU CONNECTORS

Proudly Designed and Assembled in the USA

FIP end



**40/41/40C Series** 1" OD (3/4" ID)

**50/51 Series** 1-1/4" OD (1" ID) **60/61 Series** 1-1/2" OD (1-1/4" ID)



# **Applications**

Tankless Water Heaters, Boilers, Mobile Homes, Gas Packs, Rooftop HVAC, Stationary Standby Generators, Commercial Water Heaters

# Ultra Flow® High BTU Gas Connectors

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
41-4142-12	0240923	3/4" MIP x 3/4" FIP x 12"L PVC coating	1	1
41-4142-14	0222509	3/4" MIP x 3/4" FIP x 14"L PVC coating	1	1
41-4142-18	0240937	3/4" MIP x 3/4" FIP x 18"L PVC coating	1	2
41-4142-24	0240186	3/4" MIP x 3/4" FIP x 24"L PVC coating	1	2
41-4142-30	0240187	3/4" MIP x 3/4" FIP x 30"L PVC coating	1	2
41-4142-36	0240188	3/4" MIP x 3/4" FIP x 36"L PVC coating	1	2
41-4142-48	0240976	3/4" MIP x 3/4" FIP x 48"L PVC coating	1	3
41-4142-60	0240997	3/4" MIP x 3/4" FIP x 60"L PVC coating	1	4
41-4142-72	0241035	3/4" MIP x 3/4" FIP x 72"L PVC coating	1	6
51-5152-12	0241012	1" MIP x 1" FIP x 12"L PVC coating	1	2
51-5152-14	0222510	1" MIP x 1" FIP x 14"L PVC coating	1	2
51-5152-18	0241018	1" MIP x 1" FIP x 18"L PVC coating	1	2
51-5152-24	0241029	1" MIP x 1" FIP x 24"L PVC coating	1	3
51-5152-30	0241039	1" MIP x 1" FIP x 30"L PVC coating	1	3
51-5152-36	0241051	1" MIP x 1" FIP x 36"L PVC coating	1	4
51-5152-48	0241066	1" MIP x 1" FIP x 48"L PVC coating	1	5
51-5152-60	0241090	1" MIP x 1" FIP x 60"L PVC coating	1	5
51-5152-72	0241118	1" MIP x 1" FIP x 72"L PVC coating	1	6
61-6162-12	0241195	1-1/4" MIP x 1-1/4" FIP x 12"L PVC coating	1	3
61-6162-18	0241205	1-1/4" MIP x 1-1/4" FIP x 18"L PVC coating	1	3
61-6162-24	0241215	1-1/4" MIP x 1-1/4" FIP x 24"L PVC coating	1	4
61-6162-30	0241228	1-1/4" MIP x 1-1/4" FIP x 30"L PVC coating	1	4
61-6162-36	0241237	1-1/4" MIP x 1-1/4" FIP x 36"L PVC coating	1	4
61-6162-48	0241260	1-1/4" MIP x 1-1/4" FIP x 48"L PVC coating	1	5
61-6162-60	0241274	1-1/4" MIP x 1-1/4" FIP x 60"L PVC coating	1	6
61-6162-72	0242437	1-1/4" MIP x 1-1/4" FIP x 72"L PVC coating	1	7

MIP end



Watch the ULTRAflow Overview Video, linking here

<sup>\*\*</sup> For product specifications see page 32

<sup>\*\*\*</sup> Retail bagged connectors available upon request



# **HIGH BTU CONNECTORS**

## Proudly Designed and Assembled in the USA



# SAFETY SHIELD\* SafetyShield® Yellow Coated High Btu Stainless Steel



FIP end

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
40C-4142-12	0240884	3/4" MIP x 3/4" FIP x 12"L Coated	1	2
40C-4142-14	68007058	3/4" MIP x 3/4" FIP x 14"L Coated	1	2
40C-4142-18	0240908	3/4" MIP x 3/4" FIP x 18"L Coated	1	2
40C-4142-24	0240927	3/4" MIP x 3/4" FIP x 24"L Coated	1	2
40C-4142-30	0240939	3/4" MIP x 3/4" FIP x 30"L Coated	1	3
40C-4142-36	0240950	3/4" MIP x 3/4" FIP x 36"L Coated	1	3
40C-4142-48	0240969	3/4" MIP x 3/4" FIP x 48"L Coated	1	4
40C-4142-60	0240986	3/4" MIP x 3/4" FIP x 60"L Coated	1	6
40C-4142-72	0242120	3/4" MIP x 3/4" FIP x 72"L Coated	1	6



# SUPR-SAFE® High BTU Stainless Steel

MIP end 

MIP end

FIP end

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
40-4142-12	0240828	3/4" MIP x 3/4" FIP x 12"L	1	1
40-4142-14	68001385	3/4" MIP x 3/4" FIP x 14"L	1	1
40-4142-18	0240866	3/4" MIP x 3/4" FIP x 18"L	1	1
40-4142-24	0240185	3/4" MIP x 3/4" FIP x 24"L	1	1
40-4142-30	0240924	3/4" MIP x 3/4" FIP x 30"L	1	2
40-4142-36	0240935	3/4" MIP x 3/4" FIP x 36"L	1	2
40-4142-48	0240955	3/4" MIP x 3/4" FIP x 48"L	1	2
40-4142-60	0240973	3/4" MIP x 3/4" FIP x 60"L	1	2
40-4142-72	0240987	3/4" MIP x 3/4" FIP x 72"L	1	3
50-5152-12	0240998	1" MIP x 1" FIP x 12"L	1	1
50-5152-18	0241010	1" MIP x 1" FIP x 18"L	1	1
50-5152-24	0241007	1" MIP x 1" FIP x 24"L	1	2
50-5152-30	0241015	1" MIP x 1" FIP x 30"L	1	2
50-5152-36	0241026	1" MIP x 1" FIP x 36"L	1	2
50-5152-48	0241049	1" MIP x 1" FIP x 48"L	1	3
50-5152-60	0241064	1" MIP x 1" FIP x 60"L	1	3
50-5152-72	0241088	1" MIP x 1" FIP x 72"L	1	3
60-6162-12	0241185	1-1/4" MIP x 1-1/4" FIP x 12"L	1	2
60-6162-18	0241192	1-1/4" MIP x 1-1/4" FIP x 18"L	1	2
60-6162-24	0241193	1-1/4" MIP x 1-1/4" FIP x 24"L	1	2
60-6162-30	0241206	1-1/4" MIP x 1-1/4" FIP x 30"L	1	2
60-6162-36	0241223	1-1/4" MIP x 1-1/4" FIP x 36"L	1	3
60-6162-48	0241235	1-1/4" MIP x 1-1/4" FIP x 48"L	1	3
60-6162-60	0241254	1-1/4" MIP x 1-1/4" FIP x 60"L	1	4
60-6162-72	0241259	1-1/4" MIP x 1-1/4" FIP x 72"L	1	4

## LP GAS CONNECTORS

#### Proudly Designed and Assembled in the USA



# **Applications**

- From 1st stage regulator on LP tank to riser
- From riser to 2nd stage regulator at the home
- From LP tank to home

# Advantages

- Safe and easy alternative to typical copper or polyethylene connectors
- Increase productivity with quick installation because fittings are already attached
- No cutting or flaring of copper needed which saves time and material
- 304 stainless steel tubing significantly reduces the chance of the material work hardening as opposed to copper tubing
- Heavy-duty, hot-dipped gray PVC coating for extra strength and protection against corrosion

## LP Gas Connectors-15 PSIG

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
31P-31P32P-24	0240966	5/8" OD Propane Connector with Fittings (1/2" MIP x 1/2" FIP x 24"L)	25	19
31P-31P32P-36	0240974	5/8" OD Propane Connector with Fittings (1/2" MIP x 1/2" FIP x 36"L)	25	22
31P-31P32P-48	0240982	5/8" OD Propane Connector with Fittings (1/2" MIP x 1/2" FIP x 48"L)	25	26
31P-31P32P-60	0240994	5/8" OD Propane Connector with Fittings (1/2" MIP x 1/2" FIP x 60"L)	12	15
31P-31P32P-72	0241030	5/8" OD Propane Connector with Fittings (1/2" MIP x 1/2" FIP x 72"L)	12	16
31P-41P42P-24	0240983	5/8" OD Propane Connector with Fittings (3/4" MIP x 3/4" FIP x 24"L)	25	19
31P-41P42P-36	0240990	5/8" OD Propane Connector with Fittings (3/4" MIP x 3/4" FIP x 36"L)	25	22
31P-41P42P-48	0243681	5/8" OD Propane Connector with Fittings (3/4" MIP x 3/4" FIP x 48"L)	25	26
31P-41P42P-60	0243682	5/8" OD Propane Connector with Fittings (3/4" MIP x 3/4" FIP x 60"L)	12	15



# MANUFACTURED HOME GAS CONNECTORS KITS

Proudly Designed and Assembled in the USA



**30 and 31 Series** 5/8" OD (1/2" ID)

**40 and 41 Series** 1" OD (3/4" ID) **50 Series** 1-1/4" OD (1" ID)



## Standard Gas Connector Kits

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
7010-3132	0241071	(1) #30-3132-24" Gas Connector (1/2" MIP x 1/2" FIP) 1/2" quick-disconnect, (1) Dust Cap and Dust Plug, (1) Warning Tag	1	1
7020-4142	0241023	(1) #30-4142-24" Gas Connector (3/4" MIP x 3/4" FIP) 3/4" quick-disconnect, (1) Dust Cap and Dust Plug, (1) Warning Tag	1	2
7030-4142	0241058	(1) #40-4142-24" Gas Connector (3/4" MIP x 3/4" FIP) 3/4" quick-disconnect, (1) Dust Cap and Dust Plug, (1) Warning Tag	1	2



# Gas Connector Kits with Hot-Dipped Gray PVC Coating

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
7110-3132	0241091	(1) #31-3132-24" Gas Connector (1/2" MIP x 1/2" FIP) 1/2" quick-disconnect, (1) Dust Cap and Dust Plug, (1) Warning Tag	1	2
7120-4142	0241043	(1) #31-4142-24" Gas Connector (3/4" MIP x 3/4" FIP) 3/4" quick-disconnect, (1) Dust Cap and Dust Plug, (1) Warning Tag	1	2
7130-4142	0241555	(1) #41-4142-24" Gas Connector (3/4" MIP x 3/4" FIP) 3/4" quick-disconnect, (1) Dust Cap and Dust Plug, (1) Warning Tag	1	3



## Gas Connector Kits with Full Port Valve

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
7021-4142	0241549	(1) #30-4142-24" Gas Connector (3/4" MIP x 3/4" FIP) (1) 3/4" NPT Full Port Valve, (1) 3/4" Plastic Protection Dust Plug, (1) 3/4" Plastic Protection Cap	1	2
7031-4142	0241005	1) #40-4142-24" Gas Connector (3/4" MIP x 3/4" FIP) (1) 3/4" NPT Full Port Valve, (1) 3/4" Plastic Protection Dust Plug, (1) 3/4" Plastic Protection Cap	1	2
7041-5152	0241099	(1) #50-5152-24" Gas Connector (1" MIP x 1" FIP) (1) 1" NPT Full Port Valve, (1) 1" Plastic Protection Dust Plug, (1) 1" Plastic Protection Cap	1	5



## MOVEABLE FOODSERVICE CONNECTORS AND ACCESSORIES

#### Proudly Designed and Assembled in the USA

**1650 Series** 5/8" OD (1/2" ID)

1675 Series 1" OD (3/4" ID) 16100 Series 1-1/4" OD (1" ID) 16125 Series 1-1/2" OD (1-1/4" ID)











High BTU commercial gas cooking equipment requires specifically designed gas connection systems to ensure that they are supplied with the correct amount of gas to function properly.

Dormont makes the following components designed to be used together for a maximum CODE-COMPLIANT food service equipment installation.

# The Dormont Blue Hose®

The Dormont commercial-grade, braided, coated, stainless steel gas connector is specifically designed to enable the equipment to be safely moved on a regular basis for cleaning and maintenance as determined by code requirements.

# The Restraining Cable

Prevents excess strain on the gas connector when moving the appliance.

# The SnapFast® One-Handed, Quick-Disconnect Coupling

Makes connecting and disconnecting the equipment faster, easier and safer.



Watch the Dormont Blue Hose Installation Video, linked here

						All the same
BTU/hr†	ID	PART #	Blue Hose	Snap- Fast	Valve & Elbows	Restraining Device
55k	1/2"	1650KIT72	√	√	√	√
60k	1/2"	1650KIT60	√	√	√	√
68k	1/2"	1650KIT48	√	√	√	√
77k	1/2"	1650KIT36	√	√	√	√
87k	1/2"	1650KIT24	√	√	√	√
139k	3/4"	1675KIT72*	√	√	√	√
158k	3/4"	1675KIT60*	√	√	√	√
180k	3/4"	1675KIT48*	√	√	√	√
218k	3/4"	1675KIT36*	√	√	√	√
232k	3/4"	1675KIT24*	√	√	√	√
279k	1"	16100KIT72	√	√	√	√
294k	1"	16100KIT60	√	√	√	√
334k	1"	16100KIT48	√	√	√	√
379k	1"	16100KIT36	√	√	√	√
414k	1"	16100KIT24	√	√	√	√
419k	1-1/4"	16125KIT72	√	√	√	√
476k	1-1/4"	16125KIT60	√	√	√	√
541k	1-1/4"	16125KIT48	√	√	√	√
615k	1-1/4"	16125KIT36	√	√	√	√
699k	1-1/4"	16125KIT24	√	√	√	<b>√</b>

87k	1/2"	1650BP72	√		
93k	1/2"	1650BP60	√		
106k	1/2"	1650BP48	√		
120k	1/2"	1650BP36	√		
150k	1/2"	1650BP24	√		
175k	3/4"	1675BP72	√		
198k	3/4"	1675BP60	√		
225k	3/4"	1675BP48	√		
256k	3/4"	1675BP36	√		
291k	3/4"	1675BP24	√		
350k	1"	16100BP72	√		
397k	1"	16100BP60	√		
451k	1"	16100BP48	√		
512k	1"	16100BP36	√		
582k	1"	16100BP24	√		
645k	1-1/4"	16125BP72	√		
733k	1-1/4"	16125BP60	√		
833k	1-1/4"	16125BP48	√		
946k	1-1/4"	16125BP36	√		
1075k	1-1/4"	16125BP24	√		

<sup>†</sup> Minimum Flow Capacity (0.64 Sp. Gr., 1000 BTU/ft3 Natural Gas at 0.5" wc pressure drop)



## RELIAGUARD® GAS CONNECTOR KITS





# Dormont ReliaGuard® Gas Connector Kits with SwivelGuard™

#### The Dormont SwivelGuard™

is a 360° multi-plane rotational device that significantly increases range of motion of gas connectors and caster-mounted appliances.

- Provides full 360° range of motion.
- Reduces stress on gas connectors.
- Expands aisle space because gas equipment can be moved closer to walls.
- Can be used on one or both ends of gas connector.
- Replaces rigid street elbows in most installations.
- Can be purchased as part of kits or separately as add-on.

			Ĵ	1			A CONTRACTOR OF THE PARTY OF TH		33			
BTU/hr <sup>†</sup>	ID	PART #	ReliaGuard	Standard Snap	Valve & Elbow	Full Port Valve	Restraining Device	Swivel- Guard	Swivel- Guard(2)			
Relia	ReliaGuard® Gas Connector Kits with SwivelGuard™											
56k	1/2"	RG50S60	√	√	√		V	√				
63k	1/2"	RG50S48	√	√	√		$\sqrt{}$	√				
72k	1/2"	RG50S36	√	√	√		$\sqrt{}$	√				
147k	3/4"	RG75S60	√	√	√		$\sqrt{}$	√				
167k	3/4"	RG75S48	√	√	√		$\sqrt{}$	√				
203k	3/4"	RG75S36	√	√	√		V	√				
274k	1"	RG100S60	√	√	√		√	√				
310k	1"	RG100S48	√	√	√		V	√				
353k	1"	RG100S36	√	√	√		√	√				





BTU/hr*	Dia.	SwivelGuar	rd
216k	1/2"	SM50- Gray	<b>V</b>
276k	3/4"	SM75- Gray	<b>V</b>
490k	1"	SM100- Gray	<b>V</b>

<sup>\*</sup> Minimum Flow Capacity (0.64 Sp. Gr., 1000 BTU/ft3 Natural Gas at 0.5" wc pressure drop)

#### NOTES

- Standard Snap and SwivelGuard™ are not for use in temperatures lower than 32°F (0°C) and are for indoor use only.
- Engineering Sheets with products specifications and technical information for ReliaGuard® connectors and accessories can be accessed on dormont.com

# ReliaGuard® Gas Connector Kits with Two SwivelGuard

54k	1/2"	RG502S60	√	√	√	√	√
60k	1/2"	RG502S48	√	√	√	√	√
69k	1/2"	RG502S36	√	√	√	√	√
140k	3/4"	RG752S60	√	√	√	√	√
160k	3/4"	RG752S48	√	√	√	√	√
193k	3/4"	RG752S36	√	√	√	√	√
261k	1"	RG1002S60	√	√	√	√	√
295k	1"	RG1002S48	√	√	√	V	√
336k	1"	RG1002S36	√	√	√	V	√

<sup>&</sup>lt;sup>†</sup> Minimum Flow Capacity (0.64 Sp. Gr., 1000 BTU/ft3 Natural Gas at 0.5" wc pressure drop)

<sup>\*\*</sup> For product specifications see page 30

<sup>\*\*\*</sup> Retail bagged connectors available upon request



## GAS FLOW MEASUREMENT AND DIAGNOSTIC TOOL KITS

# FIOPro-MD

# Connection Size 1" OD (3/4" ID)

# Gas Flow and Pressure Measurement System

Intermittent gas appliance issues are tough to diagnose.

FloPro-MD helps you troubleshoot and diagnose gas-related issues on hand, on-site. Troubleshoot with confidence, reduce callbacks, and provide solid service your customers can count on.

- Easy installation with common, off-the-shelf tools
- Ideal for servicing, diagnostics, & routine maintenance
- Perfect for commercial kitchen appliances, boilers, tankless water heaters, furnaces, dryers, kitchen appliances, standby power generators, light commercial boilers and water heaters & rooftop units
- App available for download at these locations







Watch the FloPro-MD Product Overview Video, linked here



Real Time Data via Free, User-Friendly Bluetooth App

(Android™ and iOS™)



Calculates Everything for You



Flowmeter, Manometer, & Calculator in One Tool



Compatible with Natural Gas (NG) & Propane (LPG)

# FloPro-MD Kit Options

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
FPMD75FFKIT	68004852	Dormont FloPro-MD ¾" FNPT, Standard Hard Case KIT	1	3
FPMD75FFKITQ	68005190	Dormont FloPro-MD ¾" FNPT with SnapFast® Quick Disconnect(QD) and Hard Case Kit	1	3



FloPro-MD Standard Kit



FloPro-MD with SnapFast QD Kit









# Easy to Use Handle

- Handles are ergonomically designed for smooth turns.
- Quarter-turn handle design makes for easy on/off operation.
- Most handles feature a lock-out for added safety.

#### Easier Installation

• Large wrench flats allow for quick, easy installation.

# Reliable Long-Lasting Performance

- The forged brass body eliminates the possibility of leaks associated with cast products.
- All valves are 100% leak tested.
- Valves are approved and design-certified by CSA for use with natural, manufactured, mixed liquefied petroleum gases, and LP gas-air mixtures.

IMPORTANT: The National Fuel Gas Code (ANSI Z223.1) requires each outlet, including a valve, be closed gas tight with a threaded plug or cap immediately after installation and until equipment is connected, and when equipment is disconnected from an outlet and the outlet is not to be used again immediately.

# Gas Adapters

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
90-3031	0240194	5/8" OD Flare (15/16" - 16 thread) x 1/2" MIP (Tapped 3/8" FIP)	25	6
90-3041	0240196	5/8" OD Flare (15/16" - 16 thread) x 3/4" MIP (Tapped 1/2" FIP)	25	7
90-3032	0240195	5/8" OD Flare (15/16" - 16 thread) x 1/2" FIP	25	5
90-3042	0240197	5/8" OD Flare (15/16" - 16 thread) x 3/4" FIP	25	5
95-3042	0241568	5/8" OD Flare (15/16" - 16 thread) x 3/4" FIP Elbow	25	7
90-2021	0240206	1/2" OD Flare x 3/8" MIP (Tapped 1/4" FIP)	25	4
90-2031	0240190	1/2" OD Flare x 1/2" MIP (Tapped 3/8" FIP)	25	6
90-2041	0240192	1/2" OD Flare x 3/4" MIP (Tapped 1/2" FIP)	25	6
90-2022	0240189	1/2" OD Flare x 3/8" FIP	25	3
90-2032	0240191	1/2" OD Flare x 1/2" FIP	25	4
90-2042	0240193	1/2" OD Flare x 3/4" FIP	25	6
90-1021	0240205	3/8" OD Flare x 3/8" MIP (Tapped 1/4" FIP)	25	3
90-1031	0240210	3/8" OD Flare x 1/2" MIP (Tapped 3/8" FIP)	25	5
90-1022	0240203	3/8" OD Flare x 3/8" FIP	25	3
90-1032	0240209	3/8" OD Flare x 1/2" FIP	25	4
95-1021	0241566	3/8" OD Flare x 3/8" MIP Elbow	25	4
90-4041	0240217	1" OD Flare x 3/4" MIP (Tapped 1/2" FIP)	10	3
90-4042	0240234	1" OD Flare x 3/4" FIP	10	4
90-5051	0240229	1-1/4" OD Flare x 1" MIP (Tapped 3/4" FIP)	10	4
90-5052	0240227	1-1/4" OD Flare x 1" FIP	10	4
90-6061	0240962	1-1/2" OD Flare x 1-1/4" MIP (Tapped 1" FIP)	10	6
90-6062	0240944	1-1/2" OD Flare x 1-1/4" FIP	10	6
SAFETYCAP-01	0240202	3/8" SAE Thread (3/8" OD)	10	1
SAFETYCAP-02	0240204	1/2" SAE Thread (1/2" OD) Thread (5/8" OD)	10	1
SAFETYCAP-03	0240207	5/8" SAE Thread (5/8" OD)	10	2
SAFETYCAP-04	0240208	5/8" OD (15/16" - 16 Thread)	10	3

Straight Reduce Port Valve





Straight Connector Valve



Angle Valve







#### Gas Shutoff Valves

Model Number	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
92-2222	0240219	3/8" FIP x 3/8" FIP Straight Reduce Port Valve	10	3
92-3232	0240200	1/2" FIP x 1/2" FIP Straight Reduce Port Valve	10	4
92-4242	0240201	3/4" FIP x 3/4" FIP Straight Reduce Port Valve	10	6
92ST-3232	0240880	1/2" FIP x 1/2" FIP Straight Reduce Port Side Tap Valve	10	5
92ST-4242	0240933	3/4" FIP x 3/4" FIP Straight Reduce Port Side Tap Valve	10	6
91-1032	0240198	3/8" OD Flare x 1/2" FIP Straight Connector Valve	10	4
91-2032	0240199	1/2" OD Flare x 1/2" FIP Straight Connector Valve	10	4
91-3032	0240236	5/8" OD Flare (15/16"-16 thread) x 1/2" FIP Straight Connector Valve	10	5
91-3042	0240291	5/8" OD Flare (15/16"-16 thread) x 3/4" FIP Straight Connector Valve	10	6
93-1032	0240269	3/8" OD Flare x 1/2" FIP Angle Valve	10	5
93-2032	0240282	1/2" OD Flare x 1/2" FIP Angle Valve	10	5
93-3042	0240302	5/8" OD Flare (15/16"-16 thread) x 3/4" FIP Angle Valve	10	6
94-3232	0240244	1/2" FIP x 1/2" FIP Straight Full Port Valve	10	5
94-4242	0240342	3/4" FIP x 3/4" FIP Straight Full Port Valve	10	8
94-5252	0240759	1" FIP x 1" FIP Straight Full Port Valve	6	8

## GAS APPLIANCE AND LINE PRESSURE REGULATORS

# Dormont gas appliance pressure regulators are designed for main burner and/or pilot applications, where precise control of tiny flows is an essential operating requirement.

- Housings are high strength aluminum castings.
- All models have been tested for multi-position mounting and may be installed in any plane or angle without restriction.
- They may be used with natural, manufactured, mixed, LP, or LP gas-air mixture.

## Gas Appliance Pressure Regulators

Part	EDP	Description	Pack Quantity	Pack Weight (lbs)
RV47LNG-22	0241604	Natural Gas 3/8" Pipe Size, 125,000 BTU per hr, 1/2 psig inlet pressure, 2.8"-5.2" w.c.	1	1
R48N32-0306-3.5	0241593	Natural Gas 1/2" Pipe Size, 250,000 BTU per hr, 1/2 psig inlet pressure, 3.0"-6.0" w.c.	1	1
R48N42-0306-3.5	0241594	Natural Gas 3/4" Pipe Size, 250,000 BTU per hr, 1/2 psig inlet pressure, 3.0"-6.0" w.c.	1	1
*R48P32-0512-10	0241595	LP Gas 1/2" Pipe Size, 400,000 BTU per hr, 1/2 psig inlet pressure, 5.0"-12.0" w.c.	1	1
*R48P42-0512-10	0241596	LP Gas 3/4" Pipe Size, 400,000 BTU per hr, 1/2 psig inlet pressure, 5.0"-12.0" w.c.	1	1
RV47CL-33	0241603	Convertible 3/8" Pipe Size, 125,000 NG/200,000 LP BTU per hr, 1/2 psig inlet pressure, 4" w.c. NG and 10" w.c. LP Gas	1	1
RV48CL-32	0241605	Convertible 1/2" Pipe Size, 230,000 NG/368,000 LP BTU per hr, 1/2 psig inlet pressure, 5" w.c. NG and 10" w.c. LP Gas	1	1
RV48CL-42	0241606	Convertible 3/4" Pipe Size, 275,000 NG/ 440,000 LP BTU per hr, 1/2 psig inlet pressure, 5" w.c. NG and 10" w.c. LP Gas	1	1
RV61LNG-52*	0241607	Natural Gas 1" Pipe Size, 900,000 BTU per hr, 1/2 psig inlet pressure, 4.0"-8.0" w.c.	1	2
RV61LNG-62*	0241608	Natural Gas 1-1/4" Pipe Size, 900,000 BTU per hr, 1/2 psig inlet pressure, 4.0"-8.0" w.c.	1	2
RV81LNG-72*	0241609	Natural Gas 1-1/2" Pipe Size, 2,500,000 BTU per hr, 1/2 psig inlet pressure, 3.0"-8.0" w.c.	1	4



<sup>\*</sup>Regulators marked are for main burner only. Not for pilot load applications.



R48P42-0512-10



RV48-CL-32



RV61LNG-52



R325 Regulator

# Dormont Manufacturing 2 psig regulators are designed for natural and liquefied propane gases.

- CSA design certified.
- Manufactured as gas appliance regulators and as line pressure regulators.
- Both series supply precise regulating control from full-flow, down to tiny pilot flows.
- In the absence of flow, these regulators provide excellent control of the outlet pressure.
- Meet standard requirements for use with residential, commercial, and industrial applications.

## Gas Appliance and Line Pressure Regulators



R625 Regulator

Part	Ordering Code	Description	Pack Quantity	Pack Weight (lbs)
R325N32-0509-06	0241590	Natural Gas Lever Action Regulator 1/2" Pipe Size, 150,000 BTU per hr, 2 psig inlet pressure, Spring range 5" to 9", spring preset at 6"	1	1
R325N32-0711-08	0241591	Natural Gas Lever Action Regulator 1/2" Pipe Size, 250,000 BTU per hr, 2 psig inlet pressure, Spring range 7" to 11", spring preset at 8"	1	1
R325P32-0711-11	0241592	LP Gas Lever Action Regulator 1/2" Pipe Size, 400,000 BTU per hr, 2 psig inlet pressure, Spring range 7" to 11", spring preset at 11"	1	1
R625N42-0711-08	0241597	Natural Gas Lever Action Regulator 3/4" Pipe Size, 600,000 BTU per hr, 2 psig inlet pressure, Spring range 7" to 11", spring preset at 8"	1	2
R625P42-0711-11	0241598	LP Gas Lever Action Regulator 3/4" Pipe Size, 970,000 BTU per hr, 2 psig inlet pressure, Spring range 7" to 11", spring preset at 11"	1	2



## Supr-Safe® STAINLESS STEEL GAS CONNECTOR SPECIFICATIONS

Proudly Designed and Assembled in the USA

# Supr-Safe® Stainless Steel Gas Connector Specifications

FIP end MIP end



## Features and Specifications

- Tubing ...... Annealed, 304 stainless steel (ASTM A240)
- Flare nuts ...... Brass or plated steel
- Adapters ...... Plated Steel
   Meets SAF J512 sta

Meets SAE J512 standard  $-45^{\circ}$  flare (with the exception of 15/16" -16 threads of 5/8" OD)

- Optional coating . Heavy-duty, antimicrobial, hot-dipped gray PVC (for 1/2" OD (21 series) and 5/8" OD (31 series only). Coating will not hold a flame.
- Approved for indoor/outdoor use with MAX operating pressure 0.5 psi
- Operating Temperature with adapters: -40°F to 350°F
- Operating Temperature with valves: -40°F to 125°F
- 100% Factory leak tested
- When installing a new appliance or when an existing appliance is moved to a new location a NEW gas connector must be used per manufacturer's installation instructions and per product standards ANSI Z21.24/CSA 6.10 and ANSI Z21.75/CSA 6.27.
- Avoid repeated bending, flexing, movement or vibration. Do not use on portable gas generators due to excessive vibration.





# **Applications**

#### Indoor

- Range
- Dryer
- Water Heater
- Gas Fireplace
- · Garage Heater
- Wall Heater
- Tankless Water Heater
- Furnace
- Space Heaters

#### Outdoor

- Rooftop Units
- Outdoor Dryer
- Stationary Outdoor Grills
- Gas Fire Pits

#### **Manufactured Home**

- Mobile Home Gas Meter
- Cross-over Gas Connection Kits

# Design Certifications and Approvals

- ANSI Z21.24/CSA 6.10 Connectors for Gas Appliances
- ANSI Z21.75/CSA 6.27 Connectors for Outdoor Appliances and Manufactured Homes
- City of New York MEA #376-92-M
- Approved by the Commonwealth of Massachusetts Board of State Examiners of Plumbers and Gas Fitters – connector length may not exceed 48".

#### **A WARNING**

Installation and service MUST be performed by qualified installer. Read and follow all Dormont safety, use, sizing, installation and care instructions and follow all building codes, construction standards, appliance manufacturer recommendations and instructions, and applicable ANSI standards.





Connector Flow Capacity – For Natural Gas (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 0.64 SG., 1000 BTU per Cu. Ft. at 0.5 inch Water Column (124 Pa) Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"	48"	60"	72"
10	3/8"	1/4"	48,000	43,800	40,000	36,400	33,400	28,300	24,900	23,100
20	1/2"	3/8"	102,000	93,100	85,000	77,100	71,100	60,500	53,200	49,100
30	5/8"	1/2"	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000

Connector Flow Capacity – **For Propane Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 1.55 SG., 2500 BTU per Cu. Ft. at 0.5 inch Water Column (124 Pa) Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"	48"	60"	72"
10	3/8"	1/4"	76,800	70,080	64,000	58,240	53,440	45,280	39,840	36,960
20	1/2"	3/8"	163,200	148,960	136,000	123,360	113,760	96,800	85,120	78,560
30	5/8"	1/2"	288,000	262,720	240,000	217,600	200,000	169,600	149,120	137,600

#### NOTICE



# SafetyShield® YELLOW COATED GAS CONNECTORS SPECIFICATIONS

Proudly Designed and Assembled in the USA

# SafetyShield® Yellow Coated Gas Connector Specifications

# Features and Specifications

• Tubing ...... Annealed, 304 stainless steel (ASTM A240)

 Coating........... SafetyShield Yellow polymer coating features enhanced corrosion resistance, flame/smoke resistance and an antimicrobial additive that inhibits the growth of bacteria, mold, and mildew.

• Flare nuts ...... Brass or plated steel

• Adapters ..... Plated Steel

Meets SAE J512 standard  $-45^{\circ}$  flare (with the exception of 15/16" -16 threads of 5/8" OD)

 Approved for indoor/outdoor use with MAX operating pressure 0.5 psi

• Operating Temperature with adapters: -40°F to 350°F

• Operating Temperature with valves: -40°F to 125°F

• 100% factory leak tested

- When installing a new appliance or when an existing appliance is moved to a new location a NEW gas connector must be used per manufacturer's installation instructions and per product standards ANSI Z21.24/CSA 6.10 and ANSI Z21.75/CSA 6.27.
- Yellow Coating MAX Temp. Rating of 350°F
- Not suitable for moveable installations. Not NSF certified
- Avoid repeated bending, flexing, movement or vibration. Do not use on portable gas generators due to excessive vibration



# **Design Certifications and Approvals**



- ANSI Z21.24/CSA 6.10 Connectors for Gas Appliances
- ANSI Z21.75/CSA 6.27 Connectors for Outdoor Appliances and Manufactured Homes
- City of New York MEA #376-92-M
- Approved by the Commonwealth of Massachusetts Board of State Examiners of Plumbers and Gas Fitters – connector length may not exceed 48".

#### **A WARNING**

Installation and service MUST be performed by qualified installer. Read and follow all Dormont safety, use, sizing, installation and care instructions and follow all building codes, construction standards, appliance manufacturer recommendations and instructions, and applicable ANSI standards.









Connector Flow Capacity – **For Natural Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 0.64 SG., 1000 BTU per Cu. Ft. at 0.5 inch Water Column (124 Pa) Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"	48"	60"	72"
10C	3/8"	1/4"	48,000	43,800	40,000	36,400	33,400	28,300	24,900	23,100
20C	1/2"	3/8"	102,000	93,100	85,000	77,100	71,100	60,500	53,200	49,100
30C	5/8"	1/2"	180,000	164,200	150,000	136,000	125,000	106,000	93,200	86,000

Connector Flow Capacity – For Propane Gas (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 1.55 SG., 2500 BTU per Cu. Ft. at 0.5 inch Water Column (124 Pa) Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"	48"	60"	72"
10C	3/8"	1/4"	76,800	70,080	64,000	58,240	53,440	45,280	39,840	36,960
20C	1/2"	3/8"	163,200	148,960	136,000	123,360	113,760	96,800	85,120	78,560
30C	5/8"	1/2"	288,000	262,720	240,000	217,600	200,000	169,600	149,120	137,600

#### NOTICE



## LV BLACK COATED GAS CONNECTOR SPECIFICATIONS

Proudly Designed and Assembled in the USA

# LV Black Coated Gas Connector Specifications

# Specifically engineered for high-temperature applications such as gas logs, fireplace inserts, and free-standing fireplaces

- Designed to reduce glare and hide the connector from view to enhance the beauty of the hearth.
- The premium hi-temperature black coating features enhanced corrosion resistance, flame/smoke resistance and an antimicrobial additive that inhibits the growth of bacteria, mold, and mildew.
- Hi-temperature black coating hides the connector while withstanding up to 350°F.
- FLARE adapters and flare nuts are plated with black to further reduce the visibility of the gas connection.

# Features and Specifications

- Tubing Annealed, 304 stainless steel (ASTM A240)
- Operating Temperature with adapters: -40°F to 350°F
- Operating Temperature with valves: -40°F to 125°F
- Flare nuts Brass or black plated steel
- · Adapters Black plated steel
- Approved for indoor/outdoor use with MAX operating pressure 0.5 psi
- Black coating withstands up to 350°F.
- 100% factory leak tested.
- When installing a new appliance or when an existing appliance is moved to a new location a NEW gas connector must be used per manufacturer's installation instructions and per product standards ANSI Z21.24/CSA 6.10 and ANSI Z21.75/CSA 6.27.

# MIP end FIP end Compared to the compared to

- Avoid repeated bending, flexing, movement or vibration. Do not use on portable gas generators due to excessive vibration
- Coating reduces glare and hides the connector from view
- Black adapters and flare nuts further reduce visibility of the connector
- Black coating withstands up to 350°F
- Exclusive No-Neck® design provides protection against stress fractures
- More corrugations per inch increase flexibility and extend service life

# Design Certifications and Approvals

- ANSI Z21.24/CSA 6.10 Connectors for Gas Appliances
- ANSI Z21.75/CSA 6.27 Connectors for Outdoor Appliances and Manufactured Homes
- City of New York MEA #376-92-M
- Approved by the Commonwealth of Massachusetts Board of State Examiners of Plumbers and Gas Fitters – connector length may not exceed 48"

#### **WARNING**

Installation and service MUST be performed by qualified installer. Read and follow all Dormont safety, use, sizing, installation and care instructions and follow all building codes, construction standards, appliance manufacturer recommendations and instructions, and applicable ANSI standards.

Connector Flow Capacity – **For Natural Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 0.64 SG., 1000 BTU per Cu. Ft. at 0.5 inch Water Column Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"
10A	3/8"	1/4"	48,000	43,800	40,000	36,400	33,400
20A	1/2"	3/8"	102,000	93,100	85,000	77,100	71,100

Connector Flow Capacity – **For Propane Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 1.55 SG., 2500 BTU per Cu. Ft. at 0.5 inch Water Column Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"
10A	3/8"	1/4"	76,800	70,080	64,000	58,240	53,440
20A	1/2"	3/8"	163,200	148,960	136,000	123,360	113,760



#### NOTICE



## Ultra Flow® HIGH BTU GAS CONNECTOR SPECIFICATIONS

# High BTU Stainless Steel Gas Connectors

# Features and Specifications

- Tubing Annealed, 304 stainless steel (ASTM A240)
- Flare nuts
   Brass or plated steel
- Adapters Plated Steel
- Optional coating Heavy-duty, antimicrobial, hot-dipped gray PVC (41, 51 & 61 series). Coating will not hold a flame.
- Approved for indoor/outdoor use with MAX operating pressure 0.5 psi
- Operating Temperature with adapters: -40°F to 350°F
- Operating Temperature with valves: -40°F to 125°F
- 100% leak tested
- When installing a new appliance or when an existing appliance is moved to a new location a NEW gas connector must be used per manufacturer's installation instructions and per product standards ANSI Z21.24/CSA 6.10 and ANSI Z21.75/CSA 6.27.
- Avoid repeated bending, flexing, movement or vibration. Do not use on portable gas generators due to excessive vibration
- Not suitable for moveable installations. Not NSF certified.

# Design Certifications and Approvals

- ANSI Z21.24/CSA 6.10 Connectors for Gas Appliances
- ANSI Z21.75/CSA 6.27 Connectors for Outdoor Appliances and Manufactured Homes
- City of New York MEA #376-92-M
- Approved by the Commonwealth of Massachusetts Board of State Examiners of Plumbers and Gas Fitters – connector length may not exceed 48".
- \* Tested and passed vibration criteria set forth in UL2200, section 35.1.3.3, "Stationary Engine Generator Assemblies," and UL536, section 7. "Flexible Metallic Hose."





## **Applications**

- Boilers
- · Gas Meters
- Furnaces
- Commercial

Designed for high BTU demand Exclusive No-Neck® design increases flexibility CSA design-certified

Durable 304 stainless steel tubing

More corrugations per inch increase flexibility and extend service life

#### Water Heaters

- Gas packs/Rooftop HVAC units
- Tankless Water Heater
- Stationary Standby Gas Generators\*
- Specifically designed for application with a significant BTU requirement. Can supply up to 1.5 million BTU (natural gas) or 2.4 million (propane), depending on length.
- Eliminates the need for pipe nipples, 90's and elbows.
- Pre-fabricated gas connector means no field threading, cutting or assembly of CSST fitting and tubing.
- Available with hot-dipped PVC coating with antimicrobial agent, SafetyShield yellow coating, or Stainless Steel.

#### **WARNING**

Installation and service MUST be performed by qualified installer. Read and follow all Dormont safety, use, sizing, installation and care instructions and follow all building codes, construction standards, appliance manufacturer recommendations and instructions, and applicable ANSI standards.

Connector Flow Capacity – **For Natural Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 0.64 SG., 1000 BTU per Cu. Ft. at 0.5 inch Water Column Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"	48"	60"	72"
40/41/40C	1"	3/4"	349,000	318,500	290,900	270,500	255,900	215,000	197,400	173,900
50/51	1-1/4"	1"	698,000	637,000	581,800	545,200	515,900	442,700	398,900	347,800
60/61	1-1/2"	1-1/4"	1,204,000	1,139,000	1,075,000	1,010,500	946,000	817,500	725,500	634,000

Connector Flow Capacity – **For Propane Gas** (per ANSI Z21.24/CSA 6.10 & ANSI Z21.75/CSA 6.27) Straight Length Capacity – BTU per Hr 1.55 SG., 2500 BTU per Cu. Ft. at 0.5 inch Water Column Pressure Drop

Series	Nominal OD (in)	Nominal ID (in)	12"	18"	24"	30"	36"	48"	60"	72"
40/41/40C	1"	3/4"	558,400	509,600	465,440	432,800	409,440	344,000	315,840	278,240
50/51	1-1/4"	1"	1,116,800	1,019,200	930,880	872,320	825,440	708,320	638,240	556,480
60/61	1-1/2"	1-1/4"	1 926 400	1 822 400	1 720 000	1 616 800	1 513 600	1 308 000	1 160 800	1.014.400

#### NOTICE





This is a representative list of certifications carried by Dormont Manufacturing. Not all products carry all certifications. Product certifications are listed on the applicable product page. Contact Dormont Manufacturing at 1-800-DORMONT for additional information.





#### Canadian Standards Association



ANSI Z21.24 /CSA6.10 Connectors for Gas Appliances

Connectors for Movable Gas Appliances ANSI Z21.69 /CSA 6.16

ANSI Z21.15 /CSA 9.1 Manually Operated Gas Valve for Appliances, Appliance

Connector Valves and Hose End Valves

ANSI Z21.93/CSA 6.30 Excess Flow Gas Valves

ANSI Z21.41 /CSA 6.9 Quick Disconnect Devices for use with Gas Fuel

ANSI Z21.18 /CSA 6.3 Gas Appliance Pressure Regulators

ANSI Z21.75 /CSA 6.27 Connectors for Outdoor Appliances and Manufactured Homes ANSI Z21.54/CSA 8.4 Gas Hose Connector for Portable Outdoor Gas Fired Appliances

ANSI Z21.90 /CSA.6.24 Gas Convenience Outlets and Operational Enclosures

ANSI/UL 567 Pipe Connectors for Flammable and Combustible Liquids and

LP-Gas. For use with natural gas and propane

#### **Additional Certifications**

NSF/ANSI 61 **Drinking Water System Components** Annex G, NSF/ANSI 61 Weighted Average Lead Content Evaluation NSF/ANSI/CAN 372 Drinking Water System Components Lead Content NSF/ANSI 169 Special Purpose Food Equipment and Devices IAPM0 TS9 Gas Supply Connectors for Manufactured Homes

Approved by the Commonwealth of Massachusetts Board of State Examiners of Plumbers and Gas Fitters.

Commonwealth of Massachusetts code requirements:

- Connector Length may not exceed 48"
- · Lever handle valves are not permitted

#### **Code Compliance:**

**ANSI Z223.1NFPA54** National Fuel Gas Code\* ICC International Fuel Gas Code\*

IAPMO/ANSI Uniform Plumbing Code (UPC) and

Uniform Mechanical Code (UMC)

B149.1 Natural Gas and Propane Installation Code- CSA Group



## DORMONT SHOWROOM AND POP ACCESSORIES

# **Call Dormont for POS information**

(800) 367-6668 (USA) (905) 332-4090 (Canada) (52) 81-1001-8600 (Latin America)

# Connect with Confidence®

# With Dormont, you—and your customers— gain the security of knowing...

- EVERY connector is backed by THE safe installation of more than 180 million gas connectors over 50 years.
- EVERY connector is 100% leak tested.
- Our products are specified by gas utilities, housing authorities, professional installers, and restaurant chains nationwide.
- Dormont makes each gas connector as if it were going to be installed in our own homes or businesses.
- Dormont provides competitive pricing without sacrificing quality.

With Dormont, you—and your customers— gain the quality assurance of...

- An ISO 9001:2015 registered U.S. manufacturer of gas connectors.
- State-of-the-art production facilities with proprietary equipment in Pittsburgh, Pennsylvania, USA.
- Expert factory-based technical support for installations.
- Exceeding the performance requirements required by CSA and the ANSI product standards.
- Consistent, world-class service and inventory support with 99% on-time shipping.

# Dormont Gas Connectors are proudly assembled in America.

Residential gas connectors and moveable FS connectors are assembled in USA from both foreign and domestic parts and components.

Dormont products are specified and preferred by gas utilities, housing authorities, professional installers, service technicians, architects, FCSI designers, appliance manufacturers and restaurant chains nationwide.



#### **TERMS AND CONDITIONS**

#### **TERMS**

Net 30 Days. Minimum order \$200 net. Orders below minimum and broken cartons are subject to a \$25.00 handling fee.

#### 1. ACCEPTANCE

If this writing differs in any way from the terms and conditions of Immediate Buyer's ("Buyer") order or if this writing is construed as an acceptance or as a confirmation acting as an acceptance, then Dormont's ("Seller") acceptance is EXPRESSLY MADE CONDITIONAL ON BUYER'S ASSENT TO ANY TERMS AND CONDITIONS CONTAINED HEREIN THAT ARE DIFFERENT FROM OR ADDITIONAL TO THOSE CONTAINED IN BUYER'S WRITING. Further, this writing shall be deemed notice of objection to such terms and conditions of Buyer. If this writing is construed as the offer, acceptance hereof is EXPRESSLY LIMITED TO THE TERMS AND CONDITIONS CONTAINED HEREIN. In any event, Buyer's acceptance of the goods shall manifest Buyer's assent to Seller's terms and conditions. No addition to or modification of these items will be effective unless set forth in writing and agreed to by Seller.

# 2. WARRANTIES AND REMEDIES

See Applicable Product Warranty.

#### 3. LIMITATIONS OF LIABILITY

The following limitations of Seller's liability are acknowledged by Buyer to be fair and reasonable and shall apply to any act or omission hereunder, and to any breach of this limited warranty.

#### a. Disclaimer of Damages

In no event shall Seller be liable for special, indirect, consequential or incidental damages, whether arising under contract, warranty, tort, negligence, strict liability or any other theory of liability. Such damages include but are not limited to loss of profits, loss of use of the goods, damage to property, and claims of third parties. Some states do not allow the exclusion or limitation of incidental or consequential damages, or any limitations on how long an implied warranty lasts, so the above exclusion or limitation may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

#### b. Replacement of Fittings

Buyer acknowledges that if Buyer replaces the adapter fittings supplied by Seller with fittings produced by another manufacturer, then all of Seller 's warranties to Buyer and to Remote Purchaser will be voided and Buyer will assume all liability for any damage, injury or loss suffered by Remote Purchaser arising out of this unauthorized modification.

#### c. Notice and Time of Claims

(i) Buyer agrees to check and inspect all products against shipping papers and for damage or shortage upon receipt of goods at destination; (ii) Every claim for loss, damage in transit, or other cause visible upon inspection shall be made with carrier. Claims for shortage must be made within five (5) days of receipt; (iii) Buyer expressly waives the statute of limitations and agrees that any legal proceeding for any breach of this limited warranty shall be waived unless held within two (2) years after the accrual of the cause of action therefor.

#### 4. SPECIAL PRODUCTS

Orders for special or modified products are non-cancelable. In the event that the customer cancels an order for such products, Watts shall charge the customer an amount equal to Watts' costs and expenses incurred in performing the purchase order prior to receipt of notice of cancellation.

#### 5. TERMS

Net 30 Days — minimum order of \$200. Interest on accounts overdue more than thirty (30) days will be charged at 2% per month or the highest rate permitted by law, whichever is lower. Orders below minimum and broken cartons are subject to a \$25.00 handling fee. Prices subject to change. Buyer shall be liable for any collection costs or attorneys' fees incurred as a result of Buyer's failure to pay its account on time.

#### 6. SHIPPING TERMS

Prepaid and allowed on \$2500 net and over. Under \$2500 net, shipments shall be F.O.B. factory. Buyer is responsible for all freight charges. The above shall apply only to shipments within the continental United States of America unless otherwise indicated by Seller. The method of shipment and carrier shall be selected by Seller.

#### 7. RETURNS

No returns are to be made to Seller without first obtaining a return authorization number. The return authorization number must be prominently displayed on the return packaging. Absolutely no returns will be accepted or credited without this prior approval. Returns are subject to 25% restocking charge plus any transportation charges incurred by Seller. Credits will be given only for items that are determined to be eligible for resale by Dormont Manufacturing.

#### 8. TAXES

The Buyer will pay, or reimburse Seller if it pays, any and all taxes or tariffs or any other similar charges imposed upon this contract, the goods covered hereby or the delivery or use or resale thereof.

#### 9. APPLICABLE LAW

All questions arising hereunder shall be interpreted and resolved in accordance with the Commercial Code of the Commonwealth of Pennsylvania without regard to its conflict of law provisions and excluding the United Nations Convention on the International Sale of Goods.

#### 10. INDEMNIFICATION

Buyer agrees to indemnify, hold harmless, and defend Seller from and against all claims and lawsuits, including attorney's fees, to the extent that Buyer's negligent acts or omissions to act cause injury, damage or loss to customers of Seller's products.



#### WARRANTY INFORMATION

# DORMONT MANUFACTURING Standard Limited Warranty and Disclaimers to End-Use (Remote) Purchasers:

Our product warranties are in many cases unique to each product or product family. We hope you find the appropriate warranty description(s) below helpful, but please consult with the appropriate technical literature for specific product warranty information.

Dormont Manufacturing warrants that the product and components manufactured by Dormont will be free from defects in material and workmanship. For all connectors, except commercial gas connectors, this limited warranty will be for two (2) years from the original date of purchase unless a different warranty period is offered by Dormont Manufacturing in writing for the applicable connector product. For commercial gas connectors, the limited warranty is for the lifetime of the appliance to which it is first connected. For Tankless Water Heater Service Valves and Water Supply Line Installation Kits, this limited warranty will be for one (1) year from the original date of purchase. HydroForce products are covered by a separate two (2) year warranty. This limited warranty only applies to a product in its original installation. There is no warranty for a product (1) that has been reused, (2) that is attached to an appliance that has been moved to a different location or (3) where original fittings supplied by Dormont have been changed or removed. Connectors and fittings are not to be reused under any circumstances. Dormont will replace, FREE OF CHARGE, during the applicable warranty period, its warranted product that it deems to be defective under normal installation, use and service. Dormont provides no warranty for components incorporated into its products that it does not manufacture and no warranty for products it does not manufacture. The only warranty extended for such products and components is that of the original manufacturer. Contact Dormont for more details on these other warranties. Replacement can be obtained by returning the product to the original place of purchase, along with the original receipt or proof of purchase. This remedy is exclusive and limited to product replacement only. Labor charges incurred in removal, installation, repair or replacement are excluded. Any damage to this product as a result of misuse, abuse, neglect, accident, improper installation, or any maintenance or use in violation of Dormont's instructions will void this limited warranty. In addition, Dormont disclaims responsibility for any damage, injury or loss caused by failures due to improper installation, use or maintenance. Product must be installed, used, repaired and maintained in accordance with Dormont's warnings and instructions, all National. State and Local codes and regulations. and standards set by the American National Standards Institute (ANSI). OTHER THAN THE ABOVE LIMITED WARRANTY, DORMONT MAKES NO ADDITIONAL WARRANTY OF ANY KIND, AND SPECIFICALLY DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY (INCLUDING WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE). IN THE ALTERNATIVE, DORMONT LIMITS ANY IMPLIED WARRANTY TO THE LENGTH OF THE LIMITED WARRANTY PROVIDED FOR THE PARTICULAR PRODUCT. Under no circumstances shall Dormont be liable for special, indirect, incidental or consequential damages resulting from use of this product whether the claim is based on breach of warranty or contract, negligence, or strict liability in tort even if Dormont could foresee or has been advised of the possibility of such damages. This warranty gives you specific legal rights, and you may also have other rights that vary from state to state. Some states do not allow limitations on how long an implied warranty lasts or the exclusion or limitation of incidental or consequential damages, so the above limitations or exclusions may not apply to you. Minimum order \$200USD net. Orders below minimum and broken cartons are subject to \$25.00 handling fee.

# DORMONT MANUFACTURING - Yellow and Black Coated Residential Connectors Limited Warranty:

#### **Warranties and Remedies**

A. Limited Warranty. Dormont Manufacturing Company ("Seller") warrants to Buyer that it holds and will pass marketable title to Yellow or Black powder-coated residential Antimicrobial Residential Connector (the "Product") sold hereunder. Seller further warrants to Buyer that the Product will be free from defects in material and workmanship during the life of the equipment to which the Product is originally connected or installed. Seller warrants to Buyer that any uncoated stainless-steel residential Antimicrobial Residential Connector and any components of any residential Antimicrobial Residential Connector manufactured by Seller other than the Product will be free from defects in material and workmanship for a period of two (2) years from tender of delivery to Buyer. For items not manufactured by Seller, the only warranty extended is that of the manufacturer or suppliers, if any.

B. Exclusions and Conditions. Seller's obligations with respect to the express warranties and remedies contained herein are conditioned on the following: (i) Seller's liability and Buyer's exclusive remedy is expressly limited to Seller's replacement of the Product or components at Seller's cost (excluding labor and freight); it being understood such replacement will be made only upon return of the defective item in accordance with Seller's shipping instructions and return authorization and subject to Seller's inspection; (ii) Buyer shall not assign its rights under these express warranties and any attempted assignment shall render such warranties, but not any disclaimers or limitations, null and void and the Product and components shall be assigned AS IS; and (iii) the Product and components shall be carefully inspected for damage by Buyer upon receipt, be installed by individuals trained and certified as professionals with respect to such installation, and be installed, used, repaired and maintained by Buyer in accordance with local codes or regulations, standards set by American National Standard Institute and/or American Gas Association Standards. This limited warranty shall apply only to the original installation of the Product and components only and the express warranties and remedies contained herein shall not apply to, and shall be null and void and of no further force or effect upon, damage and/or failure of the Product or components caused by or resulting from shipping; improper or unauthorized handling, installation, alteration or repair; misuse, abuse or other occurrences or conditions other than normal use thereof: application or conformity to local codes or regulations not previously made known to Seller; or accident or other casualty.

OTHER THAN THE ABOVE LIMITED WARRANTY, SELLER MAKES NO ADDITIONAL WARRANTY OF ANY KIND, AND SPECIFICALLY DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY (INCLUDING WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE).

#### Conditions

#### **Limitations of Liability**

The following limitations of Seller's liability are acknowledged by Buyer to be fair and reasonable and shall apply to any act or omission hereunder, and to any breach of this limited warranty.

#### **Disclaimer of Damages**

In no event shall Seller be liable for special, indirect, consequential or incidental damages, whether arising under contract, warranty, tort, negligence, strict liability or any other theory of liability. Such damages include but are not limited to loss of profits, loss of use of the goods, damage to property, and claims of third parties. Some states do not allow the exclusion or limitation of incidental or consequential damages, or any limitations on how long an implied warranty lasts, so the above exclusion or limitation may not apply to you. This limited warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

#### **Notice and Time of Claim**

- (i) Buyer agrees to check and inspect all products against shipping papers and for damage or shortage upon receipt of goods at destination;
- (ii) Every claim for loss, damage in transit, or other cause visible upon inspection shall be made with carrier. Claims for shortage must be made within five (5) days of receipt;
- (iii) Buyer expressly waives the statute of limitations and agrees that any legal proceeding for any breach of this limited warranty shall be waived unless held within two (2) years after the accrual of the cause of action therefor.

# Give us a Challenge

Don't see exactly what you're looking for? No problem.

Just because it doesn't currently exist doesn't mean we can't make it. Our design solutions team is ready and able to help you bring your idea to life. Whether its sourcing an existing product or designing a new one, we are here to facilitate your needs. Getting started is easy.

- 1. Contact Us
- 2. We'll search for the product you need
- 3. If we find it, we'll get it to you. If not, we will design it for you.

# **More Than Just Gas**

Our product offering extends beyond the gas industry. Some other applications we support include, but aren't limited to:

Oil | Protective Covering | Water & Steam | Conduit



Get in contact with us today and put us to the test.

Connect with Dormont | Connect with Confidence®



# **Watts Family of Brands**

Watts designs, manufactures, and sells an extensive line of flow control, water safety, water filtration & treatment, drainage, and PEX plumbing products.

The Watts family of companies provides a single source for solutions used to safely convey, conserve, and manage water.

Making Watts your single source for plumbing-related solutions will streamline your operations, save you money, and reduce the variety of repair parts needed for maintenance.





