

T498 Electric Heating Thermostats

Honeywell



KEY FEATURES

- Includes long-lasting Micro Switch™ mechanism
- Integrated thermometer indicates room temperature
- Easy to install – color-coded leads
- Well-suited for upgrades and high-end new constructions
- Bimetallic temperature sensor
- Rugged plastic mounting base
- Mount on 2 in. x 4 in. outlet box or on 4 in. x 4 in. junction box



ACCESSORIES:

272804A Range Stop and Locking Screws Assembly

	T498A1778	T498A1810	T498B1512	T498B1553
Ratings	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac	22 A res. @ 120/208/240Vac 19 A res. @ 277 Vac
Temperature marking	°F	°F	°F	°F
Color	Premier White®	Brush Gold Finish	Brush Gold Finish	Brush Gold Finish
Switching action	SPST	SPST	DPST	DPST
Setting temp. range	40°F to 80°F	40°F to 80°F	40°F to 80°F	40°F to 80°F
Differential temperature	3°F	3°F	3°F	3°F
Includes	Range stops and locking cover and extra knob decal for recalibration	---	Positive OFF, Range stops, locking cover and extra knob decal for recalibration	Positive OFF