Residential Expansion Tanks

TK300 Series Expansion Tanks- Heating



TK300-60/U

TK300-90/U

Maximum Operating Temperature: 240 F (115 C)
Maximum Operating Pressure: 100 psi (689 kPA)

1/2 in.

1/2 in.

Honeywell Expansion Tanks are designed to absorb hot water expansion in closed heating systems. They are equipped with butyl diaphragms to separate the air from the system water (glycol). The tanks are a welded, not clamped design. Pre-pressurized at 12 psi, the tank keeps fluids circulating and maintains minimum system pressure. Honeywell tanks resist waterlogging, loss of pressure through relief valve spills, loss of BTUs and reduce circulator running time. Use the super efficient Honeywell PowerVent or air vents to remove air and micro-bubbles from the system for maximum performance.

- Butyl/EPDM diaphragm- 9 times better than natural rubber
- Deep-drawn steel tank
- Controls system pressure
- · Air-tight cushion-factory pre-charged to 12 psig and 100% tested

2.5 gal

11.5 gal

9.5 L

40.1 L

14 lb

23 lb

6.4 kg

10.4 kg

Materials: steel shell, heavy duty butyl diaphragm

28.8 L

53.1 L

Connection Type: Male NPT Comments: Heating

7.6 gal

14.0 gal

Maximum Diameter Height Volume **Acceptance Volume Weight** Connection **Product Number** inch L Size (inch) inch mm mm gal gal lb TK300-15/U 1/2 in. 8 in. 203.2 mm 12 5/8 in. 321 mm 7.6 L 3.8 L 2.3 kg 2.0 gal 1 gal 5 b TK300-30/U 1/2 in. 279 mm 15 1/2 in. 11 in. 16.7 L 2.5 gal 9.5 L 9 b 394 mm 4.4 gal 4.1 kg

584 mm

533 mm

23 in.

21 in.

279 mm

390.5 mm

Expansion Tank Sizing based on BTU's

11 in.

15 3/8 in.

Boiler Net Output in 1000's of BTU/Hr MBH	Type of Radiation			
	Finned Tube Baseboard or Radiant Panel Use Model	Convectors or Unit Heaters Use Model	Radiators Cast Iron Use Model	Baseboard Cast Iron Use Model
50	TK300-15	TK300-15	TK300-30	TK300-30
75	TK300-30	TK300-30	TK300-30	TK300-60
100	TK300-30	TK300-30	TK300-60	TK300-60
125	TK300-30	TK300-60	TK300-60	TK300-90
150	TK300-30	TK300-60	TK300-90	TK300-90
175	TK300-60	TK300-60	XPS-030V	XPS-030V
200	TK300-60	TK300-60	XPS-030V	XPS-030V
250	TK300-60	TK300-90	XPS-030V	XPS-040V
300	TK300-90	XPS-030V	XPS-030V	XPS-040V
350	XPS-030V	XPS-030V	XPS-040V	XPS-060V
400	XPS-030V	XPS-040V	XPS-040V	XPS-060V

230 customer.honeywell.com 70-6910