


C

Multi-Discs

Angled Design (Type 29)



Zirconium abrasive grain provides consistent high cut rate, runs cooler and lasts longer than aluminum oxide



Phenolic backing prevents backing from scratching work surface

Angled design for increased contact area

- For metal, wood, and plastic

General Purpose Depressed Center Wheels (Angled Type 29)



LASTS 20X LONGER
THAN RESIN FIBER DISCS

- Ensures 90% of the abrasive material is in contact with the work surface, providing superior cut rate and maximum disc life.
- For weld head blending, removing weld slag, deburring, edge blending, surface conditioning, and metal fabrication
- Works at 10° to 25° angle

Diameter	Arbor	Grit	Max. RPM	Model	Carded Part #	10/Pkg. Part #
4"	5/8"	36	11,200	GA4030	741840-A	741810-B-10
4"	5/8"	60	11,200		741841-A	741811-B-10
4"	5/8"	80	11,200		741842-A	741812-B-10
4"	5/8"	120	11,200		741843-A	741813-B-10
4-1/2"	7/8"	36	11,000	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06	741844-A	741814-B-10
4-1/2"	7/8"	60	11,000		741845-A	741815-B-10
4-1/2"	7/8"	80	11,000		741846-A	741816-B-10
4-1/2"	7/8"	120	11,000		741847-A	741817-B-10
5"	7/8"	36	10,400	9558PB, 9565CV/PC, GA5010Z, GA5020/Y		741818-B-10
5"	7/8"	60	10,400			741819-B-10
5"	7/8"	80	10,400			741820-B-10
5"	7/8"	120	10,400			741821-B-10
7"	7/8"	36	6,600	GA7001L, GA7011C, GA7020, GA7021, GA7031Y, GA7040S	741848-A	741822-B-10
7"	7/8"	60	6,600		741850-A	741823-B-10
7"	7/8"	80	6,600			741824-B-10
7"	7/8"	80	6,600			741824-B-10

General Purpose Hubbed Wheels (Angled Type 29)



- For metal, wood, and plastic
- Works at 10° to 25° angle

Diameter	Arbor	Grit	Max. RPM	Model	Carded Part #	10/Pkg. Part #
4-1/2"	5/8" - 11	36	11,000	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06		741832-B-10
4-1/2"	5/8" - 11	60	11,000			741833-B-10
4-1/2"	5/8" - 11	80	11,000			741834-B-10
4-1/2"	5/8" - 11	120	11,000			741835-B-10
7"	5/8" - 11	36	6,600	GA7001L, GA7011C, GA7020, GA7021, GA7031Y, GA7040S		741836-B-10
7"	5/8" - 11	80	6,600			741838-B-10

Flat Design (Type 27)



Zirconium abrasive grain provides consistent high cut rate, runs cooler and lasts longer than aluminum oxide



Phenolic backing prevents backing from scratching work surface

Flat design great for use on joints, corners and edges

General Purpose Depressed Center Wheels (High Density Flat Type 27)



LASTS 30X LONGER
THAN RESIN FIBER DISCS

- For metal, wood, and plastic
- Conforms to flat or irregular surfaces
- Excellent finish consistency at a working angle of 0° to 15°

Diameter	Arbor	Grit	Max. RPM	Model	Carded Part #	10/Pkg. Part #
4-1/2"	7/8"	40	11,000	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06		741826-B-10
4-1/2"	7/8"	60	11,000			741827-B-10
4-1/2"	7/8"	80	11,000			741828-B-10
7"	7/8"	40	6,600	GA7001L, GA7011C, GA7020, GA7021, GA7031Y, GA7040S		741829-B-10
7"	7/8"	60	6,600			741830-B-10
7"	7/8"	80	6,600			741831-B-10

Masonry Depressed Center Wheels (Flat Type 27)



- For brick, stone and concrete

Diameter	Arbor	Grit	Max. RPM	Model	Carded Part #	10/Pkg. Part #
4"	5/8"	24	13,000	GA4030	A-90130	
4-1/2"	7/8"	24	12,000	9557NB/PB, 9564CV/PC/P, GA4530, GA4534, XAG01, XAG03, XAG06	A-90249	

Warning: Consult owner/operator manual and adhere to all safety precautions for accessory items. Always use recommended guards. Failure to do so may result in serious injury or death from exploding wheels. Refer to ANSI B7.1 and owner/operator manual for proper accessory mounting and grinding procedures. Always wear eye protection that meets ANSI Z87.1 requirements plus a face shield wherever possible. Tools must always be properly guarded.