



WARDFLEX® Flush Mount Gas Valve Kit

Ward Manufacturing, LLC.
117 Gulick Street
Blossburg, PA 16912
Tel. (800)248-1027
www.wardmfg.com

Description:

The 3/8" thru 1-1/4" WARDFLEX® tubing is terminated using the patented, STEPSAVER double seal fitting. The 1-1/2" and 2" tubing utilize the WARDFLEX® traditional gasketed fitting design. Only fittings designed and listed for use with the WARDFLEX® and WARDFLEX® MAX CSST Piping Systems shall be used when connecting to the flexible piping.

Features:

- Provides flush mount termination for appliance connections
- Easy Installation

Components:

- Valve Body
- Retainer Ring
- Adapter Nut
- Gasket
- Box
- Cover

Listings:

- CSA: File# 112940_0_000
- IAPMO: File# 3353
- ICC: Report# ESR-1879

Technical Data:

General

Certified Operating Pressure	25 psi
------------------------------	--------

Material

Body, Retainer Ring & Adapter Nut	Brass
Valve Handle	Steel (Painted Yellow)
Gasket	Composite Fiber
Box and Cover	ABS, white



Dimensions

Price Sheet Item #	CSST Size	NPT Size	Nut Hex	Box Dimensions	Approximate Weight (lbs)
701	1/2"	1/2"	1-3/16"	6.80"H x 6.80"W x 3.10"D	1.25
702	3/4"	1/2"	1-1/2"	6.80"H x 6.80"W x 3.10"D	1.40
703	3/4"	3/4"	1-1/2"	6.80"H x 6.80"W x 3.10"D	1.58